



Your PDF Guides

You can read the recommendations in the user guide, the technical guide or the installation guide for ALPINE CVA-1005. You'll find the answers to all your questions on the ALPINE CVA-1005 in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

User manual ALPINE CVA-1005
User guide ALPINE CVA-1005
Operating instructions ALPINE CVA-1005
Instructions for use ALPINE CVA-1005
Instruction manual ALPINE CVA-1005

CVA-1005
Mobile Multimedia Station/Receiver/AI-NET Controller

FEATURES

Tuner
MaxTune SQ Tuner
Preset Stations (FM/12/AM-6/DAP-6)
D.A.P. (Direct Access Preset)
Auto Memory
High Speed Tune
Travel Search
Local/DX Selection
FM Station Indicator
Up/Down Seek
Signal Level Indicator
Station Title Memory
Title Search Menu
Mono Switch

CD Shuttle Control
Music Sensor Up/Down
Forward/Backward
Disc Play/Pause
M.I.X. (Random Play)
Music Scan
Repeat
Direct Disc Selection
Disc Title Memory
T.S.M. (Title Search Menu)
Elapsed Time Display

AI-Net
External Processor Audio Full Control
External Processor Preset Function
Preset
As-Track Display
Multi-CD Shuttle Control
M.I.X. All

General
CD Shuttle Control Function
40W x 4 High Power Amplifier
Dual In
3 Pre-Outs
Subwoofer Level Control
Selectable Fader
Preset Fader
Loudness
Separate Bass & Treble Control
S.T.M. (Source Tone Memory)
Tone System
Demo Function
Sound Guide
Operation Indicator
Preset Encoder Volume Knob
Clock
Wireless Remote Control Included
Gold-Plated RCA Connectors
Dimension Lead
Power Antenna Lead



MP3 **SH-SHOCK** **40Wx4** **CD TEXT** **EXTRA** **EL-Processor**

SPECIFICATIONS

Monitor
Screen Size 6.5" (Diagonal)
LCD Type Transparent TN LCD
Operation System TFT Active Matrix
Number of Picture Elements 336,960 pels. (1,440 x 234)
Illumination System U-shaped cold cathode fluorescent tube

FM Tuner
Tuning Range 87-107.9MHz
Mono Usable Sensitivity 0.3dBf (0.8µV/75 ohms)
50dB Quieting Sensitivity 13.5 dBf (1.3µV/75 ohms)
Alternate Channel Selectivity 80.0 dB
Signal-to-Noise (S/N) 80.0 dB
Stereo Separation 35.0 dB
Capture Ratio 2.0 dB

AM Tuner
Tuning Range 530-1,710kHz
Usable Sensitivity (IEC Standard) 22.5/27.0 (µV/dBf)

Remote Control
Model Number RUE-416.5
Battery 2 x "AA"
Dimensions (W x H x D)mm 45mm x 45mm x 135mm
Dimensions (W x H x D)in 1-3/4" x 1-3/4" x 5-1/4"

General
Power Requirement 14.4(11-16) V.DC
Operating Temperature (°C/°F) +32°F to 113°F (0°C to +45°C)
Maximum Power Output (Note 1) 40W x 4
Continuous Power Output (Note 2) 19W x 4
Pre-Output Voltage (Before Clipping) 2V
Bass Control Range at 60Hz ±15 dB
Treble Control Range at 10kHz ±10 dB
Loudness Control at 100Hz (Max) +10dB



[You're reading an excerpt. Click here to read official ALPINE CVA-1005 user guide](#)

<http://yourpdfguides.com/dref/2444748>

Manual abstract:

I.X. (Random Play) Music Scan Repeat Direct Disc Selection Disc Title Memory T.S.M. (Title Search Menu) Elapsed Time Display Ai-Net External Processor Audio Full Control External Processor Preset Function Recall Ai-Talk Display Multi CD Shuttle Control M.I.X. ALL General CD Shuttle Control Function 40W x 4 High Power Amplifier Dual-In 3 PreOuts Subwoofer Level Control Selectable Fader Preamp Fader Loudness Separate Bass & Treble Control S.T. M.(Source Tone Memory) Tone Bypass Demo Function Sound Guide Operation Indicator Rotary Encoder Volume Knob Clock Wireless Remote Control Included Gold-Plated RCA Connectors Dimmer-on Lead Power Antenna Lead ENT DISP LIST SOURCE MENU BAND CANC. A.PROC DEFEAT MUTE VOICE LIST TUNER N/H DETOUR DISC MP/RG PLAN CHG POWER V.SEL DISP ON/OFF DEL DEST. S P E C I F I C A T I O N S Monitor Screen Size.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

6.5" (Diagonal) LCD Type

...Transparent TN LCD Operation System

...TFT Active Matrix Number of Picture Elements..

...336,960 pcs. (1,440 x 234) Illumination System

...U-shaped cold cathode fluorescent tube FM Tuner Tuning Range..

.....
.....
.....

.....
.....
.....
.....

.....87.

7-107.9MHz Mono Usable Sensitivity....

.....
.....

.....
.....
.....
.....

.....9.3dBf (0.8μV/75 ohms) 50dB Quieting Sensitivity.

.....
.....
.....

.....
.....
.....
.....

.13.5 dBf(1.3μV/75 ohms) Alternate Channel Selectivity

.....
.....
.....

.....
.....
.....
.....

.....
.....

80.0 dB Signal-to-Noise (S/N)....

.....

.....
.....
.....
.....

.....
.....
.....
.....

.....80.0 dB Stereo Separation ..

.....
.....
.....

.....
.....
.....
.....

.....
.....
.....

.....
.....35.0 dB Capture Ratio

.....
.....
.....

.....
.....
.....
.....

.....
.....
.....
.....

.....2.0 dB AM Tuner Tuning Range .

.....
.....
.....

.....
.....
.....

.....
.....
.....
.....

.530-1, 710kHz Usable Sensitivity (IEC Standard)

.....
.....
.....

.....
.....
.....

.22.5/27.0 ($\mu\text{V}/\text{dBf}$) Remote Control Model Number

.....
.....
.....
.....

.....
.....
.....

.....
.....
.....

RUE-4165 Battery

.....
.....
.....
.....

.....
.....
.....
.....

.....
.....
.....
.....

2 x "AA" Dimensions (W x H x D)mm.....

.....
.....
.....

.....
.....
.....

45mm x 45mm x 135mm Dimensions (W x H x D)in

.....
.....
.....
.....

1-3/4" x 1-3/4" x 5-1/4" General Power Requirement

.....
.....

.....
.....
.....

.....
.....
.....

.14.4(11-16) V.DC Operating Temperature (°C/°F).....

.....
.....
.....

.....+32°F to 113°F (0°C to + 45°C) Maximum Power Output (Note 1) ..

.....
.....
.....

.....
.....
.....

..40W x 4 Continous Power Output (Note 2).....

.....
.....
.....

.....
.....
.....

.....19W x 4 Pre Output Voltage (Before Clipping)

.....
.....
.....

.....
.....

