



# Your PDF Guides

You can read the recommendations in the user guide, the technical guide or the installation guide for BEHRINGER MX2442A. You'll find the answers to all your questions on the BEHRINGER MX2442A in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

User manual BEHRINGER MX2442A  
User guide BEHRINGER MX2442A  
Operating instructions BEHRINGER MX2442A  
Instructions for use BEHRINGER MX2442A  
Instruction manual BEHRINGER MX2442A

**MX2442A**

**EURODESK®**

Technical Specifications

Version 1.2 May 2002

ENGLISH



[You're reading an excerpt. Click here to read official BEHRINGER MX2442A user guide](http://yourpdfguides.com/dref/2302054)  
<http://yourpdfguides.com/dref/2302054>

**Manual abstract:**

0 dBu, 150 Ohm source 117.3 dBqp, 150 Ohm source 132.0 dBu, input shorted 122.0 dBqp, input shorted 0,007% @ +4 dBu, 1 kHz, bandwidth 80 kHz +10 dB to +60 dB +12 dBu Electronically balanced Unity to +40 dB +22 dBu +10 dB to -85 dB From off to Unity to +15 dB 12 kHz +/-15 dB, Q fixed at 2 oct. 3 kHz +/-15 dB, Q fixed at 2 oct. 100 Hz - 8 kHz +/-15 dB, Q fixed at 1 oct. 500 Hz +/-15 dB, Q fixed at 2 oct. 80 Hz +/-15 dB, Q fixed at 2 oct. 75 Hz, 18 dB/oct. +22 dBu -95 dB @ 1 kHz Bus noise @ fader 0 dB: -105.

0 dBr (ref.: +4 dBu); -92.0 dBr (ref.: +4 dBu, all input channels assigned, Unity gain, channels muted); -87.0 dBr (ref.

: +4 dBu, all input channels assigned, Unity gain) +22 dBu balanced/unbalanced +10 dB to -85 dB Bus noise @ fader 0 dB: -102.0 dBr (ref.: +4 dBu); -92.0 dBr (ref.: +4 dBu, all input channels assigned, Unity gain, channels muted); -87.

0 dBr (ref. @@@@ @ 2 1/8" / 3 13/16" x 28 3/8" x 19 1/2" (approx. 54 / 97 mm x 720 mm x 495 mm) Weight approx. 12 kg (H x W x D) Power Supply Unit approx. 3 1/2" x 17 1/8" x 9 3/4" (approx. 86 mm x 435 mm x 246 mm) Weight approx. @@@@ @ @ BEHRINGER and EURODESK are registered trademarks. ALL RIGHTS RESERVED. © 2002 BEHRINGER Spezielle Studioteknik GmbH. BEHRINGER Spezielle Studioteknik GmbH, Hanns-Martin-Schleyer-Str.

36-38, 47877 Willich-Münchheide II, Germany Tel. +49 (0) 21 54 / 92 06-0, Fax +49 (0) 21 54 / 92 06-30 5 .



[You're reading an excerpt. Click here to read official BEHRINGER](#)

[MX2442A user guide](#)

<http://yourpdfguides.com/dref/2302054>