



Your PDF Guides

You can read the recommendations in the user guide, the technical guide or the installation guide for BEHRINGER PMP960M. You'll find the answers to all your questions on the BEHRINGER PMP960M in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

User manual BEHRINGER PMP960M
User guide BEHRINGER PMP960M
Operating instructions BEHRINGER PMP960M
Instructions for use BEHRINGER PMP960M
Instruction manual BEHRINGER PMP960M

PMP980S/PMP960M

6/10 x 2 Live Powered Mixers

- ▶ PMP980S: Ultra-compact 2 x 450-Watt stereo powered mixer
- ▶ PMP960M: Ultra-compact 2 x 450-Watt dual mono powered mixer
- ▶ Revolutionary amplifier technology: enormous power, incredible sonic performance and super-light weight
- ▶ PMP980S: 10-channel mixer section features 6 mono channels and 2 stereo channels plus separate tape returns
- ▶ PMP960M: 6 mono channels plus separate tape returns
- ▶ PMP980S: 2 studio-grade 24-bit stereo FX processors with 100 awesome presets
- ▶ PMP960M: 1 studio-grade 24-bit stereo FX processor with 100 awesome presets
- ▶ FBQ Feedback Detection system instantly reveals critical frequencies for easy feedback removal
- ▶ 8/6 high-quality mic preamps with switchable +48V phantom power for condenser microphones
- ▶ Effective, extremely musical 3-band EQ, switchable Pad and Clip LEDs on all mono channels
- ▶ Stereo 7-band graphic EQ allows precise frequency correction of monitor and main outputs
- ▶ Speaker Processing function adjusts frequency response to match professional speaker systems like BEHRINGER EUROLIVE series

behringer.com

Powered Mixers

EUROPOWER — 900-Watt 10-Channel/6-Channel Mixer with FX



If you need superior sound quality for small club gigs, churches or speeches, but have to keep the outboard gear to a minimum, get ready to love the PMP980S and PMP960M. The 900-Watt, 10-channel/6-channel mixers give you everything you need in one efficient, highly portable little package.

Massive mono or stunning stereo

The difference between these two mixers is that the PMP980S gives you two stereo channels. If you make your band at a barbecue joint, you probably aren't that interested in making a space-age, multi-dimensional mix. This is just one example of where the PMP960M's six mono channels would be a perfect match.

band at a barbecue joint, you probably aren't that interested in making a space-age, multi-dimensional mix. This is just one example of where the PMP960M's six mono channels would be a perfect match.

However, if you're the brains behind a kraut-rock band with the wildest patches this side of Berlin, the two additional stereo channels on the PMP980S will provide the sonic latitude you need.

The PMP980S is also an excellent choice for a church, where vocals and stereo recordings share face time.

Continued on next page



[You're reading an excerpt. Click here to read official BEHRINGER PMP960M user guide](#)

<http://yourpdfguides.com/dref/2302586>

2.2 k balanced / 1.

1 k unbalanced 110 dB / 114 dB A-weighted (0 dBu In @ +10 dB gain) 0.001% / 0.0007% A-weighted MAIN MIX SYSTEM DATA Noise: MAIN MIX @ -oo Channel fader -oo MAIN MIX @ 0 dB Channel fader -oo MAIN MIX @ 0 dB Channel fader @ 0 dB LOUDSPEAKER OUTPUTS Type Load impedance: MAIN L/R MONITOR/MAIN MONO MAIN MONO/MAIN MONO BRIDGE DSP Converter 1/4" TRS connectors, unbalanced approx. 100 k, unbalanced +21 dBu +21 dBu RCA approx. 1 k +21 dBu DIMENSIONS/WEIGHT Dimensions (H x W x D) PMP980S MICROPHONE INPUTS Type Mic E. I.N. (20 Hz - 20 kHz) @ 0 Ohm source resistance @ 50 Ohm source resistance @ 150 Ohm source resistance Frequency response Gain Max. @@input level STEREO LINE INPUTS Type Impedance Max. @@output level MONITOR Type Impedance Max.

output level STEREO OUTPUTS Type Impedance Weight 12.4 in x 18.1 in x 8.7 in 32.7 lb Order via the BEHRINGER 24/7 Dealer Portal or contact the BEHRINGER location nearest you: BEHRINGER Australia tel.: +61 3 9877 7170, fax: +61 3 9877 7870 BEHRINGER Germany tel.: +49 2154 9206 4149, fax: +49 2154 9206 4199 BEHRINGER Japan tel.: +81 3 5281 1180, fax: +81 3 5281 1181 BEHRINGER Singapore tel.: +65 5845 1800, fax: +65 6214 0275 BEHRINGER USA / CANADA tel.: +1 425 672 0816, fax: +1 425 673 7647 behringer.

com ©2009 Red Chip Company Ltd. All rights reserved. @@@@and other countries. Windows is a registered trademark of Microsoft Corporation in the United States and other countries. ASIO is a trademark and software of Steinberg Media Technologies GmbH. VST is a trademark of Steinberg Media Technologies GmbH. AMD is a trademark or registered trademark of Advanced Micro Devices, Inc. Intel is a trademark or registered trademark of Intel Corporation or its subsidiaries in the United States and other countries. energyXT2, energyXTC and the energyXT logo are trademarks of XT Software AS incorporated in Norway, and are protected under the laws of Norway, and are being used under license by Behringer Holdings (Pte) Ltd and related companies. 985-10000-00393 .



[You're reading an excerpt. Click here to read official BEHRINGER PMP960M user guide](http://yourpdfguides.com/dref/2302586)
<http://yourpdfguides.com/dref/2302586>