



Your PDF Guides

You can read the recommendations in the user guide, the technical guide or the installation guide for FRIGIDAIRE FAFW4011L. You'll find the answers to all your questions on the FRIGIDAIRE FAFW4011L in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

User manual FRIGIDAIRE FAFW4011L
User guide FRIGIDAIRE FAFW4011L
Operating instructions FRIGIDAIRE FAFW4011L
Instructions for use FRIGIDAIRE FAFW4011L
Instruction manual FRIGIDAIRE FAFW4011L

FRIGIDAIRE
affinity.

Front Load Washers
FAFW4011L B/W

7 Wash Cycles
3.47 D.O.E. Cu. Ft./
4.0 I.E.C. Cu. Ft.

Product Dimensions
Height 36"
Width 27"
Depth 30-5/8"

More Easy To Use Features
Express-Select® Controls
Every select, selects with the touch of a button.
SilentDesign™
Designed for quiet operation.
Stay-Fresh™ Door Seal
Optional Pedestal Drawer

ENERGY STAR

Available in:
Classic Black (CB) Classic White (CW)

Based on a 12.0 lb. load as tested per DOE Method 1009#20, subject to Appliance #13.

Signature Features

- Vibration Control System**
Advanced vibration control technology keeps wash loads balanced for smooth, quiet operation ideal for second floor installation.
- TimeWise® Technology**
TimeWise technology senses wash time and adjusts dry time – so you don't wait for clothes to dry.
- Fresh Water Rinse Option**
An additional rinse cycle uses advanced rinse technology to effectively reduce detergent and address.
- Energy Saver Option**
Further reduces energy use up to 35%!

frigidare.com



[You're reading an excerpt. Click here to read official FRIGIDAIRE FAFW4011L user guide](http://yourpdfguides.com/dref/3940792)
<http://yourpdfguides.com/dref/3940792>

Manual abstract:

47 D.O.E. Cu. Ft./ 4.0 I.E.C. Cu.

@ @load as tested per DOE Protocol 10CFR430, subpart B, App. @ @Ideal for second floor installation. TimeWise® Technology TimeWise® technology ensures wash time equals dry time -- so you don't wait for clothes to dry. Fresh Water Rinse Option An additional rinse cycle uses advanced rinse technology to effectively reduce detergents and additives. Energy Saver Option Further reduces energy use up to 35%.

1 frigidaire.com Front Load Laundry - Washer Load Washers Front Frigidaire Affinity (L models) FAFW4011L B/W Features Total Capacity D.O.E./I. E.C. (Cu.Ft.) Controls Washer Drum Interior Interior Light/Door Trim Vibration Control System Wash System Advanced Rinse Technology TimeWise® Technology Ready Clean™/Ready Steam™ Fresh Water Rinse Option Stay-Fresh™ Door Seal Automatic Temperature Control Automatic Water Level Adjustments Auto Prewash Detergent Dispenser Auto Bleach Dispenser Auto Detergent Dispenser Auto Fabric Softener Dispenser Time Remaining Indicator Cycle Status Lights Cycle Signal/Cycle Signal "On/Off" Cycle Signal Volume Control Door Lock Indicator Light Control Lock/Stay-Put Door Start/Pause/Cancel Buttons Energy Saver Option Delay Start Integral Water Heater Tumble Speed (RPM) Spin Speed (Maximum RPM) Sound Package Adjustable Leveling Legs 33/47 1100 SilentDesign™ Yes Yes Yes Yes Yes Yes Chime/Yes Yes Yes Yes/Yes Yes Yes 1 to 10 Hours Yes Yes Yes Yes 3.47/4.0 Express-Select® Stainless Steel Yes/Color-Coordinated Yes Tumble Action Yes Yes 3.47 D.O.E.

Cu. Ft./4.0 I.E.C. Cu. Ft. B C A B C Cycles Wash Cycles/Specialty Cycles 7/0 A Options Water Temperature Selections Water Levels Spin Speed/Soil Level Selections Allergen 5 Automatic 5/3 Optional Accessories Dryer Stacking Kit 15" Frigidaire Affinity® Pedestal Drawers Classic Red (R) Classic Blue (N) Classic Silver (A) Classic Black (B) Classic White (W) Mobile Home Installation Kit Drain Hose Extension Kit (B) PN# CFPWD15B (W) PN# CFPWD15W PN# 137067200 PN# 137098000 NOTE: For planning purposes only. Always consult local and national electric and plumbing codes.

Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.com. PN# STACKIT4X Certifications ENERGY STAR® NSF® Certified Sanitize/Allergen Yes Product Dimensions A-Height (Single) Height (Stacked) B-Width Right Top Rear Left Top Rear 120V/60Hz/15A 1,000/8 20 222 Lbs. C-Depth Depth with Door Open 90° 36" 71-1/2" 27" 30-5/16" 51-7/16" Specifications Power Supply Connection Location Water Inlet Connection Location Voltage Rating Watts @ 120 Volts/Amps @ 120 Volts Minimum Circuit Required (Amps) Shipping Weight (Approx.) 1 Pedestal Dimensions A-Height B-Width C-Depth 15-1/4" 27" 26-1/4" Connected Load (kW Rating) @ 120 Volts 1 l.

4 For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded for safe operation. Accessories information available on the web at frigidaire.com USA · 10200 David Taylor Drive · Charlotte, NC 28262 · 1-800-FRIGIDAIRE · frigidaire.com CANADA · 5855 Terry Fox Way · Mississauga, ON L5V 3E4 · 1-800-265-8352 · frigidaire. ca FAFW4011L 04/11 © 2011 Electrolux Home Products, Inc. Specifications subject to change. Printed in the U.S.A. Frigidaire Affinity (All L Models excluding FAFW4221L) Front Load Washers FAFW4011L B/W 3.47 D.O.E. Cu.

Ft./4.0 I.E.C. Cu. @ @ @ @To minimize vibration or required. @ @ @ @60" long. @ @ @ @ @ @ @ @ (Refer to Built-In Installations on this page for cutout dimensions. @ @ in.

each, located 3" from top and bottom of door. Full-length 120 sq. in. opening also acceptable. @ @ · Do NOT install in area exposed to dripping water or outdoor weather conditions, or where gasoline or other flammables, including automobiles, are kept or stored.

movement, reinforcement of floor may be necessary. Do NOT install on carpeted surface. · Leveling legs supplied to level washer properly and reduce excessive noise and vibration. · H/C water faucets MUST be installed within 42" of washer's water inlet and MUST be 3/4" to connect to 43" inlet hoses. · Water pressure MUST be between 30 and 120 psi with NOT more than 10 psi pressure difference between hot and cold.

· Drain required with standpipe diameter of 1-1/4" min. and height of 24" min./96" max. above floor, capable of eliminating 17 gallons per minute. Attached 52" drain hose can reach 74"-high standpipe. For higher standpipe, optional Drain Hose Extension Kit available. Note: For planning purposes only. @ @ · 15" Classic Black Drawer Pedestal (PN# CFPWD15B). · 15" Classic White Drawer Pedestal (PN# CFPWD15W). · Mobile Home Installation Kit (PN# 137067200).



[You're reading an excerpt. Click here to read official FRIGIDAIRE FAFW4011L user guide](http://yourpdfguides.com/dref/3940792)
<http://yourpdfguides.com/dref/3940792>