




Your PDF Guides

You can read the recommendations in the user guide, the technical guide or the installation guide for FRIGIDAIRE FGES3045KF. You'll find the answers to all your questions on the FRIGIDAIRE FGES3045KF in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.


User manual FRIGIDAIRE FGES3045KF
User guide FRIGIDAIRE FGES3045KF
Operating instructions FRIGIDAIRE FGES3045KF
Instructions for use FRIGIDAIRE FGES3045KF
Instruction manual FRIGIDAIRE FGES3045KF




Slide-In Ranges

FGES3045K F/W/B


30" Electric




Signature Features




Quick Preheat
Preheat in less than 15 minutes!



True Convection
Multi-task cooking is faster and more even with True Convection.



Quick Boil
Boils water faster.



Express-Select® Controls
Turns on from warm to boil.

Product Dimensions

Height (Hx)	36-5/8"
Width	30"
Depth	24-1/2"

More Easy-To-Use Features

Chicken Nugget Button
Easily bake perfect chicken nuggets with the touch of a button.

One-Touch Keep Warm Setting
Just one touch of a button keeps food warm until everything—and everyone—is ready.

Keep Warm Zone
Keep food warm until everything—and everyone—is ready.

Real Stainless Steel®
Real stainless steel with a protective coating that reduces fingerprints and smudges so it's easy to clean.

Effortless™ Convection
Takes the guesswork out of convection cooking — our oven does the converting for you.

Even Baking Technology
Our smart technology ensures even baking every time.

Auto Oven Shut-Off
As an extra safety measure, the oven will automatically shut off after six hours.

A.D.A. Compliant
Sabbath Mode (Kashruth Certified)

Available in:

Stainless Steel	White	Black
EPF	OO	BB

Element	Size	Watts
Right Front	6"	2700
Right Rear	6"	1200
Left Front	6 1/2"	1600/3000
Left Rear	6"	1200
Control	Keep Warm Zone	100

Based on single mode cooking performance, not set performance using 30-60 minutes.
*Heat makes only.
†See your guide for real life appliance performance.
‡See the actual use drawings for accessibility. Guide may be updated by the original publisher. Printed on June 22, 2004, or amended August 5, 2009.

frigidaire.com



[You're reading an excerpt. Click here to read official FRIGIDAIRE FGES3045KF user guide](http://yourpdfguides.com/dref/5489767)
<http://yourpdfguides.com/dref/5489767>

Manual abstract:

3 When properly installed, meets the appliance standards in the Americans with Disabilities Act and the Architectural Barriers Act Accessibility Guidelines as published by the United States Access Board on June 23, 2004, as amended August 5, 2005. frigidaire.com Slide-In Ranges FGES3045K F/W/B Features Oven Control/Timing System Surface Type Window Exterior Door Finish Handle Design Exterior Finish (Side Panels) Convection System Oven Cleaning System Drawer Functionality Express-Select® Black Ceramic Glass (F) Color-C. Ceramic Gl. (W/B) Extra-Large Real Stainless Steel (F), Color-Coordinated (W/B) Stainless Steel (F), Color-Coordinated (W/B) Black True Convection Self Clean Storage 30" Electric Slide-In Electric Ranges Frigidaire Baseline Oven Controls Bake/Broil Effortless™ Convection Conversion Convection Bake/Broil/Roast Quick Preheat My Favorite Chicken Nugget Button Pizza Button Keep Warm Add-a-Minute Delay Start Self Clean Quick Clean Option Delay Clean Kitchen Timer/Timed Cook Option Auto Oven Shut-Off Lower Drawer Control Yes 2, 3, 4 Hours Yes Yes Yes/Yes 6 Hours Yes Yes Yes/Variable (400 550 °F) Yes Yes/Yes/Yes Yes C Cooktop Features Right Front Element (Watts) Right Rear Element (Watts) Left Front Element (Watts) Left Rear Element (Watts) Center Element (Watts) 12" 2,700 6" 1,200 6"9" 1,600/3,000 6" 1,200 Keep Warm Zone 100 A Extreme protrusion Oven Features Capacity (Cu.Ft.) Oven Light Hidden Bake Element Rack Configuration Baking System Broiling System Bake Element/Broil Element (Watts) Drawer Rack 4.2 1 Yes 2 Heavy Duty, 1 Offset Even Baking Technology Power Broil 3,400/3,400 B Certifications A.D.A.

Compliant Sabbath Mode (Star-K® Certified) Yes Yes NOTE: For planning purposes only. Always consult local and national electric codes. Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.com. Specifications Oven Interior (H x W x D) Power Supply Connection Location Voltage Rating Connected Load (kW Rating) @ 240/208 Volts Amps @ 240/208 Volts Minimum Circuit Required (Amps) Shipping Weight (Approx.)

) 16-1/2" x 24-1/8" x 18-1/32" Left Bottom Rear 240V/208V/60Hz 12.4/9.3 51.7/44.7 40 240 Lbs.

Product Dimensions A-Height (Max.) B-Width C-Depth 36-5/8" 30" 28-5/16" Cutout Dimensions Height (Min.)/(Max.) Width (Min.)/(Max.)* Depth (Min.)/(Max.)* 35-7/8"/36-5/8" 29-15/16"/30-1/16" 21-3/4"/22-1/8" Depth with Door Open 90° 45-1/2" *Cutout and countertop cutout width should match. **24" with optional backguard installed. 1When properly installed, meets the appliance standards in the Americans with Disabilities Act and the Architectural Barriers Act Accessibility Guidelines as published by the United States Access Board on June 23, 2004, as amended August 5, 2005.

Accessories information available on the web at frigidaire.com USA · 10200 David Taylor Drive · Charlotte, NC 28262 · 1-800-FRIGIDAIRE · frigidaire.com CANADA · 5855 Terry Fox Way · Mississauga, ON L5V 3E4 · 1-800-265-8352 · frigidaire.ca FGES3045K 02/11 © 2011 Electrolux Home Products, Inc. Specifications subject to change. Printed in the U.S.A. 30" Electric Slide-In Range Gallery Slide-In Ranges FGES3045K F/W/B 30" Electric Slide-In Range Specifications · Product Shipping Weight (approx.) 240 Lbs.

· Single phase 3- or 4-wire cable, 120/240 or 120/208 Volt, Countertop Preparation For detailed preparation instructions, refer to installation guide on the web. @@@@ Absolute minimum horizontal distance between overhead cabinets installed to either side of appliance must be no less than maximum width of appliance. · Allow 24" minimum clearance between rangetop and bottom of cabinet when bottom of wood or metal cabinet is protected by not less than 1/4" flame-retardant millboard covered with not less than No. 28 MGS sheet steel, 0.015" stainless steel, 0.024" aluminum or 0.020" copper. Allow 30" minimum clearance when cabinet is unprotected. · To reduce risk of fire when using overhead cabinetry, install range hood that projects horizontally a recommended minimum of 5" beyond bottom of cabinets. Optional Accessories · Rear Filler Kit: White (PN# 901193-9011), Black (PN# 901193-9010).

· Side Panel Kit: White (PN# 903074-9011), Black (PN# 903074-9010). · Backguard Kit: White (PN# 903046-9011), Black (PN# 903046-9010). Black (PN# 903075-9010). · Side Trim Kit: White (PN# 903075-9011), Accessories information available on the web at frigidaire.com USA · 10200 David Taylor Drive · Charlotte, NC 28262 · 1-800-FRIGIDAIRE · frigidaire.com CANADA · 5855 Terry Fox Way · Mississauga, ON L5V 3E4 · 1-800-265-8352 · frigidaire.ca FGES3045K 02/11 © 2011 Electrolux Home Products, Inc. Specifications subject to change. Printed in the U.S.

A. General Installation Guidelines with Side-by-Side Refrigerator Use these dimensions and clearance instructions for planning purposes only. @@.



[You're reading an excerpt. Click here to read official FRIGIDAIRE FGES3045KF user guide](#)
<http://yourpdfguides.com/dref/5489767>