



Your PDF Guides

You can read the recommendations in the user guide, the technical guide or the installation guide for FRIGIDAIRE FGMV174K M. You'll find the answers to all your questions on the FRIGIDAIRE FGMV174K M in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

User manual FRIGIDAIRE FGMV174K M
User guide FRIGIDAIRE FGMV174K M
Operating instructions FRIGIDAIRE FGMV174K M
Instructions for use FRIGIDAIRE FGMV174K M
Instruction manual FRIGIDAIRE FGMV174K M



Microwaves
FGMV174K F/M



Over-The-Range



Performance-Driven Style

- Real Stainless Steel
- Sensor Cooking
- 8 Auto Cook Options
- 7 User Preference Options
- 99% Conforms
- 1,000 Watts
- 2-Speed Mid-Rate Vent (300/180 CFM)

More Easy-To-Use Features

- Auto Start Heat Sensor
- 2-Level Light (Hi/Low)
- 15" Glass Turntable

One-Touch Options

- Auto 30-Seconds
- Chicken Mugglets
- Pizza Slice
- Baked Potato
- Beverage

Capacity

- 1.7 Cu Ft. Capacity

Overall Exterior Dimensions

Height	16 3/8"
Width	29 1/8"
Depth	16 3/8"

Available in:


Stainless
(S)


Silvermist™
(M)

*Microwave is capable of use by user with high performance oven features up to 30,000 total BTU output.

Signature Features



Effortless™ Reheat
Reheat almost anything at the touch of a button.



SpaceWise™ Rack
Our SpaceWise™ rack creates more room so you can cook two dishes at once.



Over 30 Options
Versatile settings include: chicken mugglets and snacks.



One-Touch Options
Our microwave features easy-to-use one-touch buttons so you can cook chicken mugglets, baked potatoes or popcorn with the touch of a button.

frigidaire.com



[You're reading an excerpt. Click here to read official FRIGIDAIRE FGMV174K M user guide](http://yourpdfguides.com/dref/2700701)
<http://yourpdfguides.com/dref/2700701>

Manual abstract:

@@Ft.) Microwaves FGMV174K F/M Over-The-Range Microwave Specifications · Product Shipping Weight (approx.) 60 Lbs. · Voltage Rating 120V/60 Hz/15 Amps · Connected Load (kW Rating) @ 120 Volts = 1.64kW Ducted Option Specifications · For outside ventilation. · Exhaust duct adapter will be needed for outside ventilation, to mate (For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded for safe operation.) · Amps @ 120 Volts = 14.2 Amps · Always consult local and national electric codes. · Grounded outlet should be located in cabinet above, with hole in base to route power cord.

@@@@@ Can NOT be installed in island or peninsula cabinet arrangements. · Cabinet bottom MUST be level to insure proper installation. @@@@@ Allow 26" minimum clearance for 90° door swing. with standard 3-1/4"x10" rectangular duct. If round duct required, rectangular-to-round transition adapter will be needed with no less than 6" diameter.

· For most efficient airflow exhaust, use a straight run or as few elbows as possible with a maximum duct length of 3-1/4"x10" rectangular or 6" diameter round duct, not to exceed 140 equivalent feet. · For horizontal installation, be sure to allow enough space between wall studs to accommodate exhaust. @@.



[You're reading an excerpt. Click here to read official FRIGIDAIRE FGMV174K M user guide](http://yourpdfguides.com/dref/2700701)
<http://yourpdfguides.com/dref/2700701>