



Your PDF Guides


You can read the recommendations in the user guide, the technical guide or the installation guide for HANNA INSTRUMENTS HI 98501-1. You'll find the answers to all your questions on the HANNA INSTRUMENTS HI 98501-1 in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

User manual HANNA INSTRUMENTS HI 98501-1
User guide HANNA INSTRUMENTS HI 98501-1
Operating instructions HANNA INSTRUMENTS HI 98501-1
Instructions for use HANNA INSTRUMENTS HI 98501-1
Instruction manual HANNA INSTRUMENTS HI 98501-1



Instruction Manual

HI 98501-1 Thermometer



SPECIFICATIONS

Range -50.0 to 150.0°C
Resolution 0.1°C
Accuracy ±1°C
(@20°C/68°F)
Typical EMC Deviation ±1°C
Environment 0 to 50°C (32 to 122°F);
95% RH max.
Battery Type 1 x 1.5V alkaline
Battery Life approx. 3000 hours
of continuous use
Dimensions 66 x 50 x 25 mm
(2.6 x 2 x 1")
Weight 50 g (1.8 oz.)



[You're reading an excerpt. Click here to read official HANNA INSTRUMENTS HI 98501-1 user guide](http://yourpdfguides.com/dref/2866027)
<http://yourpdfguides.com/dref/2866027>

Manual abstract:

5V alkaline Battery Life approx. 3000 hours of continuous use Dimensions Weight 66 x 50 x 25 mm (2.6 x 2 x 1") 50 g (1.8 oz.) www.hannainst.com
OPERATION · Turn the meter ON. · Dip the probe into the sample to be measured. An immersion level of 4 cm (1 ½") is recommended. Do NOT immerse above the connector.

· Wait for a few seconds for the display to stabilize. · When not in use, switch the meter OFF. · Variations in readings or fading display can indicate a weak battery. BATTERY REPLACEMENT When the thermometer can not be switched on or the display fades, open the battery compartment (see below picture) and replace the 1.5V battery, while paying attention to its polarity.

Reattach the battery cover. WARRANTY This meter is warranted for one year against defects in workmanship and materials when used for its intended purpose and maintained according to instructions. This warranty is limited to repair or replacement free of charge. Damages due to accident, misuse, tampering or lack of prescribed maintenance are not covered. @@@@Any variation introduced by the user to the supplied equipment may degrade the instrument's EMC performance.

To avoid electrical shock, do not use these instruments when voltages at the measurement surface exceed 24 VAC or 60 VDC. .



[You're reading an excerpt. Click here to read official HANNA INSTRUMENTS HI 98501-1 user guide](http://yourpdfguides.com/dref/2866027)
<http://yourpdfguides.com/dref/2866027>