




Your PDF Guides

You can read the recommendations in the user guide, the technical guide or the installation guide for HUSQVARNA 440E. You'll find the answers to all your questions on the HUSQVARNA 440E in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

User manual HUSQVARNA 440E
User guide HUSQVARNA 440E
Operating instructions HUSQVARNA 440E
Instructions for use HUSQVARNA 440E
Instruction manual HUSQVARNA 440E

Operator's manual
435 435e 440e



Please read the operator's manual carefully and make sure you understand the instructions before using the machine.

English

115 10 82-26 Rev.2 2008-06-03



[You're reading an excerpt. Click here to read official HUSQVARNA 440E user guide](http://yourpdfguides.com/dref/2291814)

<http://yourpdfguides.com/dref/2291814>

Manual abstract:

In order to prevent unintentional starting, the spark plug cap must be removed from the spark plug when assembling, checking and/or performing maintenance. Always wear approved protective gloves. Noise emission to the environment according to the European Community's Directive. The machine's emission is specified in chapter Technical data and on label. Regular cleaning is required. Visual check. Both of the operators hands must be used to operate the chain saw. Protective goggles or a visor must be worn. Never operate a chain saw holding it with one hand only. Refuelling.

Contact of the guide bar tip with any object must be avoided. Filling with oil and adjusting oil flow. WARNING! @@May cause serious personal injury. Other symbols/decals on the machine refer to special certification requirements for certain markets. The chain brake must be engaged when the chain saw is started.

WARNING! @@@@Symbols in the operator's manual:

.....

..... @@@@WHAT IS WHAT? What is what on the chain saw? ..

.....

.....

.....

..... GENERAL SAFETY PRECAUTIONS Before using a new chain saw

.....

.....

.....

..... Important

.....

.....

.....

.....

.....

.....

.....

..... Always use common sense ...

.....

.....

.....

. Personal protective equipment

.....

.....

Machines safety equipment

.....

.....

... Cutting equipment ..

.....

.....

.....

.....

.....

.....

. ASSEMBLY Fitting the bar and chain

.....

.....

.....

FUEL HANDLING Fuel

.....

.....

.....
.....
.....
.....

.....
.....
.....
Fuelling

.....
.....
.....
.....

.....
.....
.....
..... *Fuel safety*

.....
.....
.....
.....

.....
.....
.....
..... *STARTING AND STOPPING Starting and stopping*

.....
.....
.....
.....

..... *WORKING TECHNIQUES Before use:* ..

.....
.....
.....
.....

.....
.....
.....
.....

..... *General working instructions* ...

.....
.....
.....

..... *How to avoid kickback* .

.....
.....
.....

.....
.....
.....

..... *MAINTENANCE General*

.....
.....
.....
.....

.....
.....

.....
..... Carburettor adjustment

.....
.....
.....
.....

..... Checking, maintaining and servicing chain saw safety equipment ...

.....
.....
.....

.....
.....
.....

..... Muffler ...

.....
.....
.....
.....

.....
.....
.....

... Starter

.....
.....
.....

.....
.....
.....

..... Air filter .

.....
.....
.....

.....
.....
.....

.....

.... Spark plug .

.....
.....
.....

.....
.....
.....

.... Lubricating the bar tip sprocket .

.....
.....
.....

.....

.. Needle bearing lubrication ...

.....
.....

We are convinced that you will appreciate with great satisfaction the quality and performance of our product for a very long time to come. The purchase of one of our products gives you access to professional help with repairs and service whenever this may be necessary. If the retailer who sells your machine is not one of our authorised dealers, ask for the address of your nearest service workshop. It is our wish that you will be satisfied with your product and that it will be your companion for a long time. Think of this operators manual as a valuable document. By following its content (using, service, maintenance etc) the life span and the second-hand value of the machine can be extended. If you will sell this machine, make sure that the buyer will get the operators manual.

Thank you for using a Husqvarna product. Husqvarna AB has a policy of continuous product development and therefore reserves the right to modify the design and appearance of products without prior notice. 4 English 115 10 82-26 Rev.

2 2008-06-03 WHAT IS WHAT? What is what on the chain saw? 1 2 3 4 5 6 7 8 9 Cylinder cover Air purge Start reminder Combined start and stop switch Rear handle Information and warning decal Fuel tank Adjuster screws carburettor Starter handle 16 Muffler 17 Chain 18 Bar tip sprocket 19 Bar 20 Spike bumper 21 Chain catcher 22 Chain tensioner wheel 23 Clutch cover 24 Right hand guard 25 Throttle control 26 Throttle lockout 27 Knob 28 Operators manual 29 Bar guard 30 Combination spanner 10 Starter 11 Chain oil tank 12 Product and serial number plate 13 Felling direction mark 14 Front handle 15 Front hand guard 115 10 82-26 Rev.2 2008-06-03 English 5 GENERAL SAFETY PRECAUTIONS Before using a new chain saw · · Please read this manual carefully. Check that the cutting equipment is correctly fitted and adjusted. See instructions under the heading Assembly. Refuel and start the chain saw. See the instructions under the headings Fuel Handling and Starting and Stopping. Do not use the chain saw until sufficient chain oil has reached the chain. See instructions under the heading Cutting equipment. Long-term exposure to noise can result in permanent hearing impairment. So always use approved hearing protection.

! · · WARNING! Never allow children to use or be in the vicinity of the machine. As the machine is equipped with a springloaded stop switch and can be started by low speed and force on the starter handle, even small children under some circumstances can produce the force necessary to start the machine.

This can mean a risk of serious personal injury. Therefore remove the spark plug cap when the machine is not under close supervision. · Important
IMPORTANT! The machine is only designed for cutting wood.

You should only use the saw with the bar and chain combinations we recommend in the chapter Technical data. Never use the machine if you are fatigued, while under the influence of alcohol or drugs, medication or anything that could affect your vision, alertness, coordination or judgement. Wear personal protective equipment. See instructions under the heading Personal protective equipment. Do not modify this product or use it if it appears to have been modified by others.

Never use a machine that is faulty. Carry out the checks, maintenance and service instructions described in this manual. Some maintenance and service measures must be carried out by trained and qualified specialists. See instructions under the heading Maintenance. Never use any accessories other than those recommended in this manual. See instructions under the headings Cutting equipment and Technical data. CAUTION! Always wear protective glasses or a face visor to reduce the risk of injury from thrown objects.



[You're reading an excerpt. Click here to read official HUSQVARNA 440E user guide](#)

<http://yourpdfguides.com/dref/2291814>

A chain saw is capable of throwing objects, such as wood chips, small pieces of wood, etc, at great force. This can result in serious injury, especially to the eyes. **WARNING!** Running an engine in a confined or badly ventilated area can result in death due to asphyxiation or carbon monoxide poisoning.

WARNING! Faulty cutting equipment or the wrong combination of bar and saw chain increases the risk of kickback! Only use the bar/saw chain combinations we recommend, and follow the filing instructions. See instructions under the heading Technical data. **! WARNING!** Under no circumstances may the design of the machine be modified without the permission of the manufacturer. Always use genuine accessories. Non-authorized modifications and/or accessories can result in serious personal injury or the death of the operator or others. **WARNING!** A chain saw is a dangerous tool if used carelessly or incorrectly and can cause serious, even fatal injuries. It is very important that you read and understand the contents of this operator's manual. **WARNING!** The inside of the muffler contain chemicals that may be carcinogenic. Avoid contact with these elements in the event of a damaged muffler. **WARNING!** Long term inhalation of the engine's exhaust fumes, chain oil mist and dust from sawdust can represent a health risk.

WARNING! The ignition system of this machine produces an electromagnetic field during operation. This field may under some circumstances interfere with pacemakers. To reduce the risk of serious or fatal injury, we recommend persons with pacemakers to consult their physician and the pacemaker manufacturer before operating this machine. **!!!!** 6 English 115 10 82-26 Rev.2 2008-06-03 GENERAL SAFETY PRECAUTIONS Always use common sense It is not possible to cover every conceivable situation you can face when using a chain saw.

Always exercise care and use your common sense. Avoid all situations which you consider to be beyond your capability. If you still feel uncertain about operating procedures after reading these instructions, you should consult an expert before continuing. Do not hesitate to contact your dealer or us if you have any questions about the use of the chain saw. We will willingly be of service and provide you with advice as well as help you to use your chain saw both efficiently and safely.

Attend a training course in chain saw usage if possible. Your dealer, forestry school or your library can provide information about which training materials and courses are available. Approved protective helmet Hearing protection Protective goggles or a visor Gloves with saw protection Trousers with saw protection Boots with saw protection, steel toe-cap and non-slip sole Always have a first aid kit nearby. Fire Extinguisher by. Do not leave the chain saw switched on with the chain brake 8 English 115 10 82-26 Rev.2 2008-06-03 GENERAL SAFETY PRECAUTIONS If the kickback is less violent or the kickback zone of the bar is closer to you the chain brake will be activated manually by the movement of your left hand. Will my chain brake always protect me from injury in the event of a kickback? No. First, the chain brake must be in working order to provide the intended protection. Second, it must be activated during the kickback as described above to stop the saw chain. Third, the chain brake may be activated but if the bar is too close to you the brake might not have enough time to slow down and stop the chain before the chain saw hits you.

&middleoe right position. If necessary, use the combination spanner to insert or remove the mesh. **CAUTION!** The muffler gets very hot during and after use. This also applies during idling. Be aware of the fire hazard, especially when working near flammable substances and/or vapours. **! WARNING!** Overexposure to vibration can lead to circulatory damage or nerve damage in people who have impaired circulation. Contact your doctor if you experience symptoms of overexposure to vibration. Such symptoms include numbness, loss of feeling, tingling, pricking, pain, loss of strength, changes in skin colour or condition.

These symptoms normally appear in the fingers, hands or wrists. These symptoms may be increased in cold temperatures.

! WARNING! Never use a saw without a muffler, or with a damaged muffler. A damaged muffler may substantially increase the noise level and the fire hazard. Keep fire fighting equipment handy. If a spark arrestor screen is required in your area, never use the saw without or with a broken spark arrestor screen. 10 English 115 10 82-26 Rev.

2 2008-06-03 GENERAL SAFETY PRECAUTIONS Cutting equipment This section describes how to choose and maintain your cutting equipment in order to: Reduce the risk of kickback. Reduce the risk of the saw chain breaking or jumping off the bar. Obtain optimal cutting performance. Extend the life of cutting equipment. Avoid increasing vibration levels.

Cutting equipment designed to reduce kickback **! WARNING!** Faulty cutting equipment or the wrong combination of bar and saw chain increases the risk of kickback! Only use the bar/saw chain combinations we recommend, and follow the filing instructions. See instructions under the heading Technical data. General rules · Only use cutting equipment recommended by us! See instructions under the heading Technical data. The only way to avoid kickback is to make sure that the kickback zone of the bar never touches anything. By using cutting equipment with "built-in" kickback reduction and keeping the chain sharp and wellmaintained you can reduce the effects of kickback. Bar The smaller the tip radius the lower the chance of kickback. · Keep the chain's cutting teeth properly sharpened! Follow our instructions and use the recommended file gauge. A damaged or badly sharpened chain increases the risk of accidents. Chain A chain is made up of a number of links, which are available in standard and low-kickback versions. **IMPORTANT!** No saw chain design eliminates the danger of kickback.

WARNING! Any contact with a rotating saw chain can cause extremely serious injuries. · Maintain the correct depth gauge setting! Follow our instructions and use the recommended depth gauge clearance. Too large a clearance increases the risk of kickback. **! Some terms that describe the bar and chain To maintain the safety features of the cutting equipment, you should replace a worn or damaged bar or chain with a bar and chain combinations recommended by Husqvarna. See instructions under the heading Technical Data for a list of replacement bar and chain combinations we recommend. · Keep the chain properly tensioned! If the chain is slack it is more likely to jump off and lead to increased wear on the bar, chain and drive sprocket. Bar · Length (inches/cm) · · Keep cutting equipment well lubricated and properly maintained! A poorly lubricated chain is more likely to break and lead to increased wear on the bar, chain and drive sprocket.**



[You're reading an excerpt. Click here to read official HUSQVARNA](http://yourpdfguides.com/dref/2291814)

[440E user guide](http://yourpdfguides.com/dref/2291814)

<http://yourpdfguides.com/dref/2291814>

Number of teeth on bar tip sprocket (T). · Chain pitch (inches). The spacing between the drive links of the chain must match the spacing of the teeth on the bar tip sprocket and drive sprocket.

115 10 82-26 Rev.2 2008-06-03 English 11 GENERAL SAFETY PRECAUTIONS · Number of drive links. The number of drive links is determined by the length of the bar, the chain pitch and the number of teeth on the bar tip sprocket. · A sharp chain eats its way through the wood and produces long, thick chips or shavings. · Bar groove width (inches/mm).

The groove in the bar must match the width of the chain drive links. · The cutting part of the chain is called the cutter and consists of a cutting tooth (A) and the depth gauge (B). The cutters cutting depth is determined by the difference in height between the two (depth gauge setting). · Chain oil hole and hole for chain tensioner. The bar must be matched to the chain saw design.

When you sharpen a cutting tooth there are four important factors to remember. 1 Filing angle Chain · Chain pitch (inches) 2 Cutting angle · Drive link width (mm/inches) 3 File position 4 Round file diameter · Number of drive links. Sharpening your chain and adjusting depth gauge setting General information on sharpening cutting teeth · Never use a blunt chain. When the chain is blunt you have to exert more pressure to force the bar through the wood and the chips will be very small. If the chain is very blunt it will produce wood powder and no chips or shavings. It is very difficult to sharpen a chain correctly without the right equipment. We recommend that you use our file gauge. This will help you obtain the maximum kickback reduction and cutting performance from your chain. See instructions under the heading Technical data for information about sharpening your chain. 12 English 115 10 82-26 Rev.

2 2008-06-03 GENERAL SAFETY PRECAUTIONS ! WARNING! Departure from the sharpening instructions considerably increases the risk of kickback. ! WARNING! The risk of kickback is increased if the depth gauge setting is too large! Sharpening cutting teeth Adjustment of depth gauge setting To sharpen cutting teeth you will need a round file and a file gauge. See instructions under the heading Technical data for information on the size of file and gauge that are recommended for the chain fitted to your chain saw. · The cutting teeth should be newly sharpened before adjusting the depth gauge setting. We recommend that you adjust the depth gauge setting every third time you sharpen the cutting teeth. NOTE! This recommendation assumes that the length of the cutting teeth is not reduced excessively. You will need a flat file and a depth gauge tool. We recommend that you use our depth gauge tool to achieve the correct depth gauge setting and bevel for the depth gauge. · · Check that the chain is correctly tensioned. A slack chain will move sideways, making it more difficult to sharpen correctly.

· · Always file cutting teeth from the inside face. Reduce the pressure on the return stroke. File all the teeth on one side first, then turn the chain saw over and file the teeth on the other side. Place the depth gauge tool over the chain. Detailed information regarding the use of the depth gauge tool, will be found on the package for the depth gauge tool.

Use the flat file to file off the tip of the depth gauge that protrudes through the depth gauge tool. The depth gauge setting is correct when you no longer feel resistance as you draw the file along the depth gauge tool. · File all the teeth to the same length. When the length of the cutting teeth is reduced to 4 mm (0.16") the chain is worn out and should be replaced.

Tensioning the chain General advice on adjusting depth gauge setting · When you sharpen the cutting tooth (A) the depth gauge setting (C) will decrease. To maintain optimal cutting performance the depth gauge (B) has to be filed down to achieve the recommended depth gauge setting. See instructions under the heading Technical data to find the correct depth gauge setting for your particular chain. ! WARNING! A slack chain may jump off and cause serious or even fatal injury. The more you use a chain the longer it becomes. It is therefore important to adjust the chain regularly to take up the slack. Check the chain tension every time you refuel. NOTE! A new chain has a running-in period during which you should check the tension more frequently. 115 10 82-26 Rev.2 2008-06-03 English 13 GENERAL SAFETY PRECAUTIONS Tension the chain as tightly as possible, but not so tight that you cannot pull it round freely by hand.

435e, 440e · Release the knob by folding it out. 435 · Loosen the bar nut that holds the clutch cover and chain brake. Use the combination spanner. Then retighten the bar nut as tightly as you can by hand. · Turn the knob anti clockwise to loosen the bar cover. · Raise the tip of the bar and stretch the chain by tightening the chain tensioning screw using the combination spanner. Tighten the chain until it does not sag from the underside of the bar. · Adjust the tension on the chain by turning the wheel down (+) for tighter tension and up (-) to loosen the tension. · Use the combination spanner to tighten the bar nut while holding up the tip of the bar. Check that you can pull the saw chain round freely by hand, and that there is no slack on the underside of the bar.

The position of the chain tensioning screw on our chain saws varies from model to model. See instructions under the heading What is what? to find out where it is on your model. · Tighten the bar clutch by turning the knob clockwise. 14 English 115 10 82-26 Rev.2 2008-06-03 GENERAL SAFETY PRECAUTIONS · Fold the knob back in to lock the tensioning.

Checking chain lubrication · Check the chain lubrication each time you refuel. See instructions under the heading Lubricating the bar tip sprocket. Aim the tip of the bar at a light coloured surface about 20 cm (8 inches) away. After 1 minute running at 3/4 throttle you should see a distinct line of oil on the light surface. Lubricating cutting equipment ! Chain oil WARNING! Poor lubrication of cutting equipment may cause the chain to snap, which could lead to serious, even fatal injuries.

If the chain lubrication is not working: · Check that the oil channel in the bar is not obstructed. Clean if necessary. Chain oil must demonstrate good adhesion to the chain and also maintain its flow characteristics regardless of whether it is warm summer or cold winter weather. As a chain saw manufacturer we have developed an optimal chain oil which, with its vegetable oil base, is also biodegradable. We recommend the use of our own oil for both maximum chain life and to minimise environmental damage.



[You're reading an excerpt. Click here to read official HUSQVARNA](http://yourpdfguides.com/dref/2291814)

[440E user guide](http://yourpdfguides.com/dref/2291814)

<http://yourpdfguides.com/dref/2291814>

If our own chain oil is not available, standard chain oil is recommended. Never use waste oil! Using waste oil can be dangerous to you and damage the machine and environment. **IMPORTANT!** When using vegetable based saw chain oil, dismantle and clean the groove in the bar and saw chain before long-term storage. Otherwise there is a risk of the saw chain oil oxidizing, which will result in the saw chain becoming stiff and the bar tip sprocket jamming. Filling with chain oil · All our chain saws have an automatic chain lubrication system.

On some models the oil flow is also adjustable. · Check that the groove in the edge of the bar is clean. Clean if necessary. · Check that the bar tip sprocket turns freely and that the lubricating hole in the tip sprocket is not blocked. Clean and lubricate if necessary. · The saw chain oil tank and the fuel tank are designed so that the fuel runs out before the saw chain oil. However, this safety feature requires that you use the right sort of chain oil (if the oil is too thin it will run out before the fuel), and that you adjust the carburetor as recommended (a lean mixture may mean that the fuel lasts longer than the oil) and that you also use the recommended cutting equipment (a bar that is too long will use more chain oil). If the chain lubrication system is still not working after carrying out the above checks and associated measures you should contact your service agent. 115 10 82-26 Rev.2 2008-06-03 English 15 **GENERAL SAFETY PRECAUTIONS** Chain drive sprocket Bar The clutch drum is fitted with one of the following drive sprockets: A Spur sprocket (the chain sprocket is welded on the drum) B Rim sprocket (replaceable) Check regularly: · Whether there are burrs on the edges of the bar. Remove these with a file if necessary. · Whether the groove in the bar has become badly worn. Replace the bar if necessary. Regularly check the degree of wear on the drive sprocket. Replace if wear is excessive.

Replace the drive sprocket whenever you replace the chain. Needle bearing lubrication · Whether the tip of the bar is uneven or badly worn. If a hollow forms on the underside of the bar tip this is due to running with a slack chain. Both versions of sprockets have a needle bearing on the drive shaft, which has to be greased regularly (once a week). **CAUTION!** Use a high-quality bearing grease or engine oil.

See instructions under the heading Maintenance, Needle bearing lubrication. Checking wear on cutting equipment · To prolong the life of the bar you should turn it over regularly. Check the chain daily for: ! **WARNING!** Most chain saw accidents happen when the chain touches the operator. Wear personal protective equipment. See instructions under the heading Personal protective equipment. Do not tackle any job that you feel you are not adequately trained for. See instructions under the headings Personal protective equipment, How to avoid kickback, Cutting equipment and General working instructions. Avoid situations where there is a risk of kickback. See instructions under the heading Machines safety equipment. Use the recommended protective equipment and check its condition.

See instructions under the heading General working instructions. Check that all the chain saw safety features are working. See instructions under the headings General working instructions and General safety precautions. · · · Visible cracks in rivets and links. Whether the chain is stiff. Whether rivets and links are badly worn. Replace the saw chain if it exhibits any of the points above. We recommend you compare the existing chain with a new chain to decide how badly the existing chain is worn. When the length of the cutting teeth has worn down to only 4 mm the chain must be replaced. 16 English 115 10 82-26 Rev.

2 2008-06-03 **ASSEMBLY** Fitting the bar and chain The chain is correctly tensioned when there is no slack on the underside of the bar, and it can still be turned easily by hand. Tighten the bar nut with the combination spanner while holding up the tip of the bar. ! 435 **WARNING!** Always wear gloves, when working with the chain. Check that the chain brake is in disengaged position by moving the front hand guard towards the front handle. When fitting a new chain, the chain tension has to be checked frequently until the chain is run-in.

Check the chain tension regularly. A correctly tensioned chain ensures good cutting performance and long life. Unscrew the bar nut and remove the clutch cover (chain brake). Take off the transportation ring (A). 435e, 440e Check that the chain brake is in disengaged position by moving the front hand guard towards the front handle.

Fit the bar over the bar bolt. Place the bar in its rearmost position. Place the chain over the drive sprocket and in the groove on the bar. Begin on the top side of the bar. Loosen the chain tensioner wheel and remove the clutch cover (chain brake). Remove the transport guard. (A) Make sure that the edges of the cutting links are facing forward on the top edge of the bar. Mount the clutch cover and remember to fit the chain adjuster pin in the hole in the bar. Check that the drive links of the chain fit correctly over the drive sprocket and that the chain is correctly located in the groove in the bar. Tighten the bar nut with your fingers.

Tension the chain by turning the chain tensioning screw clockwise using the combination spanner. The chain should be tensioned until it does not sag from the underside of the bar. Fit the bar over the bar bolts. Place the bar in its rearmost position. Place the chain over the drive sprocket locate it in the groove on the bar. Begin on the top edge of the bar. Make sure that the edges of the cutting links are facing forward on the top edge of the bar. 115 10 82-26 Rev.2

2008-06-03 English 17 **ASSEMBLY** Mount the clutch cover and remember to fit the chain adjuster pin in the hole in the bar. Check that the drive links of the chain fit correctly over the drive sprocket and that the chain is correctly located in the groove in the bar.

Tension the chain by turning the wheel down (+). The chain should be tensioned until it does not sag from the underside of the bar. The chain is correctly tensioned when it does not sag from the underside of the bar, but can still be turned easily by hand. Hold up the bar tip and tighten the bar knob by turning the knob clockwise. When fitting a new chain, the chain tension has to be checked frequently until the chain is run-in.

Check the chain tension regularly. A correctly tensioned chain ensures good cutting performance and long life. Fitting a spike bumper To fit a spike bumper contact your service agent. 18 English 115 10 82-26 Rev.2 2008-06-03 **FUEL HANDLING** Fuel Note! The machine is equipped with a two-stroke engine and must always be run using a mixture of petrol and two-stroke oil.

It is important to accurately measure the amount of oil to be mixed to ensure that the correct mixture is obtained.



You're reading an excerpt. Click here to read official HUSQVARNA 440E user guide
<http://yourpdfguides.com/dref/2291814>

When mixing small amounts of fuel, even small inaccuracies can drastically affect the ratio of the mixture. Mixing ratio 1:50 (2%) with HUSQVARNA two-stroke oil. 1:33 (3%) with oils class JASO FB or ISO EGB formulated for air-cooled, two-stroke engines. Petrol, litre Two-stroke oil, litre 2% (1:50) 5 0,10 0,20 0,30 0,40 3% (1:33) 0,15 0,30 0,45 0,60 ! Petrol WARNING! Always ensure there is adequate ventilation when handling fuel. 10 15 20 Mixing · · Use good quality unleaded or leaded petrol. CAUTION! Engines equipped with catalytic converters must be run on unleaded fuel mixtures. Leaded gasoline will destroy the catalytic converter and it will no longer serve its purpose. @@The lowest recommended octane grade is 90 (RON). @@@@When working with continuous high revs (e.

g. limbing) a higher octane is recommended. @@Always start by filling half the amount of the petrol to be used. Then add the entire amount of oil. Mix (shake) the fuel mixture. Add the remaining amount of petrol. @@Do not mix more than one month's supply of fuel at a time. @@@@Never use oil intended for four-stroke engines. @@ · · · Never use waste oil. This results in damage to the oil pump, the bar and the chain.

@@In temperatures below 0°C (32°F) some oils become too viscous. @@Contact your service agent when choosing chain oil. @@@@Tighten the fuel cap carefully after refuelling. @@Wipe off the spillage and allow remaining fuel to evaporate. @@Wash any part of your body that has come in contact with fuel.

Use soap and water. If the machine is leaking fuel. @@Clean the fuel and chain oil tanks regularly. The fuel filter must be replaced at least once a year. Contamination in the tanks causes malfunction.

@@@@Always store fuel in an approved container designed for that purpose. @@@@Remove the spark plug cap from the spark plug. Activate the chain brake. · · ! WARNING! Fuel and fuel vapour are highly flammable. Take care when handling fuel and chain oil. @@Store the fuel in approved cans in a safe place. Fit the bar guard. Clean the machine. See instructions under the heading Maintenance schedule. 20 English 115 10 82-26 Rev.

2 2008-06-03 STARTING AND STOPPING Starting and stopping Warm engine When the chain saw is heated restart the saw only by pulling the cord powerfully until the engine starts (5). Never twist the starter cord around your hand. ! WARNING! Note the following before starting: The chain brake must be engaged when the chain saw is started to reduce the chance of contact with the moving chain during starting. Never start a chain saw unless the bar, chain and all covers are fitted correctly. Otherwise the clutch can come loose and cause personal injuries. Place the machine on firm ground. Make sure you have a secure footing and that the chain cannot touch anything. Keep people and animals well away from the working area. There is a simplified start reminder with illustrations to describe each step on the rear edge of the saw (A). As the chain brake is still engaged the speed of the engine must be set to idling as soon as possible, this is achieved by disengaging the throttle lock.

Disengagement is done by gently touching on the throttle trigger. This prevents unnecessary wear to the clutch, clutch drum and brake band. Starting The chain brake must be engaged when the chain saw is started. Activate the brake by moving the front hand guard forwards. Then let the machine idle for a few seconds before you apply full throttle.

CAUTION! Do not pull the starter cord all the way out and do not let go of the starter handle when the cord is fully extended. This can damage the machine.

Cold engine Start position (1): Set the start/stop switch in the choke position by pulling the red control outward - upward (1). Air purge (2): Press the air purge diaphragm repeatedly until fuel fills the diaphragm (at least 6 times). The diaphragm need not be completely filled.

2 A 1 Note! Reactivate the chain brake by pushing the front hand guard back towards the front handle. The chain saw is now ready for use. Grip the front handle with your left hand. Hold the chain saw on the ground by placing your right foot through the rear handle. Pull the starter handle with your right hand and pull out the starter cord slowly until you feel a resistance (as the starter pawls engage) then pull firmly and rapidly until the engine fires (3). Push down the red choke control (4) as soon as the engine fires which can be heard through a "puff" sound. Keep on pulling the cord powerfully until the engine starts. 115 10 82-26 Rev.2 2008-06-03 ! WARNING! Long term inhalation of the engine's exhaust fumes, chain oil mist and dust from sawdust can represent a health risk. English 21 STARTING AND STOPPING · Never start a chain saw unless the bar, chain and all covers are fitted correctly.

See instructions under the heading Assembly. Without a bar and chain attached to the chain saw the clutch can come loose and cause serious injury. Stopping Stop the engine by pushing the start/stop switch down. · The chain brake should be activated when starting. Se instructions under the heading Start and stop.

Do not drop start. This method is very dangerous because you may lose control of the saw. CAUTION! The start/stop switch automatically returns to run position. To avoid involuntary start up, the spark plug cap must always be removed from the spark plug when the machine is unsupervised. · · Never start the machine indoors.

Exhaust fumes can be dangerous if inhaled. @@@@All people, whether right or left handed, should use this grip. @@@@Check that the rear right hand guard is not damaged. Check that the throttle lockout works correctly and is not damaged. Check that the stop switch works correctly and is not damaged.

Check that all handles are free from oil. Check that the anti vibration system works and is not damaged. Check that the muffler is securely attached and not damaged. @@Check that the chain catcher is in place and not damaged. 4 CAUTION! @@@@cutting many small branches at the same time).

@@Make sure you can move and stand safely. Check the area around you for possible obstacles (roots, rocks, branches, ditches, etc.) in case you have to move suddenly. Take great care when working on sloping ground. 3 10 Check the chain tension. General working instructions IMPORTANT! This section describes basic safety rules for using a chain saw. This information is never a substitute for professional skills and experience. If you get into a situation where you feel unsafe, stop and seek expert advice. Contact your chain saw dealer, service agent or an experienced chain saw user. Do not attempt any task that you feel unsure of! Before using a chain saw you must understand the effects of kickback and how to avoid them.

See instructions under the heading How to avoid kickback. Before using a chain saw you must understand the difference between cutting with the top and bottom edges of the bar.



[You're reading an excerpt. Click here to read official HUSQVARNA 440E user guide](http://yourpdfguides.com/dref/2291814)

<http://yourpdfguides.com/dref/2291814>

See instructions under the headings *How to avoid kickback and Machine's safety equipment*. Wear personal protective equipment. See instructions under the heading *Personal protective equipment*. 5 Take great care when cutting a tree that is in tension. A tree that is in tension may spring back to its normal position before or after being cut. If you position yourself incorrectly or make the cut in the wrong place the tree may hit you or the machine and cause you to lose control. Both situations can cause serious personal injury. 115 10 82-26 Rev.

2 2008-06-03 English 23 **WORKING TECHNIQUES** Have control over the workpiece. If the pieces you intend to cut are small and light, they can jam in the saw chain and be thrown towards you. Even if this does not need to be a danger, you may be surprised and lose control of the saw. Never saw stacked logs or branches without first separating them. Only saw one log or one piece at a time.

Remove the cut pieces to keep your working area safe. 6 Before moving your chain saw switch off the engine and lock the chain using the chain brake. Carry the chain saw with the bar and chain pointing backwards. Fit a guard to the bar before transporting the chain saw or carrying it for any distance. 7 When you put the chain saw on the ground, lock the saw chain using the chain brake and ensure you have a constant view of the machine.

Switch the engine off before leaving your chain saw for any length of time. 4 Never use the chain saw above shoulder height and try not to cut with the tip of the bar. Never use the chain saw one-handed! **General rules** 1 If you understand what kickback is and how it happens then you can reduce or eliminate the element of surprise. By being prepared you reduce the risk. Kickback is usually quite mild, but it can sometimes be very sudden and violent. Always hold the chain saw firmly with your right hand on the rear handle and your left hand on the front handle. Wrap your fingers and thumbs around the handles. You should use this grip whether you are right-handed or left-handed. This grip minimises the effect of kickback and lets you keep the chain saw under control. Do not let go of the handles! 2 5 You must have a steady stance in order to have full control over the chain saw.

Never work standing on a ladder, in a tree or where you do not have firm ground to stand on. 3 Most kickback accidents happen during limbing. Make sure you are standing firmly and that there is nothing in the way that might make you trip or lose your balance. Lack of concentration can lead to kickback if the kickback zone of the bar accidentally touches a branch, nearby tree or some other object. 6 7 Always use a fast cutting speed, i.e. full throttle. Take great care when you cut with the top edge of the bar, i.e. when cutting from the underside of the object.

This is known as cutting on the push stroke. The chain tries to push the chain saw back towards the user. If 24 English 115 10 82-26 Rev.2 2008-06-03 **WORKING TECHNIQUES** the saw chain is jamming, the saw may be pushed back at you. Cutting on the push stroke increases the risk of kickback.

See instructions under the heading *How to avoid kickback*. Terms Cutting = General term for cutting through wood. Limbing = Cutting branches off a felled tree. Splitting = When the object you are cutting breaks off before the cut is complete. 8 Unless the user resists this pushing force there is a risk that the chain saw will move so far backwards that only the kickback zone of the bar is in contact with the tree, which will lead to a kickback.

There are five important factors you should consider before making a cut: 1 Make sure the cutting equipment will not jam in the cut. 2 Cutting with the bottom edge of the bar, i.e. from the top of the object downwards, is known as cutting on the pull stroke. In this case the chain saw pulls itself towards the tree and the front edge of the chain saw body rests naturally on the trunk when cutting. Cutting on the pull stroke gives the operator better control over the chain saw and the position of the kickback zone. Make sure the object you are cutting will not split. 3 Make sure the chain will not strike the ground or any other object during or after cutting. 4 Is there a risk of kickback? 9 Follow the instructions on sharpening and maintaining your bar and chain. When you replace the bar and chain use only combinations that are recommended by us.

See instructions under the headings *Cutting equipment and Technical data*. 5 Do the conditions and surrounding terrain affect how safely you can stand and move about? Basic cutting technique ! **WARNING!** Never use a chain saw by holding it with one hand. A chain saw is not safely controlled with one hand.

Always have a secure, firm grip around the handles with both hands. Two factors decide whether the chain will jam or the object that you are cutting will split: the first is how the object is supported before and after cutting, and the second is whether it is in tension. In most cases you can avoid these problems by cutting in two stages; from the top and from the bottom. You need to support the object so that it will not trap the chain or split during cutting. **IMPORTANT!**

If the chain jams in the cut: stop the engine! Don't try to pull the chain saw free. If you do you may be injured by the chain when the chain saw suddenly breaks free. Use a lever to open up the cut and free the chain saw.

General · Always use full throttle when cutting! · Reduce the speed to idle after every cut (running the engine for too long at full throttle without any load, i.e. without any resistance from the chain during cutting, can lead to serious engine damage). · Cutting from above = Cutting on the pull stroke. · Cutting from below = Cutting on the push stroke.

115 10 82-26 Rev.2 2008-06-03 English 25 **WORKING TECHNIQUES** The following instructions describe how to handle the commonest situations you are likely to encounter when using a chain saw. Limbing When limbing thick branches you should use the same approach as for cutting. Cut difficult branches piece by piece. The log is supported at one end.

There is a high risk that it will split. Turn the log and finish the cut from the opposite side. 1 2 3 Start by cutting from below (about 1/3 of the way through). Finish by cutting from above so that the two cuts meet. **Cutting ! WARNING!** Never attempt to cut logs while they are in a pile or when a couple of logs are lying together. Such procedures drastically increase the risk of kickback which can result in a serious or fatal injury. The log is supported at both ends. There is a high risk that the chain will jam. If you have a pile of logs, each log you attempt to cut should be removed from the pile, placed on a saw horse or runners and cut individually. Remove the cut pieces from the cutting area.

By leaving them in the cutting area, you increase the risk for inadvertently getting a kickback, as well as increasing the risk of losing your balance while working.



[You're reading an excerpt. Click here to read official HUSQVARNA 440E user guide](http://yourpdfguides.com/dref/2291814)

<http://yourpdfguides.com/dref/2291814>

Start by cutting from above (about 1/3 of the way through). Finish by cutting from below so that the two cuts meet. Tree felling technique The log is lying on the ground. There is little risk of the chain jamming or the object splitting. However there is a risk that the chain will touch the ground when you finish the cut. **IMPORTANT!** It takes a lot of experience to fell a tree. Inexperienced users of chain saws should not fell trees. Do not attempt any task that you feel unsure of! Safe distance The safe distance between a tree that is to be felled and anyone else working nearby is at least 2 1/2 tree lengths. Make sure that no one else is in this "risk zone" before or during felling.

Cut all the way through the log from above. Avoid letting the chain touch the ground as you finish the cut. Maintain full throttle but be prepared for what might happen. If it is possible (can you turn the log?) stop cutting about 2/3 of the way through the log. 26 English 115 10 82-26 Rev.

2 2008-06-03 WORKING TECHNIQUES Felling direction The aim is to fell the tree in a position where you can limb and cross-cut the log as easily as possible. You want it to fall in a location where you can stand and move about safely. Once you have decided which way you want the tree to fall you must judge which way the tree would fall naturally. Several factors affect this: Lean of the tree Bend Wind direction Arrangement of branches Weight of snow Obstacles within the reach of the tree: for example, other trees, power lines, roads and buildings. Look for signs of damage and rot in the stem, this makes it more probably that the tree will break and start to fall before you expect it to.

Remove any undergrowth from the base of the tree and check the area for obstacles (stones, branches, holes, etc.) so that you have a clear path of retreat when the tree starts to fall. Your path of retreat should be roughly 135 degrees away from the intended felling direction. Clearing the trunk and preparing your retreat Delimb the stem up to shoulder height. It is safer to work from the top down and to have the tree between you and the saw. 1 3 2 1 You may find you are forced to let the tree fall in its natural direction because it is impossible or dangerous to try to make it fall in the direction you first intended. Another very important factor, which does not affect the felling direction but does affect your safety, is to make sure the tree has no damaged or dead branches that might break off and hit you during felling. The main point to avoid is letting the tree fall onto another tree. It is very dangerous to remove a trapped tree and there is high accident risk. See instructions under the heading Freeing a tree that has fallen badly.

1 2 3 1 2 Danger zone Retreat path Felling direction Felling ! WARNING! Unless you have special training we advise you not to fell trees with a diameter larger than the bar length of your saw! Felling is done using three cuts. First you make the directional cuts, which consist of the top cut and the bottom cut, then you finish with the felling cut. By placing these cuts correctly you can control the felling direction very accurately. Directional cuts **IMPORTANT!**

During critical felling operations, hearing protectors should be lifted immediately when sawing is completed so that sounds and warning signals can be heard. To make the directional cut you begin with the top cut. Aim using the saw's felling direction mark (1) toward a goal further forward in the terrain, where you would like the tree to fall (2). Stand on the right-hand side of the tree, behind the saw, and cut with a pull stroke. 115 10 82-26 Rev.2 2008-06-03 English 27 WORKING TECHNIQUES Next make the bottom cut so that it finishes exactly at the end of the top cut. trunk diameter.

The uncut section of the trunk is called the felling hinge. The felling hinge controls the direction that the tree falls in. The directional cuts should run 1/4 of the diameter through the trunk and the angle between the top cut and bottom cut should be 45°. The line where the two cuts meet is called the directional cut line.

This line should be perfectly horizontal and at right angles (90°) to the chosen felling direction.

All control over the felling direction is lost if the felling hinge is too narrow or non-existent, or if the directional cuts and felling cut are badly placed. When the felling cut and directional cut are complete the tree should start to fall by itself or with the aid of a felling wedge or breaking bar. Felling cut The felling cut is made from the opposite side of the tree and it must be perfectly horizontal. Stand on the left side of the tree and cut on the pull stroke. Make the felling cut about 3-5 cm (1.

5-2 inches) above the bottom directional cut. We recommend that you use a bar that is longer than the diameter of the tree, so that you can make the felling cut and directional cuts with single cutting strokes. See instructions under the heading Technical data section to find out which lengths of bar are recommended for your saw. Set the spike bumper (if one is fitted) just behind the felling hinge. Use full throttle and advance the chain/bar slowly into the tree. Make sure the tree does not start to move in the opposite direction to your intended felling direction. Drive a wedge or breaking bar into the cut as soon as it is deep enough. There are methods for felling trees with a diameter larger than the bar length. However these methods involve a much greater risk that the kickback zone of the bar will come into contact with the tree. Finish the felling cut parallel with the directional cut line so that the distance between them is at least 1/10 of the 28 English 115 10 82-26 Rev.

2 2008-06-03 WORKING TECHNIQUES Freeing a tree that has fallen badly Freeing a "trapped tree" It is very dangerous to remove a trapped tree and there is high accident risk. Never try to fell the tree that is trapped. Never work in the risk zone of the hanging trapped tree. Make one or more cuts at or near the point of maximum tension. Make as many cuts of sufficient depth as necessary to reduce the tension and make the tree or branch break at the point of maximum tension. General advice: Position yourself so that you will be clear of the tree or branch when the tension is released. Never cut straight through a tree or branch that is in tension! The safest method is to use a winch. . Tractor-mounted If you must cut across tree/limb, make two to three cuts, one inch apart, one to two inches deep. . Portable Continue to cut deeper until tree/limb bends and tension is released. Cutting trees and branches that are in tension Preparations: Work out which side is in tension and where the point of maximum tension is (i.

e. where it would break if it was bent even more). Cut tree/limb from outside the bend, after tension has been released.



[You're reading an excerpt. Click here to read official HUSQVARNA 440E user guide](http://yourpdfguides.com/dref/2291814)
<http://yourpdfguides.com/dref/2291814>

Decide which is the safest way to release the tension and whether you are able to do it safely. In complicated situations the only safe method is to put aside your chain saw and use a winch.

115 10 82-26 Rev.2 2008-06-03 English 29 WORKING TECHNIQUES How to avoid kickback Limbing WARNING! A majority of kickback accidents occur during limbing. Do not use the kickback zone of the guide bar. Be extremely cautious and avoid contacting the log, other limbs or objects with the nose of the guide bar. Be extremely cautious of limbs under tension.

They can spring back toward you and cause loss of control resulting in injury. ! WARNING! Kickback can happen very suddenly and violently; kicking the chain saw, bar and chain back at the user. If this happens when the chain is moving it can cause very serious, even fatal injuries. It is vital you understand what causes kickback and that you can avoid it by taking care and using the right working technique. ! What is kickback? The word kickback is used to describe the sudden reaction that causes the chain saw and bar to jump off an object when the upper quadrant of the tip of the bar, known as the kickback zone, touches an object. Make sure that you can stand and move about safely. Work on the left side of the trunk. Work as close as possible to the chain saw for maximum control. If possible, let the weight of the chain saw rest on the trunk. Kickback always occurs in the cutting plane of the bar.

Normally the chain saw and bar are thrown backwards and upwards towards the user. However, the chain saw may move in a different direction depending on the way it was being used when the kickback zone of the bar touched the object. Keep the trunk between you and the chain saw as you move along the trunk. Cutting the trunk into logs See instructions under the heading Basic cutting technique. Kickback only occurs if the kickback zone of the bar touches an object. 30 English 115 10 82-26 Rev.2 2008-06-03 MAINTENANCE General The user must only carry out the maintenance and service work described in this Operator's Manual. More extensive work must be carried out by an authorised service workshop. Checking, maintaining and servicing chain saw safety equipment Note! All service and repair work on the machine demands special training. This is especially true of the machine's safety equipment.

If your machine fails any of the checks described below we recommend that you take it to your service workshop. Carburettor adjustment Your Husqvarna product has been designed and manufactured to specifications that reduce harmful emissions. Function · The carburettor governs the engine's speed via the throttle control. Air and fuel are mixed in the carburettor. The air/fuel mixture is adjustable.

Correct adjustment is essential to get the best performance from the machine. The T-screw regulates the throttle setting at idle speed. If the T-screw is turned clockwise this gives a higher idle speed; turning it anti-clockwise gives a lower idle speed. Chain brake and front hand guard Checking brake band wear · Brush off any wood dust, resin and dirt from the chain brake and clutch drum. Dirt and wear can impair operation of the brake.

Basic settings and running in The basic carburettor settings are adjusted during testing at the factory. Fine adjustment should be carried out by a skilled technician. Rec. idle speed: See the Technical data section. Fine adjustment of the idle speed T Adjust the idle speed with the T-screw. If it is necessary to re-adjust, turn the T-screw clockwise while the engine is running, until the chain starts to rotate. Then turn anticlockwise until the chain stops. When the idle speed is correctly adjusted the engine should run smoothly in every position and the engine speed should be safely below the speed at which the chain starts to rotate. Regularly check that the brake band is at least 0.6 mm thick at its thinnest point.

Checking the front hand guard ! WARNING! Contact your servicing dealer, if the idle speed setting cannot be adjusted so that the chain stops. Do not use the chain saw until it has been properly adjusted or repaired. Make sure the front hand guard is not damaged and that there are no visible defects such as cracks. Correctly adjusted carburettor When the carburettor is correctly adjusted the machine accelerates without hesitation and 4-cycles a little at full throttle. It is also important that the chain does not rotate at idle. If the L-jet is set too lean it may cause starting difficulties and poor acceleration. If the H-jet is set too lean the machine will have less power, poor acceleration and could suffer damage to the engine. Move the front hand guard forwards and back to make sure it moves freely and that it is securely anchored to the clutch cover. 115 10 82-26 Rev.2 2008-06-03 English 31 MAINTENANCE Checking the inertia brake release Throttle lockout Place the chain saw, with the engine switched off, on a stump or other stable surface.

Release the front handle and let the saw fall by its own weight, rotating around the rear handle towards the stump. · Make sure the throttle control is locked at the idle setting when the throttle lockout is released. · Press the throttle lockout and make sure it returns to its original position when you release it. When the bar hits the stump the brake should be applied. · Check that the throttle control and throttle lockout move freely and that the return springs work properly.

Checking the brake trigger Place the chain saw on firm ground and start it. Make sure the chain does not touch the ground or any other object. See the instructions under the heading Start and stop. · Start the chain saw and apply full throttle. Release the throttle control and check that the chain stops and remains stationary.

If the chain rotates when the throttle control is in the idle position you should check the carburettor idle adjustment. Chain catcher Grasp the chain saw firmly, wrapping your fingers and thumbs around the handles. Check that the chain catcher is not damaged and is firmly attached to the body of the chain saw. Apply full throttle and activate the chain brake by tilting your left wrist forward onto the front hand guard. Do not let go of the front handle. The chain should stop immediately. 32 English 115 10 82-26 Rev.2 2008-06-03 MAINTENANCE Right hand guard Muffler Check that the right hand guard is not damaged and that there are no visible defects, such as cracks. Never use a machine that has a faulty muffler. Vibration damping system Regularly check that the muffler is securely attached to the machine.

Regularly check the vibration damping units for cracks or deformation. Make sure the vibration damping units are securely attached to the engine unit and handle unit. Some mufflers are equipped with a special spark arrestor mesh.



[You're reading an excerpt. Click here to read official HUSQVARNA 440E user guide](http://yourpdfguides.com/dref/2291814)

<http://yourpdfguides.com/dref/2291814>

If your machine has this type of muffler, you should clean the mesh at least once a week. This is best done with a wire brush. A blocked mesh will cause the engine to overheat and may lead to serious damage. Note! The mesh must be replaced if it is damaged. If the mesh is blocked the machine will overheat and this will cause damage to the cylinder and piston. Never use a machine with a muffler that is in poor condition. Never use a muffler if the spark arrestor mesh is missing or defective.

Stop switch Start the engine and make sure the engine stops when you move the stop switch to the stop setting. The muffler is designed to reduce the noise level and to direct the exhaust gases away from the operator. The exhaust gases are hot and can contain sparks, which may cause fire if directed against dry and combustible material. CAUTION! The start/stop switch automatically returns to run position. In order to prevent unintentional starting, the spark plug cap must be removed from the spark plug when assembling, checking and/or performing maintenance.

115 10 82-26 Rev.2 2008-06-03 English 33 MAINTENANCE Starter through the hole in the starter housing and the starter handle. Tie a good knot on the starter cord. WARNING! When the recoil spring is wound up in the starter housing it is under tension and can, if handled carelessly, pop out and cause personal injury. Care must be exercised when replacing the return spring or the starter cord.

Wear protective glasses and protective gloves. ! Replacing the starter cord · Loosen the screws that hold the starter against the crankcase and remove the starter. Tensioning the recoil spring · Hook the starter cord in the notch in the pulley and turn the starter pulley about 2 turns clockwise. Note! Check that the pulley can be turned at least a further 1/2 turn when the starter cord is pulled all the way out. · Pull out the cord approx. 30 cm and hook it into the notch in the rim of the pulley. Release the recoil spring by letting the pulley rotate slowly backwards. 1 2 Stretch the line with the handle. Move your thumb and release the line. See the figure below.

· Undo the bolt in the centre of the pulley and remove the drive disc (A), drive disc spring (B) and the pulley (C). Insert and secure a new starter cord in the starter pulley. Wind approx. 3 turns of the starter cord on the starter pulley. Fit the starter pulley so that the end of the recoil spring (D) hooks into the starter pulley. Now assemble the drive disc spring, drive disc and the bolt in the centre of the pulley. Carry the starter cord 34 English 115 10 82-26 Rev.2

2008-06-03 MAINTENANCE Replacing the return and drive springs Air filter Recoil spring (A) · Lift up the starter pulley. See instructions under the heading Changing a broken or worn starter cord. Remember that the recoil spring is coiled under tension in the starter housing.

Remove the cassette with the recoil spring from the starter. Lubricate the recoil spring with light oil. Fit the cassette with recoil spring in the starter. Fit the starter pulley and tension the recoil spring. The air filter must be regularly cleaned to remove dust and dirt in order to avoid: Carburettor malfunctions Starting problems Loss of engine power Unnecessary wear to engine parts.

Excessive fuel consumption. Remove the air filter after taking off the air filter cover. When refitting make sure that the air filter seals tightly against the filter holder. Clean the filter by brushing or shaking it. · Drive disc spring (B) · Undo the bolt in the centre of the pulley and remove the drive disc and the drive disc spring.

Replace the drive disc spring and fit the drive disc above the spring. A B The filter can be cleaned more thoroughly by washing it in water and detergent. An air filter that has been in use for a long time cannot be cleaned completely. The filter must therefore be replaced with a new one at regular intervals. A damaged air filter must always be replaced. A HUSQVARNA chain saw can be equipped with different types of air filter according to working conditions, weather, season, etc. Contact your dealer for advice. Fitting the starter · To fit the starter, first pull out the starter cord and place the starter in position against the crankcase. Then slowly release the starter cord so that the pulley engages with the pawls. Fit and tighten the screws that hold the starter.

· 115 10 82-26 Rev.2 2008-06-03 English 35 MAINTENANCE Spark plug Needle bearing lubrication The spark plug condition is influenced by: . . . Incorrect carburettor adjustment. An incorrect fuel mixture (too much or incorrect type of oil). A dirty air filter. The clutch drum has a needle bearing on the output shaft. This needle bearing must be lubricated regularly. When lubricating, remove the clutch cover by loosening the two bar nuts. Lay the saw on its side with the clutch drum upwards. Lubrication involves engine oil dripping into the centre of the clutch drum as it rotates. These factors cause deposits on the spark plug electrodes, which may result in operating problems and starting difficulties.

If the machine is low on power, difficult to start or runs poorly at idle speed: always check the spark plug first before taking any further action. If the spark plug is dirty, clean it and check that the electrode gap is 0.5 mm. The spark plug should be replaced after about a month in operation or earlier if necessary.

Cooling system To keep the working temperature as low as possible the machine is equipped with a cooling system.

Note! Always use the recommended spark plug type! Use of the wrong spark plug can damage the piston/cylinder. Check that the spark plug is fitted with a suppressor. The cooling system consists of: 1 2 3 4 5 Lubricate the bar tip sprocket each time you refuel. Use the special grease gun and a good quality bearing grease. Air intake on the starter.

Air guide plate. Fins on the flywheel. Cooling fins on the cylinder. Cylinder cover (directs cold air over the cylinder). Lubricating the bar tip sprocket Clean the cooling system with a brush once a week, more often in demanding conditions. A dirty or blocked cooling system results in the machine overheating which causes damage to the piston and cylinder. 36 English 115 10 82-26 Rev.2 2008-06-03 MAINTENANCE "Air Injection" centrifugal cleaning Centrifugal cleaning means the following: All air to the carburettor passes through the starter. Dirt and dust is centrifuged out by the cooling fan. CAUTION! If the special winterising kit has been fitted or any measures have been taken to increase the temperature these changes must be reversed before the machine is used in normal temperature conditions.

@@IMPORTANT! @@@@Icing of the air filter and carburettor. Partly mask the air inlet on the starter to increase the working temperature of the engine.



[You're reading an excerpt. Click here to read official HUSQVARNA 440E user guide](http://yourpdfguides.com/dref/2291814)

<http://yourpdfguides.com/dref/2291814>