



Your PDF Guides

You can read the recommendations in the user guide, the technical guide or the installation guide for HUSQVARNA 445. You'll find the answers to all your questions on the HUSQVARNA 445 in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

User manual HUSQVARNA 445
User guide HUSQVARNA 445
Operating instructions HUSQVARNA 445
Instructions for use HUSQVARNA 445
Instruction manual HUSQVARNA 445

Operator's manual
Manuel d'utilisation
Manual de instrucciones
445 445e 450 450e



Please read the operator's manual carefully and make sure you understand the instructions before using the machine.
Lire attentivement et bien assimiler le manuel d'utilisation avant d'utiliser la machine.
Lea detenidamente el manual de instrucciones y asegúrese de entender su contenido antes de utilizar la máquina.

English (7-34)
French (35-67)
Spanish (68-99)

1153136-49 Rev.2 2010-04-08



[You're reading an excerpt. Click here to read official HUSQVARNA 445 user guide](http://yourpdfguides.com/dref/4739670)
<http://yourpdfguides.com/dref/4739670>

Manual abstract:

Other symbols/decals on the machine refer to special certification requirements for certain markets. Switch off the engine before carrying out any checks or maintenance. **nB!** The start/stop switch automatically returns to run position. In order to prevent unintentional starting, the spark plug cap must be removed from the spark plug when assembling, checking and/or performing maintenance. Never operate a chain saw holding it with one hand only. protective goggles or a visor must be worn. Contact of the guide bar tip with any object must be avoided. **wARNING!** Kickback may occur when the nose or tip of the guide bar touches an object, and cause a lightning fast reverse reaction, kicking the guide bar up and towards the operator. May cause serious personal injury.

@@@Ignition; choke: Set the choke control in the choke position.

This should automatically set the stop switch to the start position. refuelling. Filling with oil and adjusting oil flow. The chain brake should be activated when starting. @@@@Air purge Measured maximum kickback value with brake for the bar and chain combination on the label.

2 2010-04-08 English – 7 KEY TO SYMBOLS You will find the following labels on your chain saw: USA: Canada: 39° EPA III The Emissions Compliance Period referred to on the Emission Compliance label indicates the number of operating hours for which the engine has been shown to meet Federal emissions requirements. Maintenance, replacement, or repair of the emission control devices and system may be performed by any nonroad engine repair establishment or individual. 8 – English 1153136-49 Rev.

2 2010-04-08 CONTENTS Contents KEY TO SYMBOLS Symbols on the machine and/or in the manual: . What is what on the chain saw? . GENERAL SAFETY PRECAUTIONS Before using a new chain saw . important . Always use common sense . 33 AMERICAN STANDARD SAFETY PRECAUTIONS Safety precautions for chain saw users . Congratulations on your choice to buy a Husqvarna product! Husqvarna is based on a tradition that dates back to 1689, when the Swedish King Karl XI ordered the construction of a factory on the banks of the Huskvarna River, for production of muskets. The location was logical, since water power was harnessed from the Huskvarna River to create the water-powered plant. During over 300 years of continuous operation, the Husqvarna factory has produced a lot of different products, from wood stoves to modern kitchen appliances, sewing machines, bicycles, motorcycles etc. In 1956, the first motor driven lawn mowers appeared, followed by chain saws in 1959, and it is within this area Husqvarna is working today.

Today Husqvarna is one of the leading manufacturers in the world of forest and garden products, with quality as our highest priority. We develop, manufacture and market high quality motor driven products for forestry and gardening as well as for building and construction industry. Your purchase gives you access to professional help with repairs and service whenever this may be necessary. If the retailer who sells your machine is not one of our authorized dealers, ask for the address of your nearest servicing dealer. It is our wish that you will be satisfied with your product and that it will be your companion for a long time. Think of this operator's manual as a valuable document. By following its' content (using, service, maintenance etc) the life span and the second-hand value of the machine can be extended. If you ever lend or sell this machine, make sure that the borrower or buyer gets the operator's manual, so they will also know how to properly maintain and use it. Thank you for using a Husqvarna product! Husqvarna AB has a policy of continuous product development and therefore reserves the right to modify the design and appearance of products without prior notice. What is what on the chain saw? 1 2 3 4 5 6 7 8 9 Cylinder cover Decompression valve Air purge Start reminder Combined start and stop switch Rear handle Information and warning decal Fuel tank Adjuster screws, carburetor 10 Starter handle 11 Starter 12 Chain oil tank 13 Product and serial number plate 14 Felling direction mark 15 Front handle 16 Front hand guard 17 Muffler 18 Chain 19 Bar tip sprocket 20 Bar 21 Bumper spike 22 Chain catcher 23 Chain tensioning screw 24 Clutch cover 25 Right hand guard 26 Throttle control 27 Throttle lockout 28 Chain tensioner wheel (445e, 450e) 29 Knob (445e, 450e) 30 Operator's manual 31 Bar guard 32 Combination spanner 10 – English 1153136-49 Rev.

2 2010-04-08 GENERAL SAFETY PRECAUTIONS Before using a new chain saw •••Please read this manual carefully. See instructions under the heading Assembly. refuel and start the chain saw. See the instructions under the headings Fuel Handling and Starting and Stopping. Do not use the chain saw until sufficient chain oil has reached the chain.

See instructions under the heading Cutting equipment. Long-term exposure to noise can result in permanent hearing impairment. So always use approved hearing protection. Never allow children to use or be in the vicinity of the machine. As the machine is equipped with a springloaded stop switch and can be started by low speed and force on the starter handle, even small children under some circumstances can produce the force necessary to start the machine.

This can mean a risk of serious personal injury. Therefore remove the spark plug cap when the machine is not under close supervision. Under no circumstances may the design of the machine be modified without the permission of the manufacturer. always use genuine accessories. Non-authorized modifications and/or accessories can result in serious personal injury or the death of the operator or others. Your warranty may not cover damage or liability caused by the use of nonauthorized accessories or replacement parts. **wARNING!** A chain saw is a dangerous tool if used carelessly or incorrectly and can cause serious, even fatal injuries. It is very important that you read and understand the contents of this operator's manual. **wARNING!** The inside of the muffler contain chemicals that may be carcinogenic. Avoid contact with these elements in the event of a damaged muffler.

wARNING! @@ **wARNING!** This machine produces an electromagnetic field during operation. This field may under some circumstances interfere with active or passive medical implants. To reduce the risk of serious or fatal injury, we recommend persons with medical implants to consult their physician and the medical implant manufacturer before operating this machine. When using a chain saw, a fire extinguisher should be available. **wARNING!** Keep handles dry, clean and free of oil. Operate the chainsaw in well ventilated areas only. **wARNING!** Do not attempt a pruning or limbing operation in a standing tree unless specifically trained to do so.



[You're reading an excerpt. Click here to read official HUSQVARNA](http://yourpdfguides.com/dref/4739670)

[445 user guide](http://yourpdfguides.com/dref/4739670)

<http://yourpdfguides.com/dref/4739670>

This chain saw for forest service is designed for forest work such as felling, delimiting and cutting. You should only use the saw with the bar and chain combinations we recommend in the chapter Technical data. Never use the machine if you are fatigued, while under the influence of alcohol or drugs, medication or anything that could affect your vision, alertness, coordination or judgement.

wear personal protective equipment. See instructions under the heading "Personal protective equipment". Do not modify this product or use it if it appears to have been modified by others. Never use a machine that is faulty. Carry out the checks, maintenance and service instructions described in this manual. Some maintenance and service measures must be carried out by trained and qualified specialists. See instructions under the heading Maintenance. Never use any accessories other than those recommended in this manual. @@ nB! Always wear protective glasses or a face visor to reduce the risk of injury from thrown objects. A chain saw is capable of throwing objects, such as wood chips, small pieces of wood, etc, at great force.

This can result in serious injury, especially to the eyes. wARNING! Running an engine in a confined or badly ventilated area can result in death due to asphyxiation or carbon monoxide poisoning. wARNING! Faulty cutting equipment or the wrong combination of bar and saw chain increases the risk of kickback! Only use the bar/saw chain combinations we recommend, and follow the filing instructions. See instructions under the heading Technical data. courses are available. Work is constantly in progress to improve the design and technology - improvements that increase your safety and efficiency. Visit your dealer regularly to see whether you can benefit from new features that have been introduced. Most chain saw accidents happen when the chain touches the operator. You must use approved personal protective equipment whenever you use the machine. Personal protective equipment cannot eliminate the risk of injury but it will reduce the degree of injury if an accident does happen.

Ask your dealer for help in choosing the right equipment. □ ••••• Approved protective helmet Hearing protection Protective goggles or a visor Gloves with saw protection Trousers with saw protection Boots with saw protection, steel toe-cap and non-slip sole Always have a first aid kit nearby. Fire Extinguisher and Shovel Generally clothes should be close-fitting without restricting your freedom of movement. iMPORTANT! Sparks can come from the muffler, the bar and chain or other sources. Always have fire extinguishing tools available if you should need them. □ Machine's safety equipment In this section the machine's safety features and their function are explained. For inspection and maintenance see instructions under the heading Checking, maintaining and servicing chain saw safety equipment. See instructions under the heading, What is what? , to find where these parts are located on your machine. The life span of the machine can be reduced and the risk of accidents can increase if machine maintenance is not carried out correctly and if service and/or repairs are not carried out professionally. If you need further information please contact your nearest servicing dealer.

Always use common sense (2) It is not possible to cover every conceivable situation you can face when using a chain saw. Always exercise care and use your common sense. Avoid all situations which you consider to be beyond your capability. If you still feel uncertain about operating procedures after reading these instructions, you should consult an expert before continuing. Do not hesitate to contact your dealer or us if you have any questions about the use of the chain saw.

We will willingly be of service and provide you with advice as well as help you to use your chain saw both efficiently and safely. Attend a training course in chain saw usage if possible. Your dealer, forestry school or your library can provide information about which training materials and 12 – English ! wARNING! Never use a machine with defective safety components. Safety equipment must be inspected and maintained. See instructions under the heading Checking, maintaining and servicing chain saw safety equipment.

If your machine does not pass all the checks, take the saw to a servicing dealer for repair. 1153136-49 Rev. 2 2010-04-08 GENERAL SAFETY PRECAUTION Working order to provide the intended protection. Second, it must be activated during the kickback as described above to stop the saw chain. Third, the chain brake may be activated but if the bar is too close to you the brake might not have enough time to slow down and stop the chain before the chain saw hits you. Only you and proper working technique can eliminate kickback and its danger. •• Throttle lockout The throttle lockout is designed to prevent accidental operation of the throttle control. When you press the lock (A) (i. e. When you grasp the handle) it releases the throttle control (B).

When you r remove the mesh. nB! The muffler gets very hot during and after use. This also applies during idling. Be aware of the fire hazard, especially when working near flammable substances and/or vapours. Faulty cutting equipment or the wrong combination of bar and saw chain increases the risk of kickback! Only use the bar/saw chain combinations we recommend, and follow the filing instructions. See instructions under the heading Technical data. The only way to avoid kickback is to make sure that the kickback zone of the bar never touches anything. By using cutting equipment with "built-in" kickback reduction and keeping the chain sharp and wellmaintained you can reduce the effects of kickback. 14 – English 1153136-49 Rev. 2 2010-04-08 GENERAL SAFETY PRECAUTIONS Bar The smaller the tip radius the lower the chance of kickback.

Chain A chain is made up of a number of links, which are available in standard and low-kickback versions. iMPORTANT! No saw chain design eliminates the danger of kickback. wARNING! Any contact with a rotating saw chain can cause extremely serious injuries. When you sharpen a cutting tooth there are four important factors to remember. 1 2 3 4 Filing angle (19) Cutting angle (20) File position (21) Round file diameter It is very difficult to sharpen a chain correctly without the right equipment.

We recommend that you use our file gauge. This will help you obtain the maximum kickback reduction and cutting performance from your chain. (22) See instructions under the heading Technical data for information about sharpening your chain. ! Some terms that describe the bar and chain To maintain the safety features of the cutting equipment, you should replace a worn or damaged bar or chain with a bar and chain combinations recommended by Husqvarna. See instructions under the heading Technical Data for a list of replacement bar and chain combinations we recommend.



[You're reading an excerpt. Click here to read official HUSQVARNA](http://yourpdfguides.com/dref/4739670)

[445 user guide](http://yourpdfguides.com/dref/4739670)

<http://yourpdfguides.com/dref/4739670>

The spacing between the drive links of the chain must match the spacing of the teeth on the bar tip sprocket and drive sprocket. (14) • Number of drive links. The number of drive links is determined by the length of the bar, the chain pitch and the number of teeth on the bar tip sprocket. • Bar groove width (inches/mm). The groove in the bar must match the width of the chain drive links. □ Chain oil hole and hole for chain tensioner. The bar must be matched to the chain saw design. Departure from the sharpening instructions considerably increases the risk of kickback. Sharpening cutting teeth To sharpen cutting teeth you will need a round file and a file gauge. See instructions under the heading Technical data for information on the size of file and gauge that are recommended for the chain fitted to your chain saw.

• Check that the chain is correctly tensioned. A slack chain will move sideways, making it more difficult to sharpen correctly. Always file cutting teeth from the inside face. Reduce the pressure on the return stroke. File all the teeth on one side first, then turn the chain saw and file the teeth on the other side. File all the teeth to the same length. When the length of the cutting teeth is reduced to 4 mm (5/325/32") the chain is worn out and should be replaced. (23) • • General advice on adjusting depth gauge setting • When you sharpen the cutting tooth (A) the depth gauge setting (C) will decrease. To maintain optimal cutting performance the depth gauge (B) has to be filed down to achieve the recommended depth gauge setting. See instructions under the heading Technical data to find the correct depth gauge setting for your particular chain.

(24) Sharpening your chain and adjusting depth gauge setting General information on sharpening cutting teeth • Never use a blunt chain. When the chain is blunt you have to exert more pressure to force the bar through the wood and the chips will be very small. If the chain is very blunt it will produce wood powder and no chips or shavings. A sharp chain eats its way through the wood and produces long, thick chips or shavings. The cutting part of the chain is called the cutter and consists of a cutting tooth (A) and the depth gauge (B).

The cutters cutting depth is determined by the difference in height between the two (depth gauge setting). The risk of kickback is increased if the depth gauge setting is too large! • • 1153136-49 Rev. 2 2010-04-08 English – 15 GENERAL SAFETY PRECAUTIONS Adjustment of depth gauge setting 445e, 450e • • • The cutting teeth should be newly sharpened before adjusting the depth gauge setting. We recommend that you adjust the depth gauge setting every third time you sharpen the cutting teeth. nOTE! This recommendation assumes that the length of the cutting teeth is not reduced excessively.

You will need a flat file and a depth gauge tool. We recommend that you use our depth gauge tool to achieve the correct depth gauge setting and bevel for the depth gauge. Place the depth gauge tool over the chain. Detailed information regarding the use of the depth gauge tool, will be found on the package for the depth gauge tool. Use the flat file to file off the tip of the depth gauge that protrudes through the depth gauge tool. The depth gauge setting is correct when you no longer feel resistance as you draw the file along the depth gauge tool. (25) • • • Release the knob by folding it out. (30) Turn the knob anti clockwise to loosen the bar cover. (31) Adjust the tension on the chain by turning the wheel down (+) for tighter tension and up (-) to loosen the tension. (32) Tighten the bar clutch by turning the knob clockwise.

(33) Fold the knob back in to lock the tensioning. Poor lubrication of cutting equipment may cause the chain to snap, which could lead to serious, even fatal injuries. Tensioning the chain Chain oil must demonstrate good adhesion to the chain and also maintain its flow characteristics regardless of whether it is warm summer or cold winter weather. A slack chain may jump off and cause serious or even fatal injury. The more you use a chain the longer it becomes. It is therefore important to adjust the chain regularly to take up the slack. Check the chain tension every time you refuel. nOTE! A new chain has a running-in period during which you should check the tension more frequently. Tension the chain as tightly as possible, but not so tight that you cannot pull it round freely by hand. (26) 445 As a chain saw manufacturer we have developed an optimal chain oil which has a vegetable oil base.

We recommend the use of our own oil for both maximum chain life and to minimise environmental damage. If our own chain oil is not available, standard chain oil is recommended. Never use waste oil! Using waste oil can be dangerous to you and damage the machine and environment. iMPORTANT! When using vegetable based saw chain oil, dismantle and clean the groove in the bar and saw chain before long-term storage. Otherwise there is a risk of the saw chain oil oxidizing, which will result in the saw chain becoming stiff and the bar tip sprocket jamming.

Filling with chain oil Loosen the bar nut that holds the clutch cover and chain brake. use the combination spanner. Then retighten the bar nut as tightly as you can by hand. (27) • Raise the tip of the bar and stretch the chain by tightening the chain tensioning screw using the combination spanner. Tighten the chain until it does not sag from the underside of the bar.

(28) • Use the combination spanner to tighten the bar nut while holding up the tip of the bar. Check that you can pull the saw chain round freely by hand, and that there is no slack on the underside of the bar. (29) The position of the chain tensioning screw on our chain saws varies from model to model. See instructions under the heading What is what? To find out where it is on your model. 16 – English • • All our chain saws have an automatic chain lubrication system. On some models the oil flow is also adjustable. The saw chain oil tank and the fuel tank are designed so that the fuel runs out before the saw chain oil.

However, this safety feature requires that you use the right sort of chain oil (if the oil is too thin it will run out before the fuel), and that you adjust the carburetor as recommended (a weak mixture may mean that the fuel lasts longer than the oil) and that you also use the recommended cutting equipment (a bar that is too long will use more chain oil). The above conditions also apply to chain saw models with an adjustable oil pump. • 1153136-49 Rev.

2 2010-04-08 GENERAL SAFETY PRECAUTIONS Checking chain lubrication • Check the chain lubrication each time you refuel. See instructions under the heading Lubricating the bar tip sprocket. Aim the tip of the bar at a light coloured surface about 20 cm (8 inches) away. After 1 minute running at 3/4 throttle you should see a distinct line of oil on the light surface.



[You're reading an excerpt. Click here to read official HUSQVARNA 445 user guide](http://yourpdfguides.com/dref/4739670)
<http://yourpdfguides.com/dref/4739670>

If the chain lubrication is not working: ••• Check that the oil channel in the bar is not obstructed. clean if necessary. (35) Check that the groove in the edge of the bar is clean. clean if necessary. (36) Check that the bar tip sprocket turns freely and that the lubricating hole in the tip sprocket is not blocked. clean and lubricate if necessary.

(37) We recommend you compare the existing chain with a new chain to decide how badly the existing chain is worn. When the length of the cutting teeth has worn down to only 4 mm (5/32 inch) the chain must be replaced. Bar Check regularly: ••• Whether there are burrs on the edges of the bar. remove these with a file if necessary. Whether the groove in the bar has become badly worn.

replace the bar if necessary. Whether the tip of the bar is uneven or badly worn. If a hollow forms on the underside of the bar tip this is due to running with a slack chain. To prolong the life of the bar you should turn it over regularly. If the chain lubrication system is still not working after carrying out the above checks and associated measures you should contact your servicing dealer.

chain drive sprocket •! The clutch drum is fitted with one of the following drive sprockets: A Spur sprocket (the chain sprocket is welded on the drum) B Rim sprocket (replaceable) (38) Regularly check the degree of wear on the drive sprocket. replace if wear is excessive. Replace the drive sprocket whenever you replace the chain. needle bearing lubrication WARNING! Most chain saw accidents happen when the chain touches the operator. wear personal protective equipment. See instructions under the heading "Personal protective equipment". Do not tackle any job that you feel you are not adequately trained for. See instructions under the headings Personal protective equipment, How to avoid kickback, Cutting equipment and General working instructions. Avoid situations where there is a risk of kickback. See instructions under the heading Machine's safety equipment.

Use the recommended protective equipment and check its condition. See instructions under the heading General working instructions. Check that all the chain saw safety features are working. See instructions under the headings General working instructions and General safety precautions. Both versions of sprockets have a needle bearing on the drive shaft, which has to be greased regularly (once a week). nB! Use only high quality bearing grease or engine oil. See instructions under the heading Maintenance, Needle bearing lubrication. Checking wear on cutting equipment Check the chain daily for: ••• Visible cracks in rivets and links. whether the chain is stiff. Whether rivets and links are badly worn.

Replace the saw chain if it exhibits any of the points above. 1153136-49 Rev. 2 2010-04-08 English – 17 ASSEMBLY Fitting the bar and chain Tension the chain by turning the wheel down (+). The chain should be tensioned until it does not sag from the underside of the bar. (32) The chain is correctly tensioned when it does not sag from the underside of the bar, but can still be turned easily by hand.

Hold up the bar tip and tighten the bar knob by turning the knob clockwise. (33) When fitting a new chain, the chain tension has to be checked frequently until the chain is run-in. Always wear gloves, when working with the chain. Check that the chain brake is in disengaged position by moving the front hand guard towards the front handle. (39) Unscrew the bar nut and remove the clutch cover (chain brake).

Take off the transportation ring (A). (40) Fit the bar over the bar bolt. Place the bar in its rearmost position. Place the chain over the drive sprocket and in the groove on the bar. Begin on the top side of the bar. (41) Make sure that the edges of the cutting links are facing forward on the top edge of the bar. Mount the clutch cover and remember to fit the chain adjuster pin in the hole in the bar. Check that the drive links of the chain fit correctly over the drive sprocket and that the chain is correctly located in the groove in the bar. Tighten the bar nut with your fingers. Tension the chain by turning the chain tensioning screw clockwise using the combination spanner.

The chain should be tensioned until it does not sag from the underside of the bar. (42) The chain is correctly tensioned when there is no slack on the underside of the bar, and it can still be turned easily by hand. Tighten the bar nut with the combination spanner while holding up the tip of the bar. (43) When fitting a new chain, the chain tension has to be checked frequently until the chain is run-in. (44) 445e, 450e Check that the chain brake is in disengaged position by moving the front hand guard towards the front handle. (45) Loosen the chain tensioner wheel and remove the clutch cover (chain brake). remove the transport guard. (A) (46) Fit the bar over the bar bolts. Place the bar in its rearmost position. Place the chain over the drive sprocket locate it in the groove on the bar. Begin on the top edge of the bar. (41) Make sure that the edges of the cutting links are facing forward on the top edge of the bar. Mount the clutch cover and remember to fit the chain adjuster pin in the hole in the bar. Check that the drive links of the chain fit correctly over the drive sprocket and that the chain is correctly located in the groove in the bar. The machine is equipped with a two-stroke engine and must always be run using a mixture of gasoline and two-stroke oil.

It is important to accurately measure the amount of oil to be mixed to ensure that the correct mixture is obtained. When mixing small amounts of fuel, even small inaccuracies can drastically affect the ratio of the mixture. Two-stroke oil • For best results and performance use HUSQVARNA two-stroke engine oil, which is specially formulated for our air-cooled two stroke-engines. Never use two-stroke oil intended for water-cooled engines, sometimes referred to as outboard oil (rated TCW). Never use oil intended for four-stroke engines.

Always ensure there is adequate ventilation when handling fuel. Engines equipped with catalytic converters must be run on unleaded fuel mixtures. Leaded gasoline will destroy the catalytic converter and it will no longer serve its purpose. The green fuel cap on saws fitted with catalytic converters means that only unleaded gasoline can be used. the lowest recommended octane grade is 87 ((RON+MON)/2). If you run the engine on a lower octane grade than 87 so-called knocking can occur. This gives rise to a high engine temperature and increased bearing load, which can result in serious engine damage. When working with continuous high revs (e. □ •• 20 US gallon 1 2 1/2 5 • Mixing •• Always mix the gasoline and oil in a clean container intended for fuel. Always start by filling half the amount of the gasoline to be used.

Then add the entire amount of oil. Mix (shake) the fuel mixture thoroughly before filling the machine's fuel tank.



[You're reading an excerpt. Click here to read official HUSQVARNA](http://yourpdfguides.com/dref/4739670)

[445 user guide](http://yourpdfguides.com/dref/4739670)

<http://yourpdfguides.com/dref/4739670>

Do not mix more than one month's supply of fuel at a time. If the machine is not used for some time the fuel tank should be emptied and cleaned. □ Environment fuel HUSQVARNA recommends the use of alkylate fuel or environmental fuel for four-stroke engines blended with two-stroke oil as set out below. Note that carburetor adjustment may be necessary when changing the type of fuel (see instructions under the heading Carburetor). Running-in Avoid running at a too high speed for extended periods during the first 10 hours. Chain oil ••• We recommend the use of special oil (chain oil) with good adhesion characteristics. (48) Never use waste oil. This results in damage to the oil pump, the bar and the chain.

It is important to use oil of the right grade (suitable viscosity range) to suit the air temperature. In temperatures below 0°C (32°F) some oils become too viscous. This can overload the oil pump and result in damage to the oil pump components. Contact your service agent when choosing chain oil. Taking the following precautions, will lessen the risk of fire: Do not smoke and do not place any hot objects in the vicinity of fuel.

Always stop the engine and let it cool for a few minutes before refuelling. When refuelling, open the fuel cap slowly so that any excess pressure is released gently. Tighten the fuel cap carefully after refuelling. Always move the machine away from the refuelling area before starting. Clean the area around the fuel cap.

Clean the fuel and chain oil tanks regularly. The fuel filter must be replaced at least once a year. Contamination in the tanks causes malfunction. Make sure the fuel is well mixed by shaking the container before refuelling. The capacities of the chain oil tank and fuel tank are carefully matched. You should therefore always fill the chain oil tank and fuel tank at the same time. (48) ••• WARNING! Never use a machine with visible damage to the spark plug guard and ignition cable. A risk of sparking arises, which can cause a fire. Transport and storage Always store the chain saw and fuel so that there is no risk of leakages or fumes coming into contact with sparks or naked flames from electrical equipment, electric motors, relays/switches, boilers and the like. Always store fuel in an approved container designed for that purpose.

For longer periods of storage or for transport of the chain saw, the fuel and chain oil tanks should be emptied. Ask where you can dispose of waste fuel and chain oil at your local petrol station. The bar guard must always be fitted to the cutting attachment when the machine is being transported or in storage, in order to prevent accident contact with the sharp chain. Even a non-moving chain can cause serious cuts to yourself or persons you bump into with an exposed chain. Remove the spark plug cap from the spark plug. activate the chain brake. Secure the machine during transport. □ •• Long-term storage Empty the fuel/oil tanks in a well ventilated area. Store the fuel in approved cans in a safe place. See instructions under the heading Maintenance schedule.

Ensure the machine is cleaned and that a complete service is carried out before long-term storage. Take care when handling fuel and chain oil. Be aware of the risks of fire, explosion and those associated with inhalation. Fuel safety ••• I Never refuel the machine while the engine is running. Make sure there is plenty of ventilation when refuelling or mixing fuel (petrol and 2-stroke oil).

Move the machine at least 3 m from the refuelling point before starting it. Never start the machine: If you have spilled fuel or chain oil on the machine. Wipe off the spillage and allow remaining fuel to evaporate. If you have spilled fuel on yourself or your clothes, change your clothes. Wash any part of your body that has come in contact with fuel.

Check regularly for leaks from the fuel cap and fuel lines. Note the following before starting: The chain brake must be engaged when the chain saw is started to reduce the chance of contact with the moving chain during starting. Never start a chain saw unless the bar, chain and all covers are fitted correctly.

Otherwise the clutch can come loose and cause personal injuries. place the machine on firm ground. Make sure you have a secure footing and that the chain cannot touch anything. Keep people and animals well away from the working area. Never wrap the starter cord around your hand. Push down the red choke control, 5: This inactivates the choke, which is not needed when starting a warm chain saw. However the movement of the start/stop switch will have engaged a high idle, making warm starting easier.

Pull the starter handle, 6: Grip the front handle with your left hand. @@(51) Pull the starter handle with your right hand and pull out the starter cord slowly until you feel a resistance (as the starter pawls engage) then pull firmly and rapidly until the engine fires. As the chain brake is still engaged the speed of the engine must be set to idling as soon as possible, this is achieved by disengaging the throttle lock. Disengagement is done by gently touching on the throttle trigger. This prevents unnecessary wear to the clutch, clutch drum and brake band. Allow the machine to idle a few seconds before giving full throttle. There is a simplified start reminder with illustrations to describe each step on the rear edge of the saw (A). (50) NB! Do not pull the starter cord all the way out and do not let go of the starter handle when the cord is fully extended. This can damage the machine. note! Pull the front hand guard towards the front handle. The chain brake is now disengaged. Your saw is ready for use. ! Starting The chain brake should be activated when starting the chain saw. Activate the chain brake by pushing the front hand guard forwards. (49) Cold engine Start position, 1: Set the start/stop switch in the choke position by pulling the red control outward - upward.

@@@The diaphragm need not be completely filled. (50) Grip the front handle with your left hand. @@@@The diaphragm need not be completely filled. @@@@See instructions under the heading Assembly. @@The chain brake should be activated when starting.

@@ (52) Never start the machine indoors. Exhaust fumes can be dangerous if inhaled. @@Always hold the saw with both hands. @@All people, whether right or left handed, should use this grip. @@Stopping Stop the engine by pushing the start/stop switch down. (53) NB! The start/stop switch automatically returns to run position. @@@@Check that the rear right hand guard is not damaged. Check that the throttle lockout works correctly and is not damaged. CCheck that the stop switch works correctly and is not damaged. Check that all handles are free from oil.

Check that the anti vibration system works and is not damaged. Check that the muffler is securely attached and not damaged. @@Check that the chain catcher is in place and not damaged. @@Carry the chain saw with the bar and chain pointing backwards.



[You're reading an excerpt. Click here to read official HUSQVARNA](http://yourpdfguides.com/dref/4739670)

[445 user guide](http://yourpdfguides.com/dref/4739670)

<http://yourpdfguides.com/dref/4739670>

@@@ e. Cutting many small branches at the same time). @@Make sure you can move and stand safely. @@) in case you have to move suddenly. Take great care when working on sloping ground. Take great care when cutting a tree that is under tension.

@@@Both situations can cause serious personal injury. This section describes basic safety rules for using a chain saw. @@@@Do not attempt any task that you feel unsure of! @@See instructions under the heading How to avoid kickback. @@See instructions under the headings How to avoid kickback and Machine's safety equipment. wear personal protective equipment.

See instructions under the heading "Personal protective equipment". Sometimes chips get stuck in the clutch cover causing the chain to jam. Always stop the engine before cleaning. General rules If you understand what kickback is and how it happens then you can reduce or eliminate the element of surprise. By being prepared you reduce the risk.

Kickback is usually quite mild, but it can sometimes be very sudden and violent. Always hold the chain saw firmly with your right hand on the rear handle and your left hand on the front handle. Wrap your fingers and thumbs around the handles. You should use this grip whether you are right-handed or left-handed. This grip minimizes the effect of kickback and lets you keep the chain saw under control. Do not let go of the handles! (56) Most kickback accidents happen during limbing. Make sure you are standing firmly and that there is nothing in the way that might make you trip or lose your balance. Lack of concentration can lead to kickback if the kickback zone of the bar accidentally touches a branch, nearby tree or some other object. Have control over the workpiece. If the pieces you intend to cut are small and light, they can jam in the 1153136-49 Rev.

2 2010-04-08 Basic safety rules 1 ••Look around you: To ensure that people, animals or other things cannot affect your control of the machine. To make sure that none of the above might come within reach of your saw or be injured by falling trees. 3 NB! Follow the instructions above, but do not use a chain saw in a situation where you cannot call for help in case of an accident. 2 Do not use the machine in bad weather, such as dense fog, heavy rain, strong wind, intense cold, etc. Working in bad weather is tiring and often brings added risks, such as icy ground, unpredictable felling direction, etc. 22 – English WORKING

TECHNIQUES saw chain and be thrown towards you. Even if this does not need to be a danger, you may be surprised and lose control of the saw. Never saw stacked logs or branches without first separating them. Only saw one log or one piece at a time. Remove the cut pieces to keep your working area safe.

(57) 4 Never use the chain saw above shoulder height and avoid cutting with the tip of the bar. Never use the chain saw one-handed! (58) In order to keep control of your saw, always maintain a firm foothold. Never work on a ladder, in a tree or on any other insecure support. (59) Always use a fast cutting speed, i. Take great care when you cut with the top edge of the bar, i.

e. When cutting from the underside of the object. This is known as cutting with a pushing chain. The chain tries to push the chain saw back towards the user. If the saw chain is jamming, the saw may be pushed back at you.

(60) Unless the user resists this pushing force there is a risk that the chain saw will move so far backwards that only the kickback zone of the bar is in contact with the tree, which can lead to a kickback. (61) Cutting with the bottom edge of the bar, i. e. From the top of the object downwards, is known as cutting with a pulling chain. In this case the chain saw pulls itself towards the tree and the front edge of the chain saw body rests naturally on the trunk when cutting.

@@@@@Terms Cutting = General term for cutting through wood. limbing = Cutting branches off a felled tree. @@@(63) Make sure the object you are cutting will not split. @(65) Is there a risk of kickback? @@@@ iMPORTANT! If the chain jams in the cut: stop the engine! Don't try to pull the chain saw free. If you do you may be injured by the chain when the chain saw suddenly breaks free.

Use a lever to open up the cut and free the chain saw. The following instructions describe how to handle the common situations you are likely to encounter when using a chain saw. Limbing When limbing thick branches you should use the same approach as for cutting. Cut difficult branches piece by piece. Never use a chain saw by holding it with one hand. A chain saw is not safely controlled with one hand. Always have a secure, firm grip around the handles with both hands. ! Always use full throttle when cutting! Reduce the speed to idle after every cut (running the engine for too long at full throttle without any load, i. e.

Without any resistance from the chain during cutting, can lead to serious engine damage).

Cutting from above = Cutting with a pulling chain. Cutting from below = Cutting with a pushing chain. wARNING! Never attempt to cut logs while they are in a pile or when a couple of logs are lying together. Such procedures drastically increase the risk of kickback which can result in a serious or fatal injury. □ •

If you have a pile of logs, each log you attempt to cut should be removed from the pile, placed on a saw horse or runners and cut individually.

Remove the cut pieces from the cutting area. By leaving them in the cutting area, you increase the risk for inadvertently getting a kickback, as well as increasing the risk of losing your balance while working. (67) Cutting with a pushing chain increases the risk of kickback. See instructions under the heading How to avoid kickback. 1153136-49 Rev.

2 2010-04-08 English – 23 WORKING TECHNIQUES The log is lying on the ground. There is little risk of the chain jamming or the object splitting. However there is a risk that the chain will touch the ground when you finish the cut. (68) Cut all the way through the log from above. Avoid letting the chain touch the ground as you finish the cut. Maintain full throttle but be prepared for what might happen. (69) If it is possible (can you turn the log?) stop cutting about 2/3 of the way through the log. Turn the log and finish the cut from the opposite side. (70) The log is supported at one end. There is a high risk that it will split.

(71) Start by cutting from below (about 1/3 of the way through). Finish by cutting from above so that the two cuts meet. (72) The log is supported at both ends. There is a high risk that the chain will jam. (73) Start by cutting from above (about 1/3 of the way through). Finish by cutting from below so that the two cuts meet. (74) Clearing the trunk and preparing your retreat Delimb the stem up to shoulder height. It is safer to work from the top down and to have the tree between you and the saw. (77) Remove any undergrowth from the base of the tree and check the area for obstacles (stones, branches, holes, etc.



[You're reading an excerpt. Click here to read official HUSQVARNA](#)

[445 user guide](#)

<http://yourpdfguides.com/dref/4739670>

) so that you have a clear path of retreat when the tree starts to fall.

Your path of retreat should be roughly 135 degrees away from the intended felling direction. (78) 1 Danger zone 2 Retreat path 3 Felling direction Felling

Another very important factor, which does not affect the felling direction but does affect your safety, is to make sure the tree has no damaged or dead branches that might break off and hit you during felling. The main point to avoid is letting the tree fall onto another tree. It is very dangerous to remove a trapped tree and there is high accident risk. See instructions under the heading Freeing a tree that has fallen badly.

(76) **IMPORTANT!** During critical felling operations, hearing protectors should be lifted immediately when sawing is completed so that sounds and warning signals can be heard. **tree felling technique IMPORTANT!** It takes a lot of experience to fell a tree. inexperienced users of chain saws should not fell trees. Do not attempt any task that you feel unsure of! **Safe distance** The safe distance between a tree that is to be felled and anyone else working nearby is at least 2 1/2 tree lengths. Make sure that no-one else is in this "risk zone" before or during felling.

(75) **Felling direction** The aim is to fell the tree in a position where you can limb and cross-cut the log as easily as possible. You want it to fall in a location where you can stand and move about safely. Once you have decided which way you want the tree to fall you must judge which way the tree would fall naturally. Several factors affect this: ••••• **Lean of the tree** **Bend** **Wind direction** **Arrangement of branches** **Weight of snow** **Obstacles within the reach of the tree:** for example, other trees, power lines, roads and buildings. Look for signs of damage and rot in the stem, this makes it more probable that the tree will break and start to fall before you expect it to. Unless you have special training we advise you not to fell trees with a diameter larger than the bar length of your saw! **Felling is done using three cuts.** First you make the directional cuts, which consist of the top cut and the bottom cut, then you finish with the felling cut. By placing these cuts correctly you can control the felling direction very accurately. **Directional cuts** To make the directional cut you begin with the top cut. Aim using to the saw's felling direction mark (1) toward a goal further forward in the terrain, where you would like the tree to fall (2).

Stand on the right-hand side of the tree, behind the saw, and cut with a pull stroke. Next make the bottom cut so that it finishes exactly at the end of the top cut.

(79) The directional cuts should run 1/4 of the diameter through the trunk and the angle between the top cut and bottom cut should be 45°. The line where the two cuts meet is called the directional cut line. This line should be perfectly horizontal and at right angles (90°) to the chosen felling direction. (80) **Felling cut** The felling cut is made from the opposite side of the tree and it must be perfectly horizontal. Stand on the left side of the tree and cut on the pull stroke.

1153136-49 Rev. 2 2010-04-08 You may find you are forced to let the tree fall in its natural direction because it is impossible or dangerous to try to make it fall in the direction you first intended. 24 – English **WORKING TECHNIQUES** Make the felling cut about 3-5 cm (1.

5-2 inches) above the bottom directional cut. (81) Finish the felling cut parallel with the directional cut line so that the distance between them is at least 1/10 of the trunk diameter. The uncut section of the trunk is called the felling hinge. The felling hinge controls the direction that the tree falls in. (82) All control over the felling direction is lost if the felling hinge is too narrow or non-existent, or if the directional cuts and felling cut are badly placed.

(83) When the felling cut and directional cut are complete the tree should start to fall by itself or with the aid of a felling wedge or breaking bar. (84) We recommend that you use a bar that is longer than the diameter of the tree, so that you can make the felling cut and directional cuts with single cutting strokes. See instructions under the heading **Technical data** section to find out which lengths of bar are recommended for your saw. There are methods for felling trees with a diameter larger than the bar length. However these methods involve a much greater risk that the kickback zone of the bar will come into contact with the tree.

(4) If you must cut across tree/limb, make two to three cuts, one inch apart, one to two inches deep. (89) Continue to cut deeper until tree/limb bends and tension is released. (90) Cut tree/limb from outside the bend, after tension has been released. Kickback can happen very suddenly and violently; kicking the chain saw, bar and chain back at the user. If this happens when the chain is moving it can cause very serious, even fatal injuries. It is vital you understand what causes kickback and that you can avoid it by taking care and using the right working technique. what is kickback? The word kickback is used to describe the sudden reaction that causes the chain saw and bar to jump off an object when the upper quadrant of the tip of the bar, known as the kickback zone, touches an object. (61) Kickback always occurs in the cutting plane of the bar. Normally the chain saw and bar are thrown backwards and upwards towards the user. However, the chain saw may move in a different direction depending on the way it was being used when the kickback zone of the bar touched the object.

(7) Kickback only occurs if the kickback zone of the bar touches an object. (4) **Limbing** **Freeing a tree that has fallen badly** **Freeing a "trapped tree"** It is very dangerous to remove a trapped tree and there is high accident risk. Never try to fell the tree that is trapped. Never work in the risk zone of the hanging trapped tree. **Cutting trees and branches that are in tension** **Preparations:** Work out which side is in tension and where the point of maximum tension is (i. e.

Where it would break if it was bent even more). (86) Decide which is the safest way to release the tension and whether you are able to do it safely. In complicated situations the only safe method is to put aside your chain saw and use a winch. **General advice:** Position yourself so that you will be clear of the tree or branch when the tension is released.

(87) Make one or more cuts at or near the point of maximum tension. Make as many cuts of sufficient depth as necessary to reduce the tension and make the tree or branch break at the point of maximum tension. (88) Never cut straight through a tree or branch that is in tension! Do not use the kickback zone of the guide bar. Be extremely cautious and avoid contacting the log, other limbs or objects with the nose of the guide bar. be extremely cautious of limbs under tension.

They can spring back toward you and cause loss of control resulting in injury.



[You're reading an excerpt. Click here to read official HUSQVARNA](#)

[445 user guide](#)

<http://yourpdfguides.com/dref/4739670>

Make sure that you can stand and move about safely. Work on the left side of the trunk. Work as close as possible to the chain saw for maximum control. If possible, let the weight of the chain saw rest on the trunk.

Keep the trunk between you and the chain saw as you move along the trunk. Cutting the trunk into logs See instructions under the heading Basic cutting technique. 1153136-49 Rev. 2 2010-04-08 English – 25 MAINTENANCE General The user must only carry out the maintenance and service work described in this Operator's Manual. More extensive work must be carried out by an authorised service workshop. checking , maintaining and servicing chain saw safety equipment Note! All servicing and repair work on the machine requires special training. This is especially true of the machine's safety equipment. If your machine fails any of the checks described below we recommend you to contact our servicing dealer. carburetor adjustment Your Husqvarna product has been designed and manufactured to specifications that reduce harmful emissions. Function • The carburetor governs the engine's speed via the throttle control.

Air and fuel are mixed in the carburetor. the air/fuel mixture is adjustable. Correct adjustment is essential to get the best performance from the machine. The T-screw regulates the throttle setting at idle speed. If the T-screw is turned clockwise this gives a higher idle speed; turning it anti-clockwise gives a lower idle speed. Chain brake and front hand guard Checking brake band wear • Brush off any wood dust, resin and dirt from the chain brake and clutch drum. Dirt and wear can impair operation of the brake. (91) Regularly check that the brake band is at least 0.6 mm (0,024 inch) thick at its thinnest point. Checking the front hand guard Basic settings and running in The basic carburetor settings are adjusted during testing at the factory.

Fine adjustment should be carried out by a skilled technician. Fine adjustment of the idling speed T Adjust the idle speed with the T-screw. If it is necessary to re-adjust, turn the T-screw clockwise while the engine is running, until the chain starts to rotate. Then turn counterclockwise until the chain stops. A correctly adjusted idle speed setting occurs when the engine runs smoothly in every position.

It should also be good margin to the rpm when the chain starts to rotate. Make sure the front hand guard is not damaged and that there are no visible defects such as cracks. Move the front hand guard forwards and back to make sure it moves freely and that it is securely anchored to the clutch cover. Contact your servicing dealer, if the idle speed setting cannot be adjusted so that the chain stops at idle. Do not use the chain saw until it has been properly adjusted or repaired.

With the engine turned off, hold the chain saw over a stump or other firm object. Let go of the front handle so that the bar drops towards the stump as the chain saw rotates around the rear handle. (92) When the bar hits the stump the brake should be applied. (93) Checking the brake trigger Place the chain saw on firm ground and start it. Make sure the chain does not touch the ground or any other object. See the instructions under the heading Start and stop. (94) Grasp the chain saw firmly, wrapping your fingers and thumbs around the handles. (56) Apply full throttle and activate the chain brake by tilting your left wrist forward onto the front hand guard. Do not let go of the front handle. The chain should stop immediately.

(52) Correctly adjusted carburetor When the carburetor is correctly adjusted the machine accelerates without hesitation and the machine 4-cycles a little at max. speed. It is also important that the chain does not rotate at idle. If the L-jet is set too lean it may cause starting difficulties and poor acceleration. If the Hjet is set too lean the machine will have less power, poor acceleration and could suffer damage to the engine. 26 – English 1153136-49 Rev. 2 2010-04-08 MAINTENANCE Throttle lockout Muffler • • • Make sure the throttle control is locked at the idle setting when the throttle lockout is released. (95) Press the throttle lockout and make sure it returns to its original position when you release it. (96) Check that the throttle control and throttle lockout move freely and that the return springs work properly. (97) Start the chain saw and apply full throttle.

Release the throttle control and check that the chain stops and remains stationary. If the chain rotates when the throttle control is in the idle position you should check the carburetor idle adjustment. Never use a machine that has a faulty muffler. Regularly check that the muffler is securely attached to the machine. (100) Some mufflers are equipped with a special spark arrestor screen.

If your machine has this type of muffler, you should clean the screen at least once a week. This is best done with a wire brush. A blocked screen will cause the engine to overheat and may lead to serious damage. note! The screen must be replaced if it is damaged. If the screen is blocked the machine will overheat and this will cause damage to the cylinder and piston.

Never use a machine with a muffler that is in poor condition. Never use a muffler if the spark arrestor screen is missing or defective. (13) The muffler is designed to reduce the noise level and to direct the exhaust gases away from the operator. The exhaust gases are hot and can contain sparks, which may cause fire if directed against dry and combustible material. □ Chain catcher Check that the chain catcher is not damaged and is firmly attached to the body of the chain saw. (98) Right hand guard Starter ! Check that the right hand guard is not damaged and that there are no visible defects, such as cracks. (11) WARNING! When the recoil spring is wound up in the starter housing it is under tension and can, if handled carelessly, pop out and cause personal injury.

Care must be exercised when replacing the return spring or the starter cord. Wear protective glasses and protective gloves. Vibration damping system Regularly check the vibration damping units for cracks or deformation.

Make sure the vibration damping units are securely attached to the engine unit and handle unit. (99) Replacing the starter cord Stop switch • • Start the engine and make sure the engine stops when you move the stop switch to the stop setting. (53) NB! The start/stop switch automatically returns to run position.

In order to prevent unintentional starting, the spark plug cap must be removed from the spark plug when assembling, checking and/or performing maintenance. Loosen the screws that hold the starter against the crankcase and remove the starter. (101) Pull out the cord approx. 30 cm and hook it into the notch in the rim of the pulley. Release the recoil spring by letting the pulley rotate slowly backwards. (102) Undo the bolt in the centre of the pulley and remove the drive disc (A), drive disc spring (B) and the pulley (C).



[You're reading an excerpt. Click here to read official HUSQVARNA 445 user guide](http://yourpdfguides.com/dref/4739670)

<http://yourpdfguides.com/dref/4739670>

Insert and secure a new starter cord in the starter pulley.

wind approx. 3 turns of the starter cord on the starter pulley. Fit the starter pulley so that the end of the recoil spring (D) hooks into the starter pulley. Now assemble the drive disc spring, drive disc and the bolt in the centre of the pulley. Carry the starter cord through the hole in the starter housing and the starter handle.

Tie a good knot on the starter cord. (103) English – 27 • 1153136-49 Rev. 2 2010-04-08 MAINTENANCE Tensioning the recoil spring • Hook the starter cord in the notch in the pulley and turn the starter pulley about 2 turns clockwise. note! Check that the pulley can be turned at least a further 1/2 turn when the starter cord is pulled all the way out. (104) Stretch the line with the handle.

Move your thumb and release the line. see the figure below. (105) The filter can be cleaned more thoroughly by washing it in water and detergent. An air filter that has been in use for a long time cannot be cleaned completely. The filter must therefore be replaced with a new one at regular intervals. a damaged air filter must always be replaced. A HUSQVARNA chain saw can be equipped with different types of air filters according to working conditions, weather, season, etc. Contact your dealer for advice. Replacing the return and drive springs Spark plug Recoil spring (A) • Lift up the starter pulley. See instructions under the heading Changing a broken or worn starter cord.

Remember that the recoil spring is coiled under tension in the starter housing. Remove the cassette with the recoil spring from the starter. Lubricate the recoil spring with light oil. Fit the cassette with recoil spring in the starter. Fit the starter pulley and tension the recoil spring. The spark plug condition is influenced by: ••• Incorrect carburetor adjustment. An incorrect fuel mixture (too much or incorrect type of oil). a dirty air filter. □ • These factors cause deposits on the spark plug electrodes, which may result in operating problems and starting difficulties. If the machine is low on power, difficult to start or runs poorly at idle speed: always check the spark plug first before taking any further action.

If the spark plug is dirty, clean it and check that the electrode gap is 0.5 mm (0,020"). The spark plug should be replaced after about a month in operation or earlier if necessary. (108) Note! Always use the recommended spark plug type! Use of the wrong spark plug can damage the piston/cylinder. Check that the spark plug is fitted with a suppressor.

Drive disc spring (B) •• Undo the bolt in the centre of the pulley and remove the drive disc and the drive disc spring. Replace the drive disc spring and fit the drive disc above the spring. (106) Fitting the starter • To fit the starter, first pull out the starter cord and place the starter in position against the crankcase.

Then slowly release the starter cord so that the pulley engages with the pawls. Fit and tighten the screws that hold the starter.

Lubricating the bar tip sprocket • Air filter Lubricate the bar tip sprocket each time you refuel. Use the special grease gun and a good quality bearing grease.

(109) Needle bearing lubrication The air filter must be regularly cleaned to remove dust and dirt in order to avoid: ••••• Carburettor malfunctions Starting problems Loss of engine power Unnecessary wear to engine parts Excessive fuel consumption. Remove the air filter after taking off the air filter cover. When refitting make sure that the air filter seals tightly against the filter holder. This needle bearing must be lubricated regularly. When lubricating, remove the clutch cover by loosening the two bar nuts. Lay the saw on its side with the clutch drum upwards. Lubrication involves engine oil dripping into the centre of the clutch drum as it rotates. (110) 28 – English 1153136-49 Rev.

2 2010-04-08 MAINTENANCE Cooling system Winter use Running problems can occur when using the machine in the cold and snowy conditions caused by:

• To keep the working temperature as low as possible the machine is equipped with a cooling system. The cooling system consists of: 1 2 3 4 5 Air intake on the starter. Cylinder cover (directs cold air over the cylinder). (111) For running the machine in cold weather or powder snow, a special cover is available, which is mounted on the starter housing. This reduces the intake of cold air and prevents large amounts of snow from being sucked in. (113) NB! If the special winterising kit has been fitted or any measures have been taken to increase the temperature these changes must be reversed before the machine is used in normal temperature conditions. Otherwise there is a risk of overheating, resulting in severe damage to the engine. iMPORTANT! Any maintenance other than that described in this manual must be carried out by your servicing dealer (retailer). Partly mask the air inlet on the starter to increase the working temperature of the engine. Special measures are therefore often required: ° ° Temperature -5°C (23°F) or colder: Clean the cooling system with a brush once a week, more often in demanding conditions.

A dirty or blocked cooling system results in the machine overheating which causes damage to the piston and cylinder. □ Air Injection" centrifugal cleaning Centrifugal cleaning means the following: All air to the carburetor passes through the starter. Dirt and dust is centrifuged out by the cooling fan. (112) iMPORTANT! In order to maintain operation of the centrifugal cleaning system it must be regularly maintained. Clean the air intake to the starter, the fins on the flywheel, the space around the flywheel, inlet pipe and carburetor compartment.

1153136-49 Rev. 2 2010-04-08 English – 29 MAINTENANCE Maintenance schedule The following is a list of the maintenance that must be performed on the machine. Most of the items are described in the Maintenance section. Daily maintenance Weekly maintenance On chain saws without a catalytic converter, check the cooling system weekly. Check the starter, starter cord and return spring.

Monthly maintenance Check the brake band on the chain brake for wear. Replace when less than 0.6 mm (0,024 inch) remains at the most worn point. Check the clutch centre, clutch drum and clutch spring for wear. Clean the outside of the machine. Check that the components of the throttle control work safely.

(Throttle lockout and throttle control.) Clean the chain brake and check that it operates safely. Make sure that the chain catcher is undamaged, and replace it if necessary. The bar should be turned regularly for more even wear.

Check the lubrication hole in the bar, to be sure it is not clogged. clean the bar groove. If the bar has a sprocket tip, this should be lubricated. Check that the bar and chain are getting sufficient oil. Check the saw chain with regard to visible cracks in the rivets and links, whether the saw chain is stiff or whether the rivets and links are abnormally worn.



[You're reading an excerpt. Click here to read official HUSQVARNA 445 user guide](http://yourpdfguides.com/dref/4739670)
<http://yourpdfguides.com/dref/4739670>