




# Your PDF Guides

You can read the recommendations in the user guide, the technical guide or the installation guide for HUSQVARNA M145. You'll find the answers to all your questions on the HUSQVARNA M145 in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

User manual HUSQVARNA M145  
User guide HUSQVARNA M145  
Operating instructions HUSQVARNA M145  
Instructions for use HUSQVARNA M145  
Instruction manual HUSQVARNA M145



- GB GENERAL INFORMATION**  
**Transport**  
Remove spark plug lead. Empty the petrol tank. Before public transporting, engine oil and petrol must be removed.
- DE ALGEMEINE ERLÄUTERUNGEN**  
**Transport**  
Ziehen Sie das Zündkerzenkabel ab. Entleeren Sie den Benzintank. Bei Transport mit öffentlichen Verkehrsmitteln ist der Benzin und Öltank zu entleeren.
- FR RENSEIGNEMENTS GENERAUX**  
**Transport**  
Débrancher la bougie. Vider le réservoir d'essence. En cas de transport par un service public, il faut vider et l'essence et l'huile.
- ES INFORMACIONES GENERALES**  
**Transporte**  
Desconexión del cable de bujía. Vacíese el depósito de gasolina y, si se trata de transporte público, también el de aceite.
- NL ALGEMENE INFORMATIE**  
**Vervoer**  
De bougiekabel losmaken. Ledig de benzinetank. Bij openbaar vervoer dienen zowel olie-als benzinetank geleegd te worden.
- IT INFORMAZIONI GENERALI**  
**Transporto**  
Staccare il cavo d'accensione dalla candela. Svuotare il serbatoio della benzina. In caso di trasporto su mezzi pubblici, si deve svuotare sia la benzina che l'olio.

## Husqvarna M145



**Instruction manual**  
Please read these instructions carefully and make sure you understand them before using this machine.

**Anleitungshandbuch**  
Bitte lesen Sie diese Anleitungen sorgfältig durch und vergewissern Sie sich, daß Sie diese verstehen, bevor Sie die Maschine in Betrieb nehmen.

**Manuel d'instructions**  
Lisez très attentivement et soyez certain de comprendre ces instructions avant d'utiliser cette machine.

**Manual de las instrucciones**  
Por favor lea cuidadosamente y comprenda estas instrucciones antes de usar esta máquina.

**Instructieboekje**  
Lees deze instructies aandachtig en zorg dat u ze begrijpt voordat u deze machine gebruikt.

**Manuale di istruzioni**  
Prima di utilizzare la macchina leggete queste istruzioni con attenzione ed accertatevi di averle comprese bene.

532 40 85-75 Rev. 4  
02.26.08 BY/TH

Husqvarna

Printed  
in U.S.A.



[You're reading an excerpt. Click here to read official HUSQVARNA M145 user guide](http://yourpdfguides.com/dref/3469032)  
<http://yourpdfguides.com/dref/3469032>

**Manual abstract:**

@@ Change oil after each season or after 25 hours running time. Run the engine warm, remove the spark plug lead. Remove the drain plug from bottom of engine and drain oil. Fill with new oil. @@@@ Stop the blade if the lawnmower has to be tilted for transportation when crossing surfaces other than grass, and when transporting the lawnmower to and from the area to be mowed. Never operate the lawnmower with defective guards, or without safety devices, for example deflectors and/or grass catchers, in place. Do not change the engine governor settings or overspeed the engine. Operating the engine at excessive speed may increase the hazard of personal injury. Start the engine or switch on the motor carefully according to instructions and with feet well away from the blade. Do not tilt the lawnmower when starting the engine or switching on the motor, except if the lawnmower has to be tilted for starting.

In this case, do not tilt more than absolutely necessary and lift only the part which is away from the operator. Do not start the engine when standing in front of the discharge chute. Do not put hands or feet near or under rotating parts. Keep clear of the discharge opening at all times. Never pick up or carry lawnmower while the engine is running.

Stop the engine and disconnect the spark plug wire: - before cleaning blockages or unclogging chute; - before checking, cleaning or working on the lawnmower; - after striking a foreign object. Inspect the lawnmower for damage and make repairs before restarting and operating the lawnmower; - if the lawnmower starts to vibrate abnormally (check immediately). @@@@ Be familiar with the controls and the proper use of the equipment. @@ Local regulations may restrict the age of the operator. Never mow while people, especially children, or pets are nearby.

@@ While mowing, always wear substantial footwear and long trousers. Do not operate the equipment when barefoot or wearing open sandals. @@ - Refuel outdoors only and do not smoke while refueling. - Add fuel before starting the engine. @@@@ Add 2-3 spoonfuls of oil and spread it evenly throughout the filter. @@ Mow only in daylight or in good artificial light. Always be sure of your footing on slopes. Walk, never run. @@@@ Allow the engine to cool before storing in any enclosure. @@ If the fuel tank has to be drained, this should be done outdoors.

Tighten the screw properly when reassembling. @@ After 5 hours running time, tighten screws and nuts. check the oil. The spark plug must be at the highest point on the mower when it is tilted up. The level should be between FULL and ADD. NOTE: the dipstick must be screwed all the way down in order to indicate correct oil level. Avoid filling with too much oil. The mower should not be used on ground that slopes more than 15°. This could cause engine lubrication problems. Before mowing, objects such as twigs, toys and stones should be removed from the lawn.

Mow the lawn twice weekly during the most active periods of growth. Never cut more than 1/3 of the length of the grass, especially during dry periods. Mow with a high cutting height setting the first time. examine the result and lower the mower to the desired setting. Mow slowly or mow the grass twice if it is very long.

Fill the engine with engine oil. Fill the tank with petrol, not oil-blended. Both lead-free and lead-containing petrol may be used. Do not fill with petrol while the engine is running. To start a cold engine, push primer (3) times before trying to start.

use a firm push. This step is not usually necessary when starting an engine which has already run for a few minutes. Hold engine brake yoke to the handle and pull on starter handle quickly. To "STOP" engine, release engine brake yoke. NOTE: In cooler weather it may be necessary to repeat priming steps. In warmer weather over priming may cause flooding and engine will not start. @@ The mower can be set to different cutting levels. @@@@ Learn and understand their meaning. The handle can be set to different levels. .



[You're reading an excerpt. Click here to read official HUSQVARNA M145 user guide](http://yourpdfguides.com/dref/3469032)

<http://yourpdfguides.com/dref/3469032>