



Your PDF Guides

You can read the recommendations in the user guide, the technical guide or the installation guide for HUSQVARNA YTH 135. You'll find the answers to all your questions on the HUSQVARNA YTH 135 in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

User manual HUSQVARNA YTH 135
User guide HUSQVARNA YTH 135
Operating instructions HUSQVARNA YTH 135
Instructions for use HUSQVARNA YTH 135
Instruction manual HUSQVARNA YTH 135



YTH135



Instruction manual
Please read these instructions carefully and make sure you understand them before using this machine.

Anleitungshandbuch
Bitte lesen Sie diese Anleitungen sorgfältig durch und vergewissern Sie sich, daß Sie diese verstehen, bevor Sie die Maschine in Betrieb nehmen.

Manuel d'instructions
Merci de lire très attentivement le manuel d'instructions. Assurez-vous d'avoir tout compris avant d'utiliser ce tracteur.

Manual de las instrucciones
Por favor lea cuidadosamente y comprenda estas instrucciones antes de usar esta máquina.

Manuale di istruzioni
Prima di utilizzare la macchina leggere queste istruzioni con attenzione ed accertarsi di averle comprese bene.

Instructieboekje
Lees deze instructies aandachtig en zorg dat u ze begrijpt voordat u deze machine gebruikt.



[You're reading an excerpt. Click here to read official HUSQVARNA YTH 135 user guide](http://yourpdfguides.com/dref/3343270)

<http://yourpdfguides.com/dref/3343270>

Repeat this procedure three (3) times. move motion control lever to neutral (N) position. Stop tractor by turning ignition key to "OFF" position. engage transmission by placing freewheel control in driving position. Start engine and move throttle control to slow position. Drive tractor forward for approximately five feet then backwards for five feet. Repeat this driving procedure three times. Your tractor is now ready for normal operation. @@@@Park tractor on level surface so it will not roll in any direction.

Parking brake must be disengaged for the following procedure. @@Lower the cutting unit by moving the lever forwards. release the brake/clutch pedal slowly. @@@@@ localize and mark stones and other fixed objects to avoid collision. @@@@If the grass is too long and thick the drive speed can be increased by selecting a higher gear best cutting results the cutting unit's front edge (B) should be about 10 mm (0. 375") lower than the back edge (A). Adjust in the following way to raise the back edge: 1. Loosen the nut (1) on both the left and right levers. 2. Screw the nut (2) the same number of turns on both levers.

3. When the correct distance (A) is obtained this setting is locked with the nut (1). At the midpoint of both sides of mower, measure height from bottom edge of mower to ground. Distance "A" should be the same or within 6mm (1/4") of each other. â· If adjustment is necessary, make adjustment on one side of mower only.

NOTE: Three full turns of adjustment nut will change mower height about 1/8". Use original belts only when replacing! @@@@@@Start engine and move motion control lever until tractor does not move forward or backward. NOTE: If additional clearance is needed to get to adjustment bolt, move mower deck height to the lowest position. After above adjustment is made, if the tractor still creeps forward or backward while motion control lever is in neutral position, follow these steps: Â· Move the motion control lever 1/4 to 1/2 inch in the direction it is trying to creep. If tractor still creeps, repeat above steps until satisfied.

The fan and cooling fins of transmission should be kept clean to assure proper cooling. Do not attempt to clean fan or transmission while engine is running or while the transmission is hot. @@@@@@Engine will not start 1. Start motor will not turn engine 1. Poor contact between cable and battery pole. 3. Connection/disconnection level in wrong position. Too little or no oil in engine. Poor contact between battery poles and cables. @@Different air pressures in tires on left and right side.

The following steps should be taken when mowing season is over: Â· Clean the entire machine, especially underneath the cutting unit cover. â· Touch up all chipped paint surfaces in order to avoid corrosion. Start the engine and allow it to run until it is out of fuel. â· Remove the spark plug and pour one table spoon of engine oil into the cylinder. Pull the engine over in order to distribute the oil. Protect the battery from low temperatures. â· The machine shou.



[You're reading an excerpt. Click here to read official HUSQVARNA](http://yourpdfguides.com/dref/3343270)

[YTH 135 user guide](http://yourpdfguides.com/dref/3343270)

<http://yourpdfguides.com/dref/3343270>