



Your PDF Guides

You can read the recommendations in the user guide, the technical guide or the installation guide for ICOM IC-M402. You'll find the answers to all your questions on the ICOM IC-M402 in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

- User manual ICOM IC-M402
- User guide ICOM IC-M402
- Operating instructions ICOM IC-M402
- Instructions for use ICOM IC-M402
- Instruction manual ICOM IC-M402



VHF MARINE TRANSCEIVER

IC-M402



Easy to see! Easy to hear!

Large 2-digit Ch w/ scrolling channel names
Look at the size of the LCD with large letters and numbers! The large, easy to see display has 27x43mm (1 1/8x1 3/8in) dimensions, so channel indications are maximized. 10-character channel names and all settings are displayed at the same time.



The photo shows actual display sizes.

Easy to hear speaker
Newly designed large speaker grill improves the output of the front-mounted speaker. The result is that the audio sounds even louder than the 4.5W (typical) output capability, even over wind or engine noise.

Built-in DSC capability that meets RTCM SC101
The DSC watch function monitors Ch 70, while receiving another channel. It allows you to send a formatted distress message in an emergency. The position request function indicates a caller's position. Up to 30 DSC IDs are memorized.

Rugged waterproof construction
By spraying off any salt with fresh water after your outing, the IC-M402 is designed to work for many years.
(Equivalent to JIS 7, submersible 1m/30min, except cables)

Optional COMMAND/MC™
Our COMMAND/MC™ makes it convenient for using the IC-M402 from a separate cabin or tower. It allows you to remotely control all functions of the IC-M402 (except DSC operation). It offers its own large, easy to read LCD, is easy to hear and is also waterproof!

And more ...

- Dual and tri-watch functions for monitoring channel 16 (or channel 16 and another call channel), while receiving on another channel
- Position indication when connected to GPS (GPS is not included)
- Adjustable LCD backlighting and key illumination in 4 steps for nighttime operation
- Supplied remote function Mc, for convenient channel selection
- NOAA weather channels with alert function
- Simple and easy tag scanning system
- Available in black or white



Optional COMMAND/MC™, RA12TW

Icom Inc.



You're reading an excerpt. Click here to read official ICOM IC-M402 user guide

<http://yourpdfguides.com/dref/2468075>

Manual abstract:

) dimensions, so channel indications are maximized. @@It allows you to remotely control all functions of the IC-M402 (except DSC operation). It offers its own large, easy to read LCD, is easy to hear and is also waterproof! Easy to hear speaker The photo shows actual display size. A newly designed large speaker grill improves the output of the frontmounted speaker. @@It allows you to send a formatted distress message in an emergency. The position request function indicates a caller's position. @@for convenient channel selection · NOAA weather channels with alert function · Simple and easy tag scanning system · Available in black or white VHF MARINE TRANSCEIVER SPECIFICATIONS GENERAL RECEIVER · Frequency range : Tx 156.025157.425MHz

Rx 156.050163.

275MHz · Usable channels : All International, U.S.A.* and Canadian* channels; plus 10 weather* channels (* U.S.

A. @@@@Ch. @@@@Same as supplied. · OPC-999 EXTENSION CABLE FOR HM-127B/W 6m (20ft) of extension cable for additional lengthening for use with COMMANDMIC®. HM-127B (Black) HM-127W (White) · HM-127B/W REMOTE-CONTROL MICROPHONE Up to 21m (70ft) of freedom from the IC-M402 with two OPC-999 EXTENSION CABLES.

@@@Weight (approx.;except cables): 150g ; 5.3oz Supplied accessories : · Mic. @@COMMANDMIC is a registered trademark of Icom Inc, in the U.S.A.

Les spécifications et informations données dans ce document peuvent être modifiées sans préavis. .



[You're reading an excerpt. Click here to read official ICOM IC-M402 user guide](#)

<http://yourpdfguides.com/dref/2468075>