



Your PDF Guides


You can read the recommendations in the user guide, the technical guide or the installation guide for JBL GTO 1514D. You'll find the answers to all your questions on the JBL GTO 1514D in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

User manual JBL GTO 1514D
User guide JBL GTO 1514D
Operating instructions JBL GTO 1514D
Instructions for use JBL GTO 1514D
Instruction manual JBL GTO 1514D

JBL GTO1514D 15" Woofer – Technical Data

SPECIFICATIONS


DIAMETER: 15" (381mm)
SENSITIVITY (2.83V @ 1m): 96dB
POWER HANDLING: 350W_{RMS} (1400W_{PEAK})
FREQUENCY RESPONSE: 23Hz ~ 400Hz
NOMINAL IMPEDANCE: 2 or 8 Ohms
VOICE COIL DIAMETER: 2.0" (51.0mm)



SEALED BOX VOLUME (INCLUDES DRIVER DISPLACEMENT)



SEALED ENCLOSURE FREQUENCY RESPONSE @ 2.83V



SEALED ENCLOSURE CONE EXCURSION @ 350W



THIELE-SMALL PARAMETERS

VOICE COIL DC RESISTANCE:	R_{EVC} (OHMS)	1.90
VOICE COIL INDUCTANCE @ 1kHz:	L_{EVC} (mH)	1.20
DRIVER RADIATING AREA:	S_D (m²)	128.7
	S_D (in²)	830.00
MOTOR FORCE FACTOR:	Bl (Tm)	12.08
COMPLIANCE VOLUME:	V_{AS} (FT³)	5.69
	V_{AS} (LITERS)	161.40
SUSPENSION COMPLIANCE:	C_{MS} (mm/N)	164.00
MOVING MASS, AIR LOAD:	M_{ME} (GRAMS)	249.80
MOVING MASS, DIAPHRAGM:	M_{MD} (GRAMS)	236.10
FREE-AIR RESONANCE:	F_S (Hz)	24.90
MECHANICAL Q:	Q_{MS}	7.15
ELECTRICAL Q:	Q_{ES}	0.51
TOTAL Q:	Q_{TS}	0.47
MAGNETIC-GAP HEIGHT:	H_{MG} (mm)	0.31
	H_{MG} (mm)	8.00
VOICE COIL HEIGHT:	H_{VC} (mm)	1.45
	H_{VC} (mm)	37
MAXIMUM EXCURSION:	X_{MAX} (mm)	0.57
	X_{MAX} (mm)	14.50

Harman Consumer Group, Inc., 250 Crossways Park Drive, Woodbury, NY 11797, USA www.jbl.com
A Harman International Company



[You're reading an excerpt. Click here to read official JBL GTO 1514D user guide](http://yourpdfguides.com/dref/3930707)
<http://yourpdfguides.com/dref/3930707>

Manual abstract:

.... 1.90 VOICE COIL INDUCTANCE @ 1KHZ: L EVC (MH)
.. 1.20 DRIVER RADIATING AREA: S D (IN 2) ..
.....
. 128.7 S D (M2) 830.

00 BL (TM) 12.08 MOTOR FORCE FACTOR: COMPLIANCE VOLUME: VAS (FT3).
.....
... 5.69 VAS (LITERS).
.... 161.40 SUSPENSION COMPLIANCE: C MS (μ M/N) 164.

00 MOVING MASS, AIR LOAD: M MS (GRAMS) ... 249.80 MOVING MASS, DIAPHRAGM: M MD (GRAMS) ... 236.10 FS (HZ) ..
.....
. 24.90 FREE-AIR RESONANCE: MECHANICAL Q: QMS ...
..... 7.15 ELECTRICAL Q: Q ES .

.....
0.51 Q TS
.....
.. 0.47 TOTAL Q: HAG (IN)

.. 0.31 MAGNETIC-GAP HEIGHT: HAG (MM)
. 8.00 VOICE COIL HEIGHT: HVC (IN) ...
.....
. 1.45 HVC (MM)

.. 37 MAXIMUM EXCURSION: XMAX (IN)
. 0.57 X MAX (MM) ...
... @@.



[You're reading an excerpt. Click here to read official JBL GTO 1514D user guide](http://yourpdfguides.com/dref/3930707)
<http://yourpdfguides.com/dref/3930707>