



# Your PDF Guides

You can read the recommendations in the user guide, the technical guide or the installation guide for JVC KW-NT30. You'll find the answers to all your questions on the JVC KW-NT30 in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

## User manual JVC KW-NT30 User guide JVC KW-NT30 Operating instructions JVC KW-NT30 Instructions for use JVC KW-NT30 Instruction manual JVC KW-NT30

**JVC** KW-NT30  
Installation/Connection Manual  
Einbau-/Anschlußanleitung  
Manuel d'installation/raccordement

ENGLISH DEUTSCH FRANÇAIS

**WARNINGS**

- DO NOT touch any part or wire any cable in a device when it is powered on. Always wait for the device to cool down before you touch it.
- DO NOT open any part or wire any cable in a device when it is powered on. Always wait for the device to cool down before you touch it.
- DO NOT touch any part or wire any cable in a device when it is powered on. Always wait for the device to cool down before you touch it.

**WARNINGS**

- NEIN! Berühre keine Teile oder führe keine Kabel in einem Gerät, wenn es eingeschaltet ist. Warte immer ab, bis das Gerät abgekühlt ist, bevor du es berührst.
- NEIN! Öffne keine Teile oder führe keine Kabel in einem Gerät, wenn es eingeschaltet ist. Warte immer ab, bis das Gerät abgekühlt ist, bevor du es berührst.
- NEIN! Berühre keine Teile oder führe keine Kabel in einem Gerät, wenn es eingeschaltet ist. Warte immer ab, bis das Gerät abgekühlt ist, bevor du es berührst.

**AVERTISSEMENTS**

- N'ÉCARTÉZ pas une partie ou un câble d'un appareil qui est sous tension. Attendez toujours que l'appareil se refroidisse avant de le toucher.
- N'ÉCARTÉZ pas une partie ou un câble d'un appareil qui est sous tension. Attendez toujours que l'appareil se refroidisse avant de le toucher.
- N'ÉCARTÉZ pas une partie ou un câble d'un appareil qui est sous tension. Attendez toujours que l'appareil se refroidisse avant de le toucher.

**Notes on electrical connection:**

- Always use the correct wire gauge for the application. Use the correct wire gauge for the application. Use the correct wire gauge for the application.
- Always use the correct wire gauge for the application. Use the correct wire gauge for the application. Use the correct wire gauge for the application.
- Always use the correct wire gauge for the application. Use the correct wire gauge for the application. Use the correct wire gauge for the application.

**Notes on electrical connection:**

- Always use the correct wire gauge for the application. Use the correct wire gauge for the application. Use the correct wire gauge for the application.
- Always use the correct wire gauge for the application. Use the correct wire gauge for the application. Use the correct wire gauge for the application.
- Always use the correct wire gauge for the application. Use the correct wire gauge for the application. Use the correct wire gauge for the application.

**Notes on electrical connection:**

- Always use the correct wire gauge for the application. Use the correct wire gauge for the application. Use the correct wire gauge for the application.
- Always use the correct wire gauge for the application. Use the correct wire gauge for the application. Use the correct wire gauge for the application.
- Always use the correct wire gauge for the application. Use the correct wire gauge for the application. Use the correct wire gauge for the application.

**Parts list for installation and connection**

The following parts are provided for the unit. For more information, see the user manual.

Part Name	Quantity
Wiring harness	1
Mounting bracket	1
...	...

**Tools for installation and connection**

The following tools are required for the installation and connection of the unit.

Tool Name	Quantity
Wiring harness	1
Mounting bracket	1
...	...

**Liste des pièces pour l'installation et le raccordement**

Les pièces suivantes sont fournies avec l'appareil. Pour plus d'informations, consultez le manuel de l'utilisateur.

Part Name	Quantity
Wiring harness	1
Mounting bracket	1
...	...

**Outils pour l'installation et le raccordement**

Les outils suivants sont nécessaires pour l'installation et le raccordement de l'appareil.

Tool Name	Quantity
Wiring harness	1
Mounting bracket	1
...	...



You're reading an excerpt. Click here to read official JVC KW-NT30 user guide <http://yourpdfguides.com/dref/3940700>

**Manual abstract:**

If your vehicle does not have this system, a voltage inverter is required, which can be purchased at JVC IN-CAR ENTERTAINMENT dealers. The driver must not watch the monitor while driving. If the parking brake is not engaged, caution message about parking brake appears on the screen, and no playback picture will be shown. This warning appears only when the parking brake lead is connected to the parking brake system built in the car. It is recommended to connect speakers with a maximum power of more than 50 W (both at the rear and at the front, with an impedance of 4 to 8 ). If the maximum power is less than 50 W, change <Amplifier Gain> setting to prevent the speakers from being damaged (see page 67 of the INSTRUCTIONS). To prevent short circuits, cover the terminals of the UNUSED leads with insulating tape. The heat sink becomes very hot after use. Be careful not to touch it when removing this unit. At the time of installation, be sure to fix all wires (wires both from this unit and from the car itself) in a way that no wires can come into contact with the heat sink on the rear of the unit.

The following parts are provided for this unit. If anything is missing, contact your dealer immediately. The following illustration shows a typical installation. If other screws are used, parts could become loose or damaged. When tightening screws or bolts, be careful not to pinch any connection cord.

Make sure not to block the fan on the rear to maintain proper ventilation when installing the unit. When installing the unit without using the sleeve and brackets Use flat head screws or round head screws, depending on the installation location. When you use round head screws to install the unit, use the screws removed from the metal protection plates (see below). When you use screws other than those supplied, use 8 mm-long screws. If longer screws are used, they could damage the unit.

Make sure to use the round head screws (M2. 6 x 3 mm) originally attached to the unit. If longer screws are used, they could damage the unit. Beneath a non-metallised\*2 window, fix the aerial on the dashboard. Wire the aerial cord so as not to allow the rain to leak in. The aerial must be specially secured for higher speeds. BEFORE connecting the speaker leads of the power cord to the speakers, check the speaker wiring in your car. ENGLISH If your car is equipped with the ISO connector / Wenn Ihr Fahrzeug mit dem ISO-Steckverbinder ausgestattet ist / Si votre voiture est équipée d'un connecteur ISO For some VW/Audi or Opel (Vauxhall) automobiles / Bei bestimmten VW-/Audi- order Opel- (Vauxhall-) Fahrzeugen / Pour certaine voiture VW/Audi ou Opel (Vauxhall) You may need to modify the wiring of the supplied power cord as illustrated. Contact your authorized car dealer before installing this unit. From the car body Von der Fahrzeugkarosserie De la carrosserie de la voiture ISO connector of the supplied power cord ISO-Stecker des mitgelieferten Stromkabels Connecteur ISO pour le cordon d'alimentation fourni View from the lead side Von der Kabelseite aus gesehen Vue à partir du côté des fils Use modified wiring 2 if the unit does not turn on.

Incorrect connection may cause serious damage to this unit. The leads of the power cord and those of the connector from the car body may be different in color. In this case, "Speed pulse not detected. System works as GPS only mode until speed pulse is detected. " appears on the screen when the power is turned on. We recommend to attach the microphone near the steering wheel using the microphone holder. Do not use any microphone other than the one supplied. You can supply the power to the amplifiers by connecting the remote leads (blue with white stripe) of this unit and amplifiers. (To connect more than one amplifier using the remote leads, Yconnectors need to be separately purchased. ) - Disconnect the speakers from the unit, and connect them to the amplifier.

Leave the speaker leads of the unit unused. To do it, a JVC's OE remote adapter (not supplied) which matches with your car is required. Power cannot be turned on. Noise interfere with sounds. \* Is the rear ground terminal connected to the car's chassis using shorter and thicker cords? This unit does not work at all.



[You're reading an excerpt. Click here to read official JVC KW-NT30 user guide](http://yourpdfguides.com/dref/3940700)

<http://yourpdfguides.com/dref/3940700>