

Manual abstract:

If you experience problems during installation, consult your JVC car audio dealer. Disconnect the battery's negative terminal and make all electrical connections before installing the unit. Otherwise, change the <AMP GAIN> setting. (See page 21 of the INSTRUCTIONS. To prevent a short circuit, do not remove the caps on the ends of the unconnected wires or the terminals. If the fuse blows, first make sure the wires are not touching to cause a short circuit, then replace the old fuse with one that has the same rating. Install this unit in the console of your vehicle. Mount the unit so that the mounting angle is 30° or less. Be sure to ground this unit to the car's chassis again after installation. After the unit is installed, check whether the brake lamps, blinkers, wipers, etc.

On the car are working properly. Metal part such as the heat sink and enclosure become hot. B Brackets (fitted to the main unit when shipped) / Supports (fixés à l'appareil lors de l'expédition) . (x1) In-dash mounting / Montage encastré (A) Installing with the supplied sleeve / Installation avec le manchon fourni Audio system originally installed in the car / Système audio installé à l'origine dans la voiture Car dashboard / Tableau de bord de la voiture (B) Installing with the mounting brackets from the car / Installation avec les supports de montage de la voiture Audio system originally installed in the car / Système audio installé à l'origine dans la voiture Firmly attach the ground wire to the metallic body of the car using the screw originally fixed to the metallic body of the car. / Fixez solidement le fil de mise à la masse au châssis métallique de la voiture en utilisant une vis fixée à l'origine au châssis métallique de la voiture.

*1 Four of these screws are fitted to the main unit when shipped. Keep these screws for installation use if necessary. *2 For connecting the supplied USB Bluetooth adapter (KS-UBT1), see page 11 of the INSTRUCTIONS. Install the unit at an angle of less than 30°. installez l'appareil avec un angle de moins de 30°.

Are the red and black leads connected correctly? Power cannot be turned on. Is the yellow lead connected? No sound from the speakers. Is the speaker output lead short-circuited? ; Have you reset your unit? • Sound is distorted. Is the speaker output lead grounded? • This unit becomes hot. Is the speaker output lead grounded? This unit does not work at all. Have you reset your unit? Connecting the external amplifiers and/or subwoofer / Connexion d'amplificateurs extérieurs et/ou d'un caisson de grave Remote lead / Fil d'alimentation à distance Signal cord / Cordon de signal *1 JVC Amplifier / JVC Amplificateur FRONT : REAR : Extension lead / Fil prolongateur *1 To the blue (white stripe) lead of the unit / Au fil bleu (bande blanche) de l'appareil To front speakers / Aux enceintes avant To rear speakers or subwoofer / Aux enceintes arrière ou caisson de grave *3 Reset the unit. / Réinitialisez l'autoradio. LINE OUT Rear ground terminal / Borne arrière de masse MIC (Microphone input terminal / Prise d'entrée de microphone) Connecting the microphone unit / Connexion du microphone Adjust the angle / Ajustez l'angle From Radio aerial / À partir de l'antenne radio REAR L R FRONT USB cable (approx. 1. Contact your authorized car dealer before installing this unit.

(Blue , white stripe) / Fil d'alimentation à distance/ antenne automatique , 200 mA max. (Bleu, bande blanche) To car light control switch (Orange, white stripe) / À l'interrupteur d'éclairage de la voiture (Orange, bande blanche) Accessory terminal (Red) / Prise accessoire (Rouge) Metallic body/chassis of the car (Black) / Corps métallique/châssis de la voiture (Noir) Modified wiring 1 / Câblage modifié 1 Use modified wiring 2 if the unit does not turn on. / Utilisez le câblage modifié 2 si l'appareil ne se met pas sous tension. A5 A6 Modified wiring 2 / Câblage modifié 2 A7 A8 IMPORTANT/IMPORTANT: A custom wiring harness (separately purchased) which is suitable for your car is recommended for connection between the unit and your car. *3 Make the <L/O MODE> setting accordingly, see page 21 of the INSTRUCTIONS. .



[You're reading an excerpt. Click here to read official JVC KW-R600BT user guide](http://yourpdfguides.com/dref/4539221)
<http://yourpdfguides.com/dref/4539221>