



Your PDF Guides

You can read the recommendations in the user guide, the technical guide or the installation guide for KENWOOD KVT-536DVD. You'll find the answers to all your questions on the KENWOOD KVT-536DVD in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

User manual KENWOOD KVT-536DVD
User guide KENWOOD KVT-536DVD
Operating instructions KENWOOD KVT-536DVD
Instructions for use KENWOOD KVT-536DVD
Instruction manual KENWOOD KVT-536DVD

KENWOOD

MONITOR WITH DVD RECEIVER

KVT-536DVD
KVT-536DVDM

INSTALLATION MANUAL

Kenwood Corporation

© 2014-2015 KENWOOD CORPORATION



[You're reading an excerpt. Click here to read official KENWOOD KVT-536DVD user guide](http://yourpdfguides.com/dref/5534230)
<http://yourpdfguides.com/dref/5534230>

Manual abstract:

indd 1 09.10.26 4:08:34 PM Accessories 1

..1 2 ...

.....

..1 3

..2 4

..1 5 ...

.....

..4 6

..4 2 | KVT-536DVD/KVT-536DVDM B54-4752-00_00_KVT-536DVD_En.indd 2 09.10.26 4:08:34 PM Installation Procedure 1. To prevent a short circuit, remove the key from the ignition and disconnect the - battery. 2. Make the proper input and output wire connections for each unit. 3. Connect the speaker wires of the wiring harness. 4. Connect the wiring harness wires in the following order: ground, battery, ignition. 5. Connect the wiring harness connector to the unit.

6. Install the unit in your car. 7. Reconnect the - battery. 8.

•••••The unit may be damaged or fail to work if you share the - wires or ground them to any metal part in the car. • When only two speakers are being connected to the system, connect the connectors either to both the front output terminals or to both the rear output terminals (do not mix front and rear). For example, if you connect the + connector of the left speaker to a front output terminal, do not connect the - connector to a rear output terminal. • After the unit is installed, check whether the brake lamps, blinkers, wipers, etc. on the car are working properly. • Mount the unit so that the mounting angle is 30° or less. • This unit has the cooling fan (page 5) to decrease the internal temperature. Do not mount the unit in a place where the cooling fan of the unit are blocked. Blocking these openings will inhibit the cooling of the internal temperature and result in malfunction. 2WARNING If you connect the ignition wire (red) and the battery wire (yellow) to the car chassis (ground), you may cause a short circuit, that in turn may start a fire.

2CAUTION • Install this unit in the console of your vehicle. Do not touch the metal part of this unit during and shortly after the use of the unit.

•••••Do not use your own screws. Use only the screws provided. If you use the wrong screws, you could damage the unit. •• Therefore, the speaker wire should be checked. •••••@ CONT To rear left speaker To rear right speaker English | 5

B54-4752-00_00_KVT-536DVD_En.indd 5 09.10.26 4:08:38 PM Optional Accessory Connection iPod (commercially available) KCA-iP301V (Optional Accessory) Audio Input Resistance-free stereo type mini plug (3.

5Φ) iPod AUDIO IN Audio Output (Black) Visual Input (Yellow) Resistance-free mini plug (3.5Φ) Visual Output (Yellow) USB terminal USB terminal To KCA-BT200 (Optional Accessory) TV Tuner (Optional Accessory) TV ANTENNA INPUT Connection cable (Included in the Navigation System) Navigation System (Optional Accessory) 6 | KVT-536DVD/KVT-536DVDM B54-4752-00_00_KVT-536DVD_En.indd 6 TO MONITOR UNIT Connection cable (Included in the TV tuner)/Navigation units that can be connected to this unit. (As of December, 2009): □KNA-G630 □KNA-G630CN For latest information, access the www.kenwood.com/cs/ce/.

09.10.26 4:08:39 PM Installation/Removing the Unit Installation Bend the tabs of the mounting sleeve with a screwdriver or similar utensil and attach it in place. Make sure that the unit is installed securely in place.

If the unit is unstable, it may malfunction (eg, the sound may skip). English | 7 B54-4752-00_00_KVT-536DVD_En.indd 7 09.10.26 4:08:40 PM Installation/Removing the Unit Removing the Hard Rubber Frame (escutcheon) 1. Engage the catch pins on the removal tool 3 and remove the two locks on the lower level. Lower the frame and pull it forward as shown in the figure. Escutcheon (Accessory 4) Removal Tool (Accessory 3) Removing the Unit 1. Remove the hard rubber frame by referring to the removal procedure in the section <Removing the Hard Rubber Frame>. 2.

Insert the two removal tools 3 deeply into the slots on each side, as shown. Removal Tool (Accessory 3) Catch Lock/• The frame can be removed from the top side in the same manner. 3. Lower the removal tool toward the bottom, and pull out the unit halfway while pressing towards the inside. 2. •••••Use only the screws provided. ••Mount the bracket at each side. Car Bracket Accessory 5 (M5x6mm) Accessory 5 (M5x6mm) Screws (included in audio unit package) Screws (included in audio unit package) 2. Bend each end of case to fix the bracket. Use a flat-blade screwdriver or pliers, and bend each case tab into the hole of installation bracket to fix the bracket.

10 | KVT-536DVD/KVT-536DVDM B54-4752-00_00_KVT-536DVD_En.indd 10 09.10.26 4:08:42 PM B54-4752-00_00_KVT-536DVD_En.indd 11 09.10.26 4:08:42 PM B54-4752-00_00_KVT-536DVD_En.indd 12 09.10.26 4:08:43 PM .



[You're reading an excerpt. Click here to read official KENWOOD](http://yourpdfguides.com/dref/5534230)

[KVT-536DVD user guide](http://yourpdfguides.com/dref/5534230)

<http://yourpdfguides.com/dref/5534230>