



# Your PDF Guides

You can read the recommendations in the user guide, the technical guide or the installation guide for LA CROSSE TECHNOLOGY WS2801. You'll find the answers to all your questions on the LA CROSSE TECHNOLOGY WS2801 in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

**User manual LA CROSSE TECHNOLOGY WS2801**  
**User guide LA CROSSE TECHNOLOGY WS2801**  
**Operating instructions LA CROSSE TECHNOLOGY WS2801**  
**Instructions for use LA CROSSE TECHNOLOGY WS2801**  
**Instruction manual LA CROSSE TECHNOLOGY WS2801**

**WS-2801-IT**  
**Wireless Professional Weather Center**  
Instructions Manual

**TABLE OF CONTENTS**

**INTRODUCTION** ..... 35

**INVENTORY OF CONTENTS** ..... 35

**FEATURES**..... 36

WIRELESS DISPLAY ..... 36

THERMO-HYGRO SENSOR ..... 36

WIND SENSOR ..... 36

RAIN SENSOR ..... 37

**SETTING UP** ..... 37

**ADDITIONAL NOTES FOR THE SOLAR WIND AND RAIN SENSORS MODES** ..... 38

IDLE MODE ..... 38

STOP MODE ..... 38

**MOUNTING THE SENSORS AND PLACEMENT OF THE WIRELESS DISPLAY**..... 39

WIND SENSOR ..... 40

RAIN SENSOR ..... 40

THERMO-HYGRO SENSOR ..... 40

HEAVY WEATHER PC SOFTWARE ..... 40

**FUNCTION KEYS**..... 41

SET KEY ..... 41

▲ UP ARROW KEY ..... 41

▼ DOWN ARROW KEY ..... 41

ALARM KEY ..... 41

MIN/MAX KEY ..... 41

**LCD SCREEN** ..... 42

MODE 1 DISPLAY: ..... 42

MODE 2 DISPLAY: ..... 42

**MANUAL SETTINGS** ..... 43

LCD CONTRAST SETTING ..... 43

MANUAL TIME SETTING ..... 43



[You're reading an excerpt. Click here to read official LA CROSSE TECHNOLOGY WS2801 user guide](http://yourpdfguides.com/dref/3678203)  
<http://yourpdfguides.com/dref/3678203>

*Manual abstract:*

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
.....

*... 36 WIND SENSOR .....*

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

*..... 36 RAIN SENSOR .*

.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
.....

*..... 37 SETTING UP: .....*

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
. 37 ADDITIONAL NOTES FOR THE SOLAR WIND AND RAIN SENSORS MODES:....  
.. 38 IDLE MODE .....

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
... 38 STOP MODE ..

.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

.. 38 MOUNTING THE SENSORS AND PLACEMENT OF THE WIRELESS DISPLAY:..... 39 WIND SENSOR ...

.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
.....

.. 40 RAIN SENSOR .....

.....  
.....  
.....  
.....

.....  
.....

.....  
.....  
.....  
.....  
.....

..... 40 THERMO-HYGRO SENSOR ..

.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

... 40 HEAVY WEATHER PC SOFTWARE.....

.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

. 40 FUNCTION KEYS:.....

.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

41 SET KEY.....

.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

.....  
.....  
.....  
..... 41 UP ARROW KEY....

.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

..... 41 DOWN ARROW KEY ....

.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

..... 41 ALARM KEY .

.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

..... 41 MIN/MAX KEY .

.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

.....  
.....  
.....  
.....  
.....  
.....  
*. 41 LCD SCREEN...*  
.....

.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

..... *42 MODE 1 DISPLAY: ...*

.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

.. *42 MODE 2 DISPLAY: ...*

.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

..... *42 MANUAL SETTINGS...*

.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

.....

.....

.....

.....

.....

..... 43 LCD CONTRAST SETTING...

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

... 43 MANUAL TIME SETTING .....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.... 43 32 12/24 HOUR TIME DISPLAY SETTING .....

.....

.....

.....

.....

.....

.....

.....

.. 44 CALENDAR SETTING ...

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.. 44 °F/°C TEMPERATURE UNIT SETTING ...

.....

.....  
.....  
.....  
.....

..... 45 WIND SPEED UNIT SETTING .....

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

..... 45 RAINFALL UNIT SETTING .....

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

..... 45 RELATIVE AIR PRESSURE UNIT SETTING .....

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

..... 46 RELATIVE PRESSURE REFERENCE VALUE SETTING.....

.....  
.....  
.....  
.....

..... 46 WEATHER TENDENCY SENSITIVITY LEVEL SETTING .....

.....  
.....  
.....  
.....

..... 46 STORM WARNING THRESHOLD VALUE SETTING...

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....



.....  
..... 47 STORM ALARM ON/ OFF SETTING.....

.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

..... 47 WIND DIRECTION DISPLAY TYPE SETTING..

.....  
.....  
.....  
.....  
.....  
.....  
.....

..... 48 FACTORY RESET PROCEDURE ....

.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

... 48 TO EXIT THE MANUAL SETTING MODE.....

.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

..... 49 WEATHER ALARM OPERATIONS..

.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

. 49 THE FOLLOWING WEATHER ALARMS CAN BE ADJUSTED IN ALARM SETTING MODE ....

.....  
.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
*. 49 DEFAULT WEATHER ALARM VALUES ....*  
.....

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

*... 50 PRESSURE ALARMS.....*

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

*..... 50 INDOOR TEMPERATURE ALARMS .*

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

*.. 50 INDOOR HUMIDITY ALARMS..*

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

*..... 51 OUTDOOR TEMPERATURE ALARMS .....*

.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
... 51 OUTDOOR HUMIDITY ALARMS.

.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

... 52 WIND GUST ALARM .....

.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
52 WIND DIRECTION ALARM .....

.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

..... 53 24H RAINFALL ALARM ...

.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
.....

.....  
.....  
*53 HYSTERESIS .....*

.....  
.....

.....  
.....  
.....

.....  
.....  
.....

.....  
.....  
.....

*. 54 WEATHER FORECAST AND WEATHER TENDENCY .....*

.....  
.....  
.....

.....  
.....

*... 54 WEATHER FORECASTING ICONS: ..*

.....  
.....  
.....  
.....

.....  
.....  
.....

*. 54 WEATHER TENDENCY INDICATOR.....*

.....  
.....  
.....

.....  
.....  
.....

*... 55 AIR PRESSURE HISTORY (ELECTRONIC BAROMETER WITH BAROMETRIC PRESSURE TREND)..*

.....  
.....

.....  
.....  
.....

.....  
.....  
.....

.....  
.....  
.....

*55 WIND DIRECTION AND WIND SPEED MEASUREMENT.....*

.....  
.....  
.....  
.....

*56 RAINFALL MEASUREMENT .....*

.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
.....

*..... 56 33 VIEWING THE MIN/MAX WEATHER DATA.....*

.....  
.....  
.....  
.....

.....  
.....  
.....

*..... 57 RESET THE MINIMUM AND MAXIMUM WEATHER DATA...*

.....  
.....  
.....  
.....

*..... 57 TOTAL RAINFALL AMOUNT.....*

.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

*57 CARE AND MAINTENANCE:.....*

.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
.....

..... 57 SPECIFICATIONS: ...

.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

58 INDOOR TEMPERATURE.....

.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

..... 58 OUTDOOR TEMPERATURE / DEW POINT .

.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

58 INDOOR HUMIDITY .....

.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

... 58 OUTDOOR HUMIDITY ..

.....  
.....  
.....  
.....  
.....

.....  
.....  
.....  
.....

.....  
.....  
.....

.. 58 WIND SPEED/ GUST .....

.....  
.....  
.....

.....  
.....  
.....

.....  
.....  
.....

..... 58 WIND CHILL/ DEW POINT ..

.....  
.....  
.....

.....  
.....  
.....

.....  
.....  
.....

..... 58 RAINFALL (24H, TOTAL) ....

.....  
.....  
.....

.....  
.....  
.....

.....  
.....  
.....

..... 59 OUTDOOR DATA RECEPTION ....

.....  
.....  
.....

.....  
.....  
.....

.....

.....  
*. 59 AIR PRESSURE ...*

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

*59 TRANSMISSION RANGE .....*

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

*59 POWER CONSUMPTION.....*

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

*59 DIMENSIONS (L X W X H) .....*

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

*..... 59 LIABILITY DISCLAIMER..*

.....

.....

.....



.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....  
.....

.. 59 34 INTRODUCTION ongratulations on purchasing this state-of-the-art weather station. Featuring time, date, calendar, weather forecast, wind gust and wind speed, indoor/outdoor temperature and humidity, air pressure and rainfall, this weather station will provide you with various weather information and weather forecasts. Heavy Weather Pro software allows you to use a PC to monitor and record weather data received from your wireless weather station via a proprietary USB device that was provided with your 2800 series weather station. You can monitor and record a variety of data collected by your weather station including both indoor and external values sampled by the various weather station sensors. You can also review weather history data, and analyze trends and tendencies over time using the software's charts and graphing features. Download the free Heavy Weather Pro PC software at: [www.lacrossetechnology.fr](http://www.lacrossetechnology.fr)

**C INVENTORY OF CONTENTS** Carefully open the package and check that the following contents are complete: Wind Sensor Rain Sensor ThermoHygro Sensor Wireless Display USB Transceiver . . . . . Mast holder Right angle · adaptor 1 x U-bolts 2 Washers + 2 Nuts Plastic Reset Rod · Base sensor, funnel top cover and battery cover (preassembled) . . . · Rain protection · cover Wall mount adapter Mounting screws Plastic anchors for screws USB wireless interface for PC Foldable stand 35 **FEATURES: WIRELESS DISPLAY** . . . . Time display in 12/24 hour time format Automatic time and date (PC time) update from USB transceiver if connected Calendar display (date, month, year) Weather forecast with 3 weather icons (sunny, cloudy, and rainy) with weather tendency indicator Temperature display in °C/°F Humidity display in RH% Dew point display in °C/°F . . . . . Wind chill display in °C/°F MIN/MAX values of indoor/outdoor temperature, indoor/outdoor humidity, dew point display with time and date of recording Relative air pressure reading in hPa/ inHg and 24h/72h history graph selectable Wind speed displayed in km/h, m/s, mph, knots, and Beaufort scale Wind speed & direction with LCD compass display (16 steps/ 22.

5 degree) MAX records for wind gust with time & date of recording Rainfall display in mm/inch Rainfall data for total rain, last hour, last 24h, last week, last month Weather alarm modes: temperature, humidity, wind gust, wind direction, air pressure, 24h rain and storm warning LCD contrast setting Storage of 1797 sets of weather records with user selectable recording interval from 1 minute to 24 hours **THERMO-HYGRO SENSOR** · · Transmission of temperature and humidity data Transmission range: about 100 meters (Open field, free of obstructions) **WIND SENSOR** · · · 100% solar-powered with built-in rechargeable alkaline power cell High-efficient solar panels maintain operation throughout all seasons Transmission range: about 100 meters (Open field, free of obstructions) 36 **RAIN SENSOR** · · · · 100% solar-powered with built-in rechargeable alkaline power cell High-efficient solar panels maintain operation throughout all seasons Self-emptying bucket Transmission range: about 100 meters (Open field, free of obstructions). **SETTING UP: IMPORTANT:** Make sure to observe the correct polarity when inserting batteries. The "+" markings on the batteries must line up with the diagrams inside the battery compartments. Inserting the batteries incorrectly may result in permanent damage to the units. During the setup process, place the wireless display and the outdoor sensors on a surface with 1-3 meters between the sensors and the display.

Only use Alkaline Batteries for the Wireless Display and Thermo-hygro sensor, rechargeable batteries may not work. Press Reset Button on Bottom 1. It is important to allow sufficient light to reach the solar of the Wind Sensor (Solar Panel Must Face Light) panel while activating the wind sensor. Make sure the lights are on tery voltage is low, the sensor(s) 38 enters the IDLE mode. User should place the sensor(s) under a bright environment in order to charge up the rechargeable batteries.

**MOUNTING THE SENSORS AND PLACEMENT OF THE WIRELESS DISPLAY: IMPORTANT:** Ensure that all of the sensor data can be received at the intended mounting locations before you drill mounting holes. The outdoor sensors have a wireless range of 100 meters. Keep in mind that the 100 meters range equates to an open air scenario with no obstructions. Each obstruction (roof, walls, floors, ceilings, etc.) will reduce the range. Wind Sensor Wind Sensor Solar Panels Solar Panels True Faces Faces True South South 100m (max.) 25 m (max.) Solar Rain Sensor 100m (max.



[You're reading an excerpt. Click here to read official LA CROSSE TECHNOLOGY WS2801 user guide](http://yourpdfguides.com/dref/3678203)  
<http://yourpdfguides.com/dref/3678203>

\* Wind and Rain Sensors should be located on the same side of the house as the Thermo-hygro Sensor to ensure the signal strength 100 m (max.) The thermo-hygro sensor measures outdoor temperature & humidity and collects the data from the wind and the rain sensors and sends all outdoor weather data to the wireless display, so the thermo-hygro sensor must be within the 100 meters wireless range of the wireless display.

This allows the wind and rain sensors to be placed relative to the thermo-hygro sensor rather than the wireless display. See Wireless Data Diagram above. The wind and rain sensors must be mounted within the 100 meters wireless range of the thermo-hygro sensor and on the same side of the house. The wireless display must be within the 25 meters wireless range of the USB transceiver to send weather data to the PC. If the sensor wireless icons drop from the display as you move them into their intended locations, the sensors may be too far from the wireless display. Try moving the wireless display or the sensors closer and wait a few minutes to see if the wireless icons display again. If the wireless icons are still not displayed after re-positioning the sensors or the wireless display, press and hold the UP ARROW key for 2 seconds to re-synchronize the wireless display with the sensors. WIND SENSOR The wind sensor must be installed with the front of the sensor (the solar panel) facing true South, or the reported wind direction will not be accurate. Mount within the 100 meters wireless range of the thermo-hygro sensor and on the same side of the house. The roof may or may not be an ideal mounting location.

Secure the main unit to the shaft of the mast holder. Use the right-angle adaptor if the wind sensor will be mounted on a horizontal mast or surface. Fasten the wind sensor to a suitable mast using the two U-bolts, washers and nuts included. Note: Mount the wind sensor onto a mast so the wind can reach the sensor unobstructed from all directions for an accurate reading. The ideal mast is between 15.

75mm and 33mm in diameter. The wind sensor DOES NOT have replaceable batteries, it consumes solar power and charges the internal battery pack automatically. RAIN SENSOR The rain sensor should be mounted on a level surface in an open area and bright area within the 100 meters wireless range of the thermo-hygro sensor and on the same side of the house. Mount the rain sensor at least 0.30 meter off the ground level for optimum wireless transmission.

The rain sensor should be accessible to allow for period cleaning of debris or insects. THERMO-HYGRO SENSOR The thermo-hygro sensor is "weather resistant", but not "water proof". To ensure an extended life of your sensor, mount it in a semi-covered place out of the elements. An ideal location for the thermo-hygro sensor is under the eaves on the North side of the house to avoid the effects of sunlight. Mount the sensor 0.5 meter down from the eaves to ensure optimum performance. This way the weather data collected by the sensor will not be affected by the temperature of the air coming out of the attic. To wall mount the thermo-hygro sensor, fix the wall holder onto the desired wall using the included screws, plug the sensor firmly into the wall holder and replace the rain cover if it is not already in place. Note: After mounting the units, if the weather data is not received, press and hold the UP ARROW key for 2 seconds to synchronize the wireless display to the sensors. HEAVY WEATHER PC SOFTWARE Use your PC to store and graph the latest weather data collected by the weather station.

Download the Heavy Weather PC software from [www.lacrossetechnology.fr](http://www.lacrossetechnology.fr) The Heavy Weather Pro User's Guide available on the download page details the computer requirements, installation and usage instructions. 40 FUNCTION KEYS: SET KEY · Press and hold for 3 seconds to enter the SET mode, where the following can be changed: LCD contrast, Manual time setting, 12/24 hour time display, Calendar setting, °F/°C temperature unit, Wind speed unit, Rainfall unit, Pressure unit, Relative pressure reference setting, Weather tendency threshold setting, Storm warning threshold setting and Storm Alarm On/ Off setting.

Wind direction display type, Factory reset · Press to toggle between the display of Mode 1 or Mode 2: · Mode 1: "Wind speed + outdoor temp + 24 hr. pressure history graph" · Mode 2: "Gust + Dew Point temp + 72 hr. pressure history graph" · In the weather alarm setting mode, press and release to switch the weather alarm On/ Off · In the weather alarm setting mode, press and hold to adjust the weather alarm value · Stop the alarm during the time alarm or weather alarm ringing UP ARROW KEY · Press to toggle between the display of seconds or date in the time display · Press to increase the level of different settings in SET mode · Stop the alarm during the time alarm or weather alarm ringing · Press to reset the MIN/MAX record when in MIN/MAX display mode · Press and hold for 2 seconds to synchronize the Wireless Display to the sensors DOWN ARROW KEY · Press to switch the rainfall display mode: Total, 1h, 24h, week, month · Press to decrease the level of different settings in SET mode · Stop the alarm during the time alarm or weather alarm ringing · Press and hold for 2 seconds to synchronize the Wireless Display to the USB transceiver ALARM KEY · Press to enter the time alarm and weather alarm setting mode · Confirm particular alarm setting · Press to exit the manual setting mode · Stop the alarm during the time alarm or weather alarm ringing · Press to exit max/min record display mode MIN/MAX KEY · Press to display minimum and maximum records of various weather data · Stop the alarm during the time alarm or weather alarm ringing · Press to exit the manual setting mode · Press to exit the weather alarm setting mode 41 LCD SCREEN When the signal from the transmitter is successfully received by the Weather Station, the icon will be switched on. (If not successful, the icon will not be shown on the LCD). User can see whether the last reception was successful ( icon is on) or not ( icon is off). Blinking of the icon shows that a reception is in process. Barometric Pressure Pressure History Graph Indoor Temperature and Humidity Wind Direction Wind Speed Time and Date Forecast Icon and Weather Tendency Arrows Outdoor Temperature and Humidity Wind Chill Rainfall Amount · Press the SET key to toggle between Mode 1 and Mode 2 display: MODE 1 DISPLAY: · · · Pressure history graph displays 24 hour history Outdoor temperature displayed in the outdoor section Wind speed displayed in the wind section MODE 2 DISPLAY: · · · Pressure history graph displays 72 hour history Dew point displayed in the outdoor section Wind gust displayed in the wind section 42 MANUAL SETTINGS

Press and hold the SET key for 3 seconds to enter the SET mode.



[You're reading an excerpt. Click here to read official LA CROSSE TECHNOLOGY WS2801 user guide](http://yourpdfguides.com/dref/3678203)  
<http://yourpdfguides.com/dref/3678203>

If you wait 30 seconds without pressing any keys while in SET mode, the display will automatically return to Mode 1 display. While in SET mode, each press of the SET key will advance to the next SET mode item. 1. LCD contrast setting 2. Manual time setting 3.

12/24 hour time display 4. Calendar setting 5. °F/°C temperature unit setting 6. Wind speed unit 7. Rainfall unit setting 8.

Air pressure unit setting 9. Relative pressure reference value setting 10. Weather tendency threshold value 11. Storm warning threshold value 12. Storm alarm On/ Off setting 13. Wind direction display type 14. Factory Reset LCD CONTRAST SETTING The LCD contrast can be set within 8 levels, from "Lcd 1" to "Lcd 8" (default setting is "Lcd 5"): 1. Press and hold the SET key for 3 seconds, the contrast level digit will start flashing. 2. Press the UP ARROW key or DOWN ARROW key to adjust the level of contrast.

3. Press the SET key to confirm and to enter the MANUAL TIME SETTING. MANUAL TIME SETTING The time will be updated automatically with the time from the computer when the display is synchronized with the USB transceiver and connected to the Heavy Weather Pro software. The time can also be set manually by following the steps below: 1. The hour digit is flashing. 2. Press the UP ARROW key or DOWN ARROW key to set the hour. Continually holding the key will increase the digit faster. 3. Press the SET key to switch to the minutes.

The minute digit will start flashing. 4. Press the UP ARROW key or DOWN ARROW key to set the minute. Continually holding the key will increase the digit faster. 5.

Press the SET key to confirm and to enter the 12/24 HOUR TIME DISPLAY SETTING. 12/24 HOUR TIME DISPLAY SETTING The time can be set to view as 12-hour or 24-hour format. The default time-display mode is 24-h. To set to 12-h time display: 1. The 24h or 12h digit is flashing 2.

Press the UP ARROW key or DOWN ARROW key to toggle the value. 3. Press the SET key to confirm and to enter the CALENDAR SETTING. Note: · 24h time display format will show: Day/ Month/ Year · 12h time display format will show: Month/ Day/ Year CALENDAR SETTING The default date is 1. 1. of year 2009. @@The date can also be set manually by following the steps below. 1. The year digit starts flashing. 2.

Press the UP ARROW key or DOWN ARROW key to set the year. The range runs from "00" (2000) to "99" (2099). Hold the key in to change the value faster. 3. Press the SET key to confirm the year and enter the month setting. The month digit will start flashing. 4. Press the UP ARROW key or DOWN ARROW key to set the month. Hold the key in to change the value faster. 5.

@@The day digit will start flashing. 6. Press the UP ARROW key or DOWN ARROW key to set the day. Hold the key in to change the value faster. 7.

@@(default °C). 1. The temperature unit is flashing 2. @@3. @@The default unit is km/h.

1. The wind speed unit is flashing. 2. @@3. @@The default unit is mm. 1. The rainfall unit is flashing. 2. @@@@The default unit is hPa. 1.

The relative air pressure unit is flashing. 2. @@@@The default unit is hPa. 1. The current relative pressure value will start flashing 2. @@Continually holding the key will allow the value to increase faster. 3. @@@@The default value is 3 hPa. Select lower numbers for high humidity areas, i.e. Oceanside.

Select high numbers for arid areas, i.e. desert. 46 1. The sensitivity value and tendency arrow will start flashing 2.

Press the UP ARROW key or DOWN ARROW key to select the value. 3. @@(Default 5 hPa). 1. The sensitivity value and tendency arrows will start flashing.

2. Press the UP ARROW key or DOWN ARROW key to select the value. 3. @@1. The digit "AOFF" will start flashing. 2. @@"AOFF" = Off; "AON" = On)

3. @@Note: If a storm warning alarm is activated, the downward weather tendency arrow will be flashing. (See WEATHER TENDENCY INDICATOR below). 47 WIND DIRECTION DISPLAY TYPE SETTING The wind direction can be displayed using either compass directions or degree measurements (default setting is compass directions).

1. The wind direction will start flashing. 2. Press the UP ARROW key or DOWN ARROW key to toggle from compass directions to degree measurements. 3. If you do not wish to reset the display to factory defaults, simply press the ALARM or MIN/MAX key, or wait until the SET mode times out and returns to the normal display mode. 4. If you wish to perform a FACTORY RESET, press the SET key to confirm and to enter the FACTORY RESET PROCEDURE. SEE WARNINGS in the FACTORY RESET section. FACTORY RESET PROCEDURE WARNING: Performing a factory reset will erase all MIN/MAX values and weather data stored in the display's internal memory and return the weather units settings back to the factory defaults.

If you have not yet uploaded the data to the Heavy Weather Pro software, the data will be lost. If you do not wish to reset the display to factory defaults either: · Press the MIN/MAX key or the ALARM key, or · Simply wait until the SET mode times out and returns to the Mode 1 display (normal mode). To reset the display to factory defaults, follow the procedure below: WARNING: A factory reset will erase the connection between the display and the thermohygro sensor and require the connection to be re-established. 1. "rES oFF" will start flashing.

2. Use the UP ARROW key to turn "rES on". 3. Press the SET key to confirm and a countdown timer will begin counting down from "127". When the timer displays "dOnE", you must remove the batteries from the display for 10 minutes.

While the batteries are out of the display, also remove the batteries from the thermo-hygro sensor. 4. After waiting for 10 minutes, insert the batteries into the thermo-hygro sensor, making sure to align the "+" symbol on the batteries with the markings on the battery cover and inside the battery compartment. 48 5.

Within 2 minutes of inserting the batteries into the thermo-hygro sensor, insert the batteries into the display, making sure to align the "+" symbol on the batteries with the markings inside the battery compartment. 6. Wait 5 minutes for the outdoor weather data to display. If any of the outdoor data displays "--" after waiting for 5 minutes, follow the "Setting Up" Procedure near the beginning of this manual or in the Quick Set Up Manual included with the product. TO EXIT THE MANUAL SETTING MODE To exit the manual setting anytime during the manual setting modes, either: · Press the ALARM key or the MIN/MAX key or · Simply wait 30 seconds until the SET mode time out and return to the Mode 1 display (normal mode). WEATHER ALARM OPERATIONS The Weather alarms can be set when certain weather conditions are met according to your requirements.

For example, you can set the thresholds for the outdoor temperature to +40°C (high) and -10°C (low), while enabling the high alarm and disabling the low alarm (i.e. temperatures <-10°C won't trigger alarm, but temperatures >+40°C will).



[You're reading an excerpt. Click here to read official LA CROSSE TECHNOLOGY WS2801 user guide](http://yourpdfguides.com/dref/3678203)  
<http://yourpdfguides.com/dref/3678203>

... If the value meets the condition for high alarm or low alarm, the buzzer will ring for 2 minutes and the value will blink, along with the corresponding icon ("HI AL"/ "LO AL"). Press any key to stop a ringing alarm. The high and low alarms can be switched On/Off independently, according to your needs. If at any time during the alarm setting process you would like to exit alarm setting mode, press the MIN/MAX key or wait for about 30 seconds and the display will return to normal display mode automatically. In normal display mode, press the ALARM key to enter ALARM mode. Subsequent presses of the ALARM key will advance to the next weather alarm section. · Note: Weather alarms can also be set from the Heavy Weather Pro software.

Consult the Heavy Weather Pro User's Guide for instructions. THE FOLLOWING WEATHER ALARMS CAN BE ADJUSTED IN ALARM SETTING MODE ·

High and Low pressure alarms · High and Low indoor temperature alarms · High and Low indoor humidity alarms · High and Low outdoor temperature alarms · High and Low outdoor humidity alarms · High wind gust alarm · Wind direction alarm · High rainfall amount in 24 hour period alarm 49 DEFAULT WEATHER ALARM VALUES Pressure Temperature (In or Out) Relative Humidity (In or Out) PRESSURE ALARMS 1. In the normal display mode, press the ALARM key once. The high pressure alarm display will be shown. 2.

Press and hold the SET key for about 2 seconds. The pressure digit will start flashing. 3. Press the UP ARROW key or DOWN ARROW key to set the high pressure alarm value. Hold the arrow key to change the value faster.

4. Press the ALARM key to confirm the setting. The digit will stop flashing. 5. Press the SET key to switch the alarm on or off. The (( )) icon indicates the alarm is switched on. 6. Press the ALARM key once. The Low Pressure alarm display will be shown. 7.

Press and hold the SET key for about 2 seconds. The pressure digit will start flashing. 8. Press the UP ARROW key or DOWN ARROW key to set the low pressure alarm value. Hold the arrow key in to change the value faster. 9. Press the ALARM key to confirm the setting. The digit will stop flashing. 10. Press the SET key to switch the alarm on or off.

The (( )) icon indicates the alarm is switched on. 11. Press the ALARM key to move to the indoor temperature alarm settings. INDOOR TEMPERATURE ALARMS 1. The high indoor temperature alarm display will be shown.

2. Press and hold the SET key for about 2 seconds. The temperature digit will start flashing. 3. Press the UP ARROW key or DOWN ARROW key to set the high indoor temperature alarm value.

Hold the key to change the value faster. 4. Press the ALARM key to confirm the setting. The digit will stop flashing. 5. Press the SET key to switch the alarm on or off. The (( )) icon indicates that the alarm is switched on. 6. Press the ALARM key once. The low indoor temperature alarm display will be shown.

50 Low High Low High Low High 960 hPa 1040 hPa 0°C 40°C 45% 70% Wind gust Rainfall in 24 hours High 100 km/h High 50 mm 7. Press and hold the SET key for about 2 seconds. The temperature digit will start flashing. 8. Press the UP ARROW key or DOWN ARROW key to set the low indoor temperature alarm value. Hold the arrow key in to change the value faster. 9. Press the ALARM key to confirm the setting. The digit will stop flashing. 10.

Press the SET key to switch the alarm on or off. The (( )) icon indicates the alarm is switched on. 11. Press the ALARM key to move to the indoor humidity alarm settings. INDOOR HUMIDITY ALARMS 1.

The high indoor humidity alarm display will be shown. 2. Press and hold the SET key for about 2 seconds. The humidity digit will start flashing. 3.

Press the UP ARROW key or DOWN ARROW key to set the high indoor humidity alarm value. Hold the key in to change the value faster. 4. Press the ALARM key to confirm the setting. The digit will stop flashing. 5. Press the SET key to switch the alarm on or off. The (( )) icon indicates the alarm is switched on. 6.

Press the ALARM key once.

The low indoor humidity alarm display will be shown. 7. Press and hold the SET key for about 2 seconds. The humidity digit will start flashing. 8. Press the UP ARROW key or DOWN ARROW key to set the low indoor humidity alarm value. Hold the key in to change the value faster. 9. Press the ALARM key to confirm the setting. The digit will stop flashing.

10. Press the SET key to switch the alarm on or off. The (( )) icon indicates the alarm is switched on. 11. Press the ALARM key to move to the outdoor temperature alarm settings.

OUTDOOR TEMPERATURE ALARMS 1. The high outdoor temperature alarm display will be shown. 2. Press and hold the SET key for about 2 seconds. The temperature digit will start flashing.

3. Press the UP ARROW key or DOWN ARROW key to set the high outdoor temperature alarm value. Hold the key in to change the value faster. 4. Press the ALARM key to confirm the setting. The digit will stop flashing. 5. Press the SET key to switch the alarm on or off. The (( )) icon indicates that the alarm is switched on. 6.

Press the ALARM key once. The low outdoor temperature alarm display will be shown. 51 7. Press and hold the SET key for about 2 seconds. The temperature digit will start flashing. 8. Press the UP ARROW key or DOWN ARROW key to set the low outdoor temperature alarm value. Hold the arrow key in to change the value faster. 9. Press the ALARM key to confirm the setting.

The digit will stop flashing. 10. Press the SET key to switch the alarm on or off. The (( )) icon indicates the alarm is switched on. 11.

Press the ALARM key to move to the outdoor humidity alarm settings. OUTDOOR HUMIDITY ALARMS 1. The high outdoor humidity alarm display will be shown. 2. Press and hold the SET key for about 2 seconds.

The humidity digit will start flashing. 3. Press the UP ARROW key or DOWN ARROW key to set the high outdoor humidity alarm value. Hold the key in to change the value faster. 4. Press the ALARM key to confirm the setting. The digit will stop flashing. 5. Press the SET key to switch the alarm on or off. The (( )) icon indicates the alarm is switched on.

6. Press the ALARM key once. The low outdoor humidity alarm display will be shown. 7. Press and hold the SET key for about 2 seconds. The humidity digit will start flashing. 8. Press the UP ARROW key or DOWN ARROW key to set the low outdoor humidity alarm value. Hold the key in to change the value faster. 9.

Press the ALARM key to confirm the setting. The digit will stop flashing. 10. Press the SET key to switch the alarm on or off. The (( )) icon indicates the alarm is switched on.

11. Press the ALARM key to move to the wind gust alarm settings. WIND GUST ALARM 1. The wind gust alarm display will be shown. 2.

Press and hold the SET key for about 2 seconds. The wind gust digit will start flashing. 3. Press the UP ARROW key or DOWN ARROW key to set the wind gust alarm value. Hold the key in to change the value faster. 4. Press the ALARM key to confirm the setting. The digit will stop flashing.

[You're reading an excerpt. Click here to read official LA CROSSE TECHNOLOGY WS2801 user guide](#)



<http://yourpdfguides.com/dref/3678203>



5. Press the SET key to switch on or off the alarm.

The (( )) icon indicates the alarm is switched on. 6. Press the ALARM key to move to the wind direction alarm settings. 52 WIND DIRECTION ALARM  
Note: Multiple wind direction alarms can be set simultaneously if desired. 1. The wind direction alarm display will be shown. 2. Press and hold the SET key for about 2 seconds. The wind direction arrow on the outside of the compass circle will start flashing with the corresponding compass direction or degrees reading displayed in the center of the compass. 3.

Press the UP ARROW key or DOWN ARROW key to move the wind direction alarm pointer. 4. Press the SET key to set a wind direction alarm. A pointer icon will appear inside of the compass circle to indicate an alarm setting for that wind direction. 5.

To remove an alarm setting for a wind direction, press the SET key again to remove the selected wind direction alarm. The arrow icon inside the compass circle will disappear. 6. If more than one wind direction is desired as an alarm setting, Press the UP ARROW key or DOWN ARROW key to move the wind direction alarm pointer to the next desired setting. 7.

Press the SET key to confirm the next wind direction. A pointer icon will appear inside of the compass circle to indicate an alarm setting for that wind direction. You can set as many wind direction alarms as you desire. 8. Press the ALARM key to confirm the setting. The wind direction arrow will stop flashing. 9. Press the SET key to switch on or off the alarm. The (( )) icon indicates the alarm is switched on. 10.

Press the ALARM key to move to the 24h rainfall alarm settings. 24H RAINFALL ALARM 1. The 24h rainfall alarm display will be shown. 2. Press and hold the SET key for about 2 seconds. The 24h rainfall digit will start flashing. 3. Press the UP ARROW key or DOWN ARROW key to set the 24h rainfall value.

Hold the key in to change the value faster. 4.

Press the ALARM key to confirm the setting. The digit will stop flashing. 5. Press the SET key to switch on or off the alarm. The (( )) icon indicates the alarm is switched on.

6. Press the ALARM key to exit the alarm settings. 53 HYSTERESIS To compensate for fluctuation of the measured data, which may cause the weather alarm to sound constantly if the measured reading is Weather data Hysteresis close to your set level, a hysteresis function has Temperature 1°C been implemented for each weather alarm. For Humidity 3% RH example, if the high temperature alarm is set to Pressure 1 hPa +25°C and the current value moves to +25°C, the Wind speed 10 km/h alarm will be activated (if it has been enabled). Now when the temperature drops to +24.

88°C or below and thereafter again increases to beyond +25°C, the data will be blinking, but no alarm will be activated. It has to drop to below +24°C (with a pre-set hysteresis of 1°C) so that the alarm can be produced again. Hysteresis values for the various weather data types are given in the table. Note: The temperature or humidity data will keep flashing even after a key has been pressed to stop the alarm has been switched off to indicate that the current weather condition is out of the pre-set limit(s) WEATHER FORECAST AND WEATHER TENDENCY WEATHER FORECASTING ICONS: Weather forecasting icons are displayed in any of the following combinations: Sunny Cloudy with sunny intervals Rainy For every sudden or significant change in the air pressure, the weather icons will update accordingly to represent the change in weather. (Every time a new average pressure value has been obtained (once per minute), this value is compared with an internal reference value. If the difference between these values is bigger than the selected weather tendency sensitivity, the weather-icon changes, either for worse or for better. In this case, the current pressure value becomes the new weather tendency reference.) If the icons do not change, either the air pressure has not changed or the change has been too small for the Weather Center to register. So you may adjust the "sensitivity" of the pressure change checking in the setting mode see WEATHER TENDENCY SENSITIVITY VALUE SETTING above. However, if the icon displayed is a sun or raining cloud, there will be no change of icon if the weather gets any better (with sunny icon) or worse (with rainy icon) since the icons are already at their extremes.

The icons displayed forecasts the weather in terms of getting better or worse and not necessarily sunny or rainy as each icon indicates. For example, if the current weather is cloudy and the rainy icon is displayed, it does not mean that the product is faulty 54 because it is not raining. It simply means that the air pressure has dropped and the weather is expected to get worse but not necessarily rainy. Note: After setting up, readings for weather forecasts should be disregarded for the next 48-60 hours. This will allow sufficient time for the Weather station to collect air pressure data at a constant altitude and therefore result in a more accurate forecast. Common to weather forecasting, absolute accuracy cannot be guaranteed. The weather forecasting feature is estimated to have an accuracy level of about 75% due to the varying areas the Weather Center has been designed for use. In areas that experience sudden changes in weather (for example from sunny to rain), the Weather Center will be more accurate compared to use in areas where the weather is stagnant most of the time (for example mostly sunny). If the Weather Center is moved to another location significantly higher or lower than its initial standing point (for example from the ground floor to the upper floors of a house), disregard the weather forecast for the next 48-60 hours, as the Weather Center may mistake the new location as being a possible change in air-pressure when really it is due to the slight change of altitude. WEATHER TENDENCY INDICATOR Working together with the weather icons is the weather tendency indicators (arrow located on the left and right sides of the weather icons).

When the indicator points upwards, it means that the air-pressure is increasing and the weather is expected to improve, but when indicator points downwards, the air-pressure is dropping and the weather is expected to become worse. Taking this into account, one can see how the weather has changed and is expected to change. For example, if the indicator is pointing downwards together with cloud and sun icons, then the last noticeable change in the weather was when it was sunny (the sun icon only). Therefore, the next change in the weather will be cloud with rain icons since the indicator is pointing downwards. Note: Once the weather tendency indicator has registered a change in air pressure, it will remain permanently visualized on the LCD.

AIR PRESSURE HISTORY (ELECTRONIC BAROMETER WITH BAROMETRIC PRESSURE TREND) The LCD also shows the relative air pressure value and the air pressure history. Press the SET key to toggle between Mode1 and Mode2 of the display.



[You're reading an excerpt. Click here to read official LA CROSSE TECHNOLOGY WS2801 user guide](http://yourpdfguides.com/dref/3678203)  
<http://yourpdfguides.com/dref/3678203>

· Mode 1: the bar graph displays the air pressure history of the past 24 hours in seven steps. The horizontal axis represents the last 24 hours of air pressure recording (-24, -18, -12, -9, -6, -3 and 0 hour). Mode 2: the bar graph displays the air pressure history of the past 72 hours in seven steps. The horizontal axis represents the last 72 hours of air pressure recording (-72, -48, -36, -24, -12, -6 and 0 hour). 55 · The vertical bars are plotted at each of the nine steps and give the trend over the recorded period. The 0 hour vertical bar will always display at the midline height to indicate the current air pressure. The varying height of bars in other columns on the graph indicate a relative change in air pressure up or down from the previous measurement. New pressure measurements are compared to previously recorded pressure measurements. The pressure change is expressed by the difference between the current ("0h") and the past readings in divisions of  $\pm 0.06$  inHg or  $\pm 2$  hPa. If the bars are rising from left to right, this indicates that the weather is getting better due to an increase in air pressure. If the bars are falling from left to right, this indicates that the weather is expected to get worse due to a drop in air pressure. At every full hour, the current air pressure is used as a basis for the display of a new graph bar.

The existing graph is then moved one column to the left. Note: For accurate barometric pressure trend, the Weather Center should operate at the same altitude and should not be moved. If the unit has been moved, for example, from the ground floor to the second floor of the house then the readings for the next 4860 hours should be disregarded. Note: The bar graph will scroll right to left regularly to prevent LCD burnout. WIND DIRECTION AND WIND SPEED MEASUREMENT · The current wind direction is indicated by a pointer on the outer circle of the compass. The last 6 wind directions are displayed with pointers on the inner circle. · The wind direction (abbreviation or degrees) is displayed in center of compass. Press the SET key to toggle between Mode 1 and Mode 2 of the display Mode 1 displays the following wind data: · Wind direction (shown on the compass scale of 16 divisions) · Wind chill in °C or °F · Wind speed in km/h, mph, bft, knots or m/s Mode 2 displays the following wind data: · Wind direction (shown on the compass scale of 16 divisions) · Wind chill in °C or °F · Wind gust in km/h, mph, bft, knots or m/s RAINFALL MEASUREMENT The 1hour, 24 hour, week, month or total rainfall measurement is displayed on the LCD, in the unit of mm or inch. · Press the DOWN ARROW to select the rainfall display from the following modes: 1. Total rainfall - reset manually (see "RESET THE MIN/MAX WEATHER DATA") 56 2.

Last 1 hour rainfall it shows the sum of last 15 entries of four minutes rainfall 3. Last 24 hours rainfall - it shows the sum of last 24 entries of hourly rainfall 4. Weekly rainfall - it shows the weekly rainfall. The rainfall measurement starts counting on the second day after the first time power up or factory reset. (Eg. : if the unit is powered up on Monday day time, then the weekly rainfall is updated every Tuesday after 23:59 h (11:59 pm)) 5. Monthly rainfall updates on every 1st of the month at 00:00(midnight) (12:00am). VIEWING THE MIN/MAX WEATHER DATA The weather station will record the maximum and minimum value of the various weather data with time and date of recording automatically. The following stored maximum and minimum weather data can be viewed by pressing the MIN/MAX key in normal display mode. 1.

2. 3. 4. 5. 6. 7. MIN/MAX indoor temperature with the date and time of recording MIN/MAX indoor humidity with the date and time of recording MIN/MAX outdoor temperature with the date and time of recording MIN/MAX dew point temperature with the date and time of recording MIN/MAX outdoor humidity with the date and time of recording MAX wind gust with the date and time of recording Total rainfall with the date and time of recording RESET THE MINIMUM AND MAXIMUM WEATHER DATA To reset the aforementioned MIN/MAX weather data, you need to reset each of the data independently. 1. Press MIN/MAX key to show the desired weather data. 2.

Press UP ARROW key. The stored value will be reset to the current value and current time. @@@@To reset the rainfall reading, press the UP ARROW key. @@Note: Until the first rainfall total reset is performed, the time and date of the total rainfall are displayed as "-:-- --:--:--". After the rainfall total is reset, the rainfall total display will indicate the date and time of the last rainfall total reset. CARE AND MAINTENANCE: · Extreme temperatures, vibration and shock should be avoided as these may cause damage to the unit and give inaccurate forecasts and readings. · Precautions shall be taken when handling the batteries. Injuries, burns, or property damage may be resulted if the batteries are in contact with conducting materials, 57 · · · · · heat, corrosive materials or explosives.

The batteries shall be taken out from the unit before the product is to be stored for a long period of time. Immediately remove all low powered batteries to avoid leakage and damage. Replace only with new batteries of the recommended type. When cleaning the display and casings, use a soft damp cloth only. Do not use solvents or scouring agents as they may mark the LCD and casings.

Do not submerge the unit in water. Special care shall be taken when handling a damaged LCD display. The liquid crystals can be harmful to user's health. Do not make any repair attempts to the unit. Return them to their original point of purchase for repair by a qualified engineer.

Opening and tampering with the unit may invalidate their guarantee. Never touch the exposed electronic circuit of the device as there is a danger of electric shock should it become exposed. Do not expose the units to extreme and sudden temperature changes, this may lead to rapid changes in forecasts and readings and thereby reduce their accuracy. SPECIFICATIONS: INDOOR TEMPERATURE -40°C to +59.9°C with 0.1°C resolution -40°F to +139.8°F with 0.2°F resolution ("OF.L" displayed if outside this range) OUTDOOR TEMPERATURE / DEW POINT -40°C to +59.9°C with 0.

1°C resolution -40°F to +139.8°F with 0.2°F resolution ("OF.L" displayed if outside this range) INDOOR HUMIDITY 1% to 99% with 1% resolution ("- -" displayed if < 1%, "99" displayed if 99%) OUTDOOR HUMIDITY 1% to 99% with 1% resolution ("- -" displayed if < 1%, "99" displayed if 99%) WIND SPEED/ GUST 0 to 180 km/h with resolution of 0.36 km/h 0 to 111.8 mph with resolution of 0.22 mph 0 to 12 bft 0 to 97.1 knots with resolution of 0.



[You're reading an excerpt. Click here to read official LA CROSSE TECHNOLOGY WS2801 user guide](http://yourpdfguides.com/dref/3678203)  
<http://yourpdfguides.com/dref/3678203>

19 knots 0 to 50 m/s with resolution of 0.1 m/s (displays "OF.

L" when > 180 km/h; 111.8 mph; 50 m/s; 12 bft; 97.1 knots) WIND CHILL/ DEW POINT -40°C to +59.9°C with 0.1°C resolution -40°F to +139.

8°F with 0.2°F resolution (displays "OF.L" if outside this) 58 RAINFALL (24H, TOTAL) 0 to 9999.9 mm with 0.1mm resolution 0" to 393.

7" with 0.01" resolution (displays "OF.L" when > 9999.9mm) OUTDOOR DATA RECEPTION Temperature and humidity data received every 13 seconds  
Wind data received every 17 seconds Rain data received every 19 seconds AIR PRESSURE Relative pressure pre-set range: 920 to 1080 hpa 27.10 to 31.90  
inHg Air pressure measured every 15 seconds TRANSMISSION RANGE Thermo-hygro: about 100 meters (330 feet) in open space Rain: about 100 meters  
(330 feet) in open space Wind: about 100 meters (330 feet) in open space USB transceiver about 25 meters (82 feet) in open space POWER CONSUMPTION  
Weather Center: 2 x C, IEC LR14, 1.5V Thermo-hygro transmitter: 2 x C, IEC LR14, 1.5V Rain sensor: Solar-powered by solar cells Wind sensor: Solar-  
powered by solar cells Battery life: approximately 12 months (Alkaline batteries recommended) for Weather station and Thermo-hygro transmitter

DIMENSIONS (L X W X H) Weather Center: 190.4 x 37 x 190.4mm (7.

5" x 1.46" x 7.5") Thermo-hygro transmitter: 79.4 x 89.8 x 189.3 (3.12" x 3.53" x 7.45") Solar Wind sensor: 250 x 145.9 x 192.

3mm (9.84" x 5.74" x 7.57") Solar Rain sensor: Ø 131.6 x 182.

7mm (Ø 5.19" x 7.19") USB transceiver: 81.8 x 9 x 22.7mm (3.

22" x 0.35" x 0.89") **LIABILITY DISCLAIMER** · The electrical and electronic wastes contain hazardous substances. Disposal of electronic waste in wild  
country and/or in unauthorized grounds strongly damages the environment. · Please contact your local or/and regional authorities to retrieve the addresses of  
legal dumping grounds with selective collection. · All electronic instruments must from now on be recycled. User shall take an active part in the reuse,  
recycling and recovery of the electrical and electronic waste. · The unrestricted disposal of electronic waste may do harm on public health and the quality of  
environment. 59 . . . . . As stated on the gift box and labeled on the product, reading the "User manual" is highly recommended for the benefit of the user.  
This product should not be thrown in general rubbish collection points.

The manufacturer and supplier cannot accept any responsibility for any incorrect readings and any consequences that occur should an inaccurate reading  
take place. This product is designed for use in the home only as indication of the temperature. This product is not to be used for medical purposes or for  
public information. The specifications of this product may change without prior notice. This product is not a toy. Keep out of the reach of children. No part of  
this manual may be reproduced without written authorization of the manufacturer. R&TTE Directive 1999/5/EC Summary of the Declaration of Conformity :  
We hereby declare that this wireless transmission device does comply with the essential requirements of R&TTE Directive 1999/5/EC. 60 .



[You're reading an excerpt. Click here to read official LA CROSSE  
TECHNOLOGY WS2801 user guide  
http://yourpdfguides.com/dref/3678203](http://yourpdfguides.com/dref/3678203)