



Your PDF Guides


You can read the recommendations in the user guide, the technical guide or the installation guide for MCCULLOCH SUPER AIR STREAM III. You'll find the answers to all your questions on the MCCULLOCH SUPER AIR STREAM III in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

User manual MCCULLOCH SUPER AIR STREAM III
User guide MCCULLOCH SUPER AIR STREAM III
Operating instructions MCCULLOCH SUPER AIR STREAM III
Instructions for use MCCULLOCH SUPER AIR STREAM III
Instruction manual MCCULLOCH SUPER AIR STREAM III

ILLUSTRATED PARTS LIST

MODEL NAMES	SERIAL NUMBER PREFIX	MODELS
Super Air Stream III	13-	400048-03
Super Air Stream IV	13-	400048-04
Eager Beaver III	13-	400048-05
Eager Beaver IV	13-	400048-06

**EAGER BEAVER® III & IV
SUPER AIR STREAM® III & IV
GAS BLOWER &
BLOWER/VAC**



McCutloch products are identified by a model number (in this instance 400048) followed by a suffix number (03 or 04). Suffix numbers denote variations in parts or assemblies used in the manufacture of this product.

Illustrated Parts Lists (IPLs) contain a PART NUMBER, DESCRIPTION, UNITS per assembly and STOCKING CODE for each part. Stocking Codes are:

- A - Factory stocked. Slow moving part.
- B - Distributor stocked. Medium to slow moving part.
- C - Dealer stocked. Fast to medium moving part.
- D - Indicates a McCutloch service tool.

NOTE: The following explains symbols/footnotes in this IPL:

- (-) A dash preceding a PART NUMBER indicates that it is a new part number, different from the one listed in the previous IPL for this unit.
- (.) One or more dots (. Spring-Starter) preceding a part DESCRIPTION indicates the part is included in the kit or assembly described directly above the circles.
- (---) If four dashes appear in place of a PART NUMBER, the part is not available individually but is included in the next higher assembly or subassembly.
- Ⓢ Circled numbers preceding a DESCRIPTION footnote the part or assembly to additional information on the page.
- (*) An asterisk draws attention to general information.

The policy of McCutloch Corporation is one of continual improvement in design, manufacturing and engineering advancement whenever possible to assure still finer power tools. Hence, specifications, equipment, colors, design and manufacturer's suggested list prices, are subject to change without notice. McCutloch Corporation reserves the right to make such changes without prior notification or obligation to backfit or supply backfit components for units previously shipped from the factory.

NOVEMBER 1990

MCCULLOCH CORPORATION
P.O. Box 11990 • Tucson, Arizona 85734

219272-02

CONTENTS

	PAGE
FIGURE 1 Powerhead Assembly	2
FIGURE 2 General Assembly	4
FIGURE 3 Accessories	5
FIGURE 4 Carburetor Assembly	6
FIGURE 5 Specifications	7
FIGURE 6 Tools/Lubrication	7

© U.S.A. - McCutloch Corporation, 1990 • Printed in U.S.A.



[You're reading an excerpt. Click here to read official MCCULLOCH SUPER AIR STREAM III user guide](http://yourpdfguides.com/dref/3598965)
<http://yourpdfguides.com/dref/3598965>

.. "E" Ring-Throttle Shaft ..
.. Screw-Throttle Adjust. ... (~! . Screw-High Speed ..

.. 0 . Screw-Low Speed ... @ . Spring-Adjuster Screw ..
.. . Screw-Metering Cover . Retainer-Primer .

Primer Bulb . Base Asy-Primer . Diaphragm Asy--etering , Gasket.Metering Chamber . Screw-Pin Retaining .
Pin-Metering Lever . Levar.Metering , Valve-Inlet Needle . SpringMetering Lever . Nozzle Asy-Check'Valve . Plug-Welch . Retainer-Check Valve . Valve-
Check . Spring-Adj. Screw 1 NOTE: Carburetor parts are shown for identification and disassembly sequence purposea only.

Components are not available separately unless a part number is listed before the part description. @ Contained in Nejob Repair Kit, P/N 3244W (CODE,B).

@ Contained in (iaeket/Dlephragm Kit, P/N 224401 (CODEB). 494 BLOWERIVAC SPECIFICATIONS ENGINE TYPE DISPLACEMENT CYLINDER
IGNITION MUFFLER SPARK TYPE

.....
.....
..... Two Cycle ...

.....
.....
.....21.
2cc

.....
.. Aluminun Electronic Volume fhma~ o Single Cylinder ...

.....
.....
.....
.....
.....
.....

..... Large SCREEN ARRESTOR

.....
.....

U.S. Forest Service Approved CARBURETOR AIR FILTER

.....
.....
All Position

.....
Molded Felt Diaphragm FUEL CAPACITY RUNNING TIME

.....
.....
..14.6

.....35-40 FL OZ. Minutes AIR VOLUME OILTYPE ...

.....
.....
.....
.....
..400CFM

.....
.....
..40:1 ...

.....
140 2-Cycle MPH Fan Custom LubricarN AIR VELOCITY IMPELLER IMPELLER IMPELLER TYPE BLADE SPEED

.....
.....
.. Centrifugal NUMBER

.....
...6 RPM...
.....

.....7000 DRY WEIGHT NUMBER LENGTH VACUUM NUMBER BLOWER .

.....
.....
.....

..11.2Lbs. TUBES TUBES

.....
... 2 Sections .
.....

... 34 3/4" Total

.....
.....
4 1/2"

... 25 DIA. @@

... @@.



[You're reading an excerpt. Click here to read official MCCULLOCH SUPER AIR STREAM III user guide](http://yourpdfguides.com/dref/3598965)
<http://yourpdfguides.com/dref/3598965>