



Your PDF Guides

You can read the recommendations in the user guide, the technical guide or the installation guide for NILFISK BR 800S. You'll find the answers to all your questions on the NILFISK BR 800S in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

User manual NILFISK BR 800S User guide NILFISK BR 800S Operating instructions NILFISK BR 800S Instructions for use NILFISK BR 800S Instruction manual NILFISK BR 800S

Better design gives added value



TECHNICAL SPECIFICATIONS		CE					
Description	Unit	BR 600 S	BR 800 GS	BR 700 S	BR 700 CS	BR 800 S	BR 800 CS
Voltage	V	36	36	36	36	36	36
Rated power	W	2250	2320	2000	2020	2500	2500
Sound pressure level at 1.5 m (ISO 3744)	dB(A)	85	85	85	85	85	85
Productivity (ste theoretical / actual) (km/h)	m/h	4100/2900	4100/2900	4800/3400	4800/3400	5000/3800	5000/3800
Scrubbing width	mm	610	610	710	710	810	810
Max speed	km/h	6,7	6,7	6,7	6,7	6,7	6,7
Solution recovery tank	litres	112/113	113/113	113/113	113/113	113/113	113/113
Brushpad diameter	mm	310/300	-	360/325	-	410/406	-
Brush pressure	kg	27-103	27-103	27-103	27-103	27-103	27-103
Brush speed	rpm	250	900	250	900	250	900
Length x width x height	cm	152x72x135	152x72x135	152x72x135	152x72x135	152x72x135	152x72x135
Operating Weight	kg	632	632	632	632	632	632



Nilfisk-Advance AS
Sjællandsgade 2B
DK-2820 Brøndby
Denmark
Tel: +45 4433 8100
Fax: +45 4433 7700
www.nilfisk-advance.com

98018408-04025 © 2018 Nilfisk-Advance Group

Printed in Denmark by Christensgaard Design A/S



[You're reading an excerpt. Click here to read official NILFISK BR 800S user guide](#)

<http://yourpdfguides.com/dref/3215075>

Manual abstract:

Squeegee features "quick release" blade replacement QuickChange™ no tools interchangeable deck system Adjusting side skirts prevent splash, and guide solution to the squeegee to leave floors dry TECHNICAL SPECIFICATIONS Description Voltage Rated power Sound pressure level at 1,5 m (ISO 3744) Productivity rate theoretical/actual (km/h) Scrubbing width Max speed Solution/ recovery tank Brush/pad diameter Brush pressure Brush speed Length x width x height Operating Weight Specifications and details are subject to change without prior notice Unit V W dB(A) m²/h mm km/h litres mm kg rpm cm kg BR 600S 36 2350 65 4100/2900 610 6,7 113/113 310/305 27-103 250 152x72x135 632 BR 600CS 36 2520 65 4100/2900 610 6,7 113/113 27-103 900 632 BR 700S 36 2500 65 4800/3400 710 6,7 113/113 360/335 27-103 250 632 BR 700CS 36 2520 65 4800/3400 710 6,7 113/113 27-103 900 632 BR800S 36 2500 65 5500/3800 810 6,7 113/113 410/406 27-103 250 632 BR 800CS 36 2520 65 5500/3800 810 6,7 113/ 113 27-103 900 632 152x72x135 152x72x135 152x72x135 Nilfisk-Advance A/S Sognevej 25 DK-2605 Brøndby Denmark Tel. +45 4323 8100 Fax +45 4343 7700 www.nilfisk-advance.com 96016406-06/05, © 2006.05 Nilfisk-Advance Group Printed in Denmark by Dronninglund Bogtrykkeri A/S Ride-on scrubber/dryers Nilfisk BR 600S/700S/800S Right size for hard cleaning tasks Total versatility in ride-on cleaning The Nilfisk BR 600S/700S/800S make cleaning floors easy. @@@@The water-detergent mixing ratio is always accurate, never guesswork. @@One bottle of highly concentrated detergent allows up to 15 water tank loads (of 113 litres) of operating time before needing to be changed or refilled. EDS offers better productivity by cutting cleaning time. .



[You're reading an excerpt. Click here to read official NILFISK BR 800S user guide](http://yourpdfguides.com/dref/3215075)

<http://yourpdfguides.com/dref/3215075>