



Your PDF Guides

You can read the recommendations in the user guide, the technical guide or the installation guide for NILFISK GD 930. You'll find the answers to all your questions on the NILFISK GD 930 in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

User manual NILFISK GD 930
User guide NILFISK GD 930
Operating instructions NILFISK GD 930
Instructions for use NILFISK GD 930
Instruction manual NILFISK GD 930

GD 930 & GD 930S2



INSTRUCTION FOR USE
BETRIEBSANLEITUNG
INSTRUCTIONS D'UTILISATION
INSTRUCCIONES DE MANEJO
INSTRUÇÕES DE OPERAÇÃO
ISTRUZIONI SULL'USO
GEBRUIKSAANWIJZING
BRUKSANVISNING
DRIFTSINSTRUKS
DRIFTSVEJLEDNING
KÄYTTÖOHJE

CE
822 9393 000
P01

Printed in Hungary

 **Nilfisk**
setting standards



[You're reading an excerpt. Click here to read official NILFISK GD 930 user guide](http://yourpdfguides.com/dref/2885130)
<http://yourpdfguides.com/dref/2885130>

Manual abstract:

Accidents due to misuse can only be prevented by those using the machine. When using an electrical appliance, basic precautions should always be followed, including the following: **READ AND FOLLOW ALL SAFETY INSTRUCTIONS.** • Do not use the machine unless filters are fitted. • If the cleaner is not working properly or has been dropped, damaged, left outdoors, or dropped into water, return it to a service center or dealer. • Use only as described in this manual and only with the manufacturer's recommended attachments. • The use of this machine in conjunction with the pick-up of hazardous materials (such as asbestos) has not been investigated by Underwriters laboratories Inc. This appliance is provided with double insulation. To reduce the risk of fire, electric shock, or injury, please read and follow all safety instructions and caution markings before use. •••• Disconnect the cleaner before servicing and when not in use. Do not use with damaged cord or plug.

to unplug grasp the plug, not the cord. Do not handle plug or cleaner with wet hands. Turn off all controls before unplugging. •• do not run cleaner over cord. Keep cord away from heated surfaces.

•• Do not put any objects into openings or use with opening blocked. Keep openings free of dust, lint, hair, and anything else that could reduce the flow of air. • Do not pick up anything that is burning or smoking, such as cigarettes, matches, or hot ashes. • Use extra care when using on stairs. • Do not use to pick up flammable or combustible liquids such as gasoline, or use in areas where they may be present.

• This appliance is not to be used by children or persons with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction. Children must be supervised not to play with the appliance. • Caution: Do not pick-up hazardous material without Hepa-filter mounted. • All contact with the machine, dustbag, filter and all other accessories used when picking-up hazardous materials should be handled according to the regulations valid for the vacuumed material. In a double-insulated appliance, two systems of insulation are provided instead of earthing. No earthing means is provided on a double-insulated appliance, nor should a means for earthing be added to the appliance. Servicing a doubleinsulated appliance requires extreme care and knowledge of the system, and should be done only by qualified service personnel. Replacement parts for a double-insulated appliance must be identical to the parts they replace. A double insulated appliance is marked with the words "DOUBLE INSULATION" or "DOUBLE INSULATED." The symbol (square within a square) may also be used on the product.

Noise level according to BS 5415: GD 930 S2 reduced speed 45 dB(A) GD 930 S2 full speed 53 dB(A) Noise level with the nozzle against the floor according to IEC 704: GD 930 S2 reduced speed 71 dB(A) GD 930 S2 full speed 76 dB(A) Specifications and details are subject to change without prior notice. The accessories shown in the pictures may vary from model to model. This appliance conforms with EC-Directive 89/336/EEC, EEC, 93/31/EEC, 73/23/EEC, 93/68/EEC. A) Loosen the two snap lockings by pulling them outwards b) Lift the cover from the container. Fit the opening on the dust bag over the air inlet. press the membrane over the flanged edge on the inlet. Secure with the lock washer. Power is supplied to the socket when the machine is switched on. The filters are located inside the lid. To reach them lift out the filter holder(a).

Instead of these two filters you can fit a micro filter of HEPA-quality (e), which traps 99,99% of all particles larger than 0,3 microns. The machine is also fitted with a backup filter (d) located above the motor. This filter should also be inspected and replaced if necessary. •••••••••• Push the hose coupling all the way in and turn clockwise. Standard: Fit the sections together and twist to lock in place.

Telescopic: Push down the catch and then adjust the length. The accessories shown in the pictures may vary from model to model. •• Work with the brush on hard floors and without it on soft floors. c) Universal nozzle for both hard floors and carpets. •••••• The clip on the hose handle holds the nozzle when it is not in use.

•••••••••• Ensure that the plug fitted to the end of the power supply cord is suitable for your supply socket, if not refer to the information contained in 'Electrical Connections', or consult a qualified electrician. The electrical installation from which the supply is drawn must be maintained to current Institute of Electrical Engineers wiring regulations. **REGULAR SERVICING and INSPECTION** of your machine must be carried out by suitably qualified personnel in accordance with relevant legislation and regulations. In particular, electrical tests for earth continuity, insulation resistance, and condition of the flexible cord should be checked frequently. In the event of any defect the machine **MUST** be withdrawn from service, completely checked and repaired. Trained Service Engineers will be pleased to carry out on site servicing on a regular or as requested basis, to ensure the continuing safety and efficiency of your machine. Machines are fitted with a 13 amp. Only fuses that are ASTA approved to BS 1362 should be fitted. Never use the plug without the fuse cover fitted. Replacement fuse covers are available at any electrical retail outlet.

If the available socket outlet is not suitable for the plug supplied, the plug must be cut off and an appropriate plug fitted. The plug thus cut off **MUST BE DESTROYED** for safety reasons before being disposed of. Machines built for other voltages and frequencies are not normally supplied with a fitted plug. If it is necessary to fit a plug, the wires in this power supply cord are coloured in accordance with the following code: Machines are fitted with a 13 amp. Only fuses that are ASTA approved to BS 1362 should be fitted. Never use the plug without the fuse cover fitted. Replacement fuse covers are available at any electrical retail outlet. If the available socket outlet is not suitable for the plug supplied, the plug must be cut off and an appropriate plug fitted. The plug thus cut off **MUST BE DESTROYED** for safety reasons before being disposed of. Machines built for other voltages and frequencies are not normally supplied with a fitted plug.

•••••••• To connect the new plug: If using a three-pin plug, do not make any connection to the terminal in the plug which is marked with the letter 'E' or by the safety earth symbol or coloured green or green & yellow. This machine is double-insulated and no earth connection is necessary. The wire which is coloured blue must be connected to the terminal in the plug which is marked with the letter 'N' or is coloured black or blue.



[You're reading an excerpt. Click here to read official NILFISK GD](http://yourpdfguides.com/dref/2885130)

[930 user guide](http://yourpdfguides.com/dref/2885130)

<http://yourpdfguides.com/dref/2885130>

The wire which is coloured brown must be connected to the terminal in the plug which is marked with the letter L' or is coloured red or brown. @@La figure (b) montre le filtre standard, la figure (c) le filtre fin.



[You're reading an excerpt. Click here to read official NILFISK GD 930 user guide](#)

<http://yourpdfguides.com/dref/2885130>