



**Manual abstract:**

@@39262 39233 39323 31016 31011 30147 31040 74mm Body cap Eyepiece cap ME Eyecup FP Cover for accessory shoe FK 133.5mm 4x AA batteries Software S-SW74 Delivered without lens 95mm 2.7" Optional accessories 133.5mm Built for the tough everyday photography. Code No. 50099 Code No. 50154 Backpack for a complete system Code No. 50160 SLR case > CCD with 10.2 Megapixels resolution. @@> Dust and spray protected body. 60 individual seals on the body ensure that humidity, dust and dirt have no effect on the working parts of the camera. > Reliable system against dust on the sensor: seals prevent dust contamination, coating of the Low Pass filter prevents adhesion of dust particles, vibration eliminates dust from the sensor, an adhesive strip collects dust shaken from the sensor and the "Dust Alert" system warns of persistent adhering particles on the sensor. > PENTAX "Dynamic Range Enlargement" (DRE). @@@@> Picture Modes and automatic functions provide for precise camera settings. The camera can independently recognise which programme is best suited for each photograph situation and immediately adjust for the optimal settings to match the situation. @@@@50158 Aluminium case Code No. 39212 AC Mains Adapter Kit K-AC10E Code No. 39687 Battery grip D-BG3 Code No. 39357 Sensor Cleaning Kit Code No. 37377 IR Remote Control F Code No. 37248 Cable release CS 205 Code No. 30465 Flash AF-200 FG Code No. 30333 Flash with case AF-360 FGZ Code No. 30425 Flash AF-540 FGZ Code No. 21547 smc PENTAX DA 18 55mm f/3.5 5.6 AL II Code No. @@21567 smc PENTAX DA 50 200mm f/4.0 5.6 ED Code No. 21727 smc PENTAX DA 55 300mm f/4.0 5.8 ED Code No. 21650 smc PENTAX DA\* 16 50mm f/2.8 ED AL [IF] SDM Code No. @@1,100 images\* approx. 550 images (50% with flash) approx. 700 min. @@@@Daylight, Shade, Cloudy, Tungsten, Neon (W, N, D), Flash, manual balance, 3 selectable settings for Kelvin and Mired Value with fine adjust · Digital filters: BW, Sepia, Colour (18 options), Soft filter and Slim Filter, HDR (3 options) · Drive Modes: Single, Series (Hi/Low): 2.8fps. to 4 images in JPEG (Hi), 1.1fps to capacity of memory card (Low). 4 images in RAW (DNG). Auto Bracketing, Self-timer with 2sec. delay (mirror up lock) and 12sec. delay, IR Remote Control, series. Viewfinder · Built-in, non-interchangeable Pentamirror finder · Viewing area 96% with finder magnification of 0.85x (with 50mm f/1.4 lens at infinity, -1m1) · Bright non-interchangeable "Natural Bright II" focusing screen · Viewfinder indications below image area · Dioptre correction -2.5 dpt. @@Adds approx. @@· 3 step "Dust Removal" system: 1. Special coating of Low Pass Filter, 2. Vibration system to remove dust, 3. @@@Operational range: EV 1 EV 21 · Electronically controlled vertical-run focal plane shutter Shutter speeds: Automatic: 1/4,000 30sec. (stepless) Manual: 1/4,000 30sec. (in 0.5 EV steps) and Bulb Flash sync: 1/180sec. @@Actual performance may vary according to operating conditions. Tests conducted using the monitor and flash for 50% of shots.

We recommend Energizer batteries. As of 01.01.2008. All data reserved and subject to change without notice. .



[You're reading an excerpt. Click here to read official PENTAX K200 user guide](#)

<http://yourpdfguides.com/dref/2342635>