



# Your PDF Guides

You can read the recommendations in the user guide, the technical guide or the installation guide for RICOH AFICIO MP C4501. You'll find the answers to all your questions on the RICOH AFICIO MP C4501 in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

**User manual RICOH AFICIO MP C4501**  
**User guide RICOH AFICIO MP C4501**  
**Operating instructions RICOH AFICIO MP C4501**  
**Instructions for use RICOH AFICIO MP C4501**  
**Instruction manual RICOH AFICIO MP C4501**

**RICOH**

Work smarter and faster



Aficio MP C4501/MP C5501



[You're reading an excerpt. Click here to read official RICOH AFICIO MP C4501 user guide](http://yourpdfguides.com/dref/3799378)  
<http://yourpdfguides.com/dref/3799378>

**Manual abstract:**

Outstanding eco specs include lowest in-class power consumption to reduce the environmental impact of your office. Advanced security features ensure that these highly reliable multifunctional printers are trusted partners in your office. Stay secure with standard HDD overwrite and encryption features. Print from USB memory or SD card (optional). Manage print costs with quota setting. Print/copy at 45/55 colour pages per minute. Scan at high speed with single pass duplex (MP C4501SPDF/MP C5501SPDF). Totally reliable, fully functional OPTIMAL PRODUCTIVITY ENSURED Choose the AficioTMMMP C4501/MP C5501 for high productivity and efficiency. After taking only 22/36 seconds to warm up, these devices race along at 45/55 colour pages per minute. The warm-up time of the single pass duplex models is 24/38 seconds.

Recovery from sleep mode is equally fast: a mere 20/32 seconds and 20/34 for SPDF models accordingly. Massive documents are no problem as the trays can hold up to 4,400 sheets. Save time by printing directly from a USB memory stick or SD card with the optional USB/SD slot (printable file formats: PDF, JPEG and TIFF). DUPLEX MAKES THE DIFFERENCE Simplex scanning is a fast 67 pages per minute. @@@@Set and manage the number of outputs of each individual or group.

@@The devices can also be set to Eco Mode, a setting which can help you reduce energy use significantly. For a fast warm-up time the devices incorporate Ricoh's IH roller fusing system. In addition, Ricoh products are Energy Star compliant. This means less CO2 is produced in providing the energy needed to run Ricoh devices. COPIER Copying process: Copy speed: Resolution: Multiple copy: Warm-up time: First output speed: Zoom: Memory: HDD: Paper input capacity: Laser beam scanning & electro-photographic printing Full colour: 45/55 copies per minute B/W: 45/55 copies per minute 600 dpi Up to 999 22/36 seconds (24/38 seconds for SDPF) Full colour: 5.

9/5.0 seconds B/W: 3.7/3.1 seconds 25 - 400% (in 1% steps) 2 GB (standard) 160 GB (standard) Standard: 2 x 550-sheet paper trays 1 x 100-sheet bypass tray Maximum: 4,400 sheets Maximum: 3,625 sheets A6 - A3 Paper trays: 60 - 256 g/m<sup>2</sup> Bypass tray: 60 - 300 g/m<sup>2</sup> Duplex unit: 60 - 169 g/m<sup>2</sup> Standard 670 x 677 x 760 mm Less than 130/133 kg (with ARDF/SPDF) 220 - 240 V, 50/60 Hz Operation: Maximum 1.7 kW Energy saver mode: 102 W Auto Off mode: 1.5 W 2.64/3.53 kWh (MP C4501AD/MP C5501AD) SCANNER Scan speed: Maximum 67 originals per minute (LEF, A4, 200/300 dpi) (with ARDF) Maximum 85/116 originals per minute (LEF, A4, 200/300 dpi) (with SPDF, simplex/duplex) Maximum 1,200 dpi (TWAIN scan only) A5 - A3 PDF/JPEG/TIFF/High compression PDF Network TWAIN SMTP, POP3 Maximum 500 per job Maximum 2,000 Via LDAP or locally on Hard Disk Drive SMB, FTP, NCP Maximum 50 folders per job Resolution: Original size: Output formats: Bundled drivers: Scan to e-mail: Destination addresses: Stored destination addresses: Address book: Scan to folder: Destination: Paper output capacity: Paper size: Paper weight: SOFTWARE SOLUTIONS SmartDeviceMonitorTM, Web SmartDeviceMonitorTM, Web Image Monitor Duplexing: Dimensions (W x D x H): Weight: Power source: Power consumption: FAX (OPTION) Circuit: Compatibility: Modem speed: Resolution: Compression method: Scanning speed: Memory capacity: Memory backup: PSTN, PBX ITU-T (CCITT) G3, ITU-T (T.37) Internet fax, ITU-T (T.38) IP fax Maximum: 33.

6 Kbps Standard/detail: 200 x 100/200 dpi Maximum: 400 x 400 dpi (option) MH, MR, MMR, JBIG 0.8 seconds (A4, SEF, standard/detail mode) Standard: 4 MB Maximum: 28 MB Yes TEC: PRINTER Print speed: Printer language: Resolution: Interface: Full colour: 45/55 prints per minute B/W: 45/55 prints per minute Standard: PCL5c, PCL6 (XL) Option: Adobe® PostScript® 3TM, IPDS Maximum: 1,200 x 1,200 dpi Standard: Ethernet 10 base-T/100 base-TX, USB 2.0, USB Host I/F Option: Bi-directional IEEE 1284/ECP, Wireless LAN (IEEE 802.11a, b, g, WPA support), Ethernet 1000 base-T, USB 2.0/SD Slot TCP/IP, IPX/SPX Windows® 2000/XP/Vista/7/Server 2003/ Server 2008/Server 2008R2, Novell® NetWare® 6.5, Sun® Solaris 2.6/7/8/9/10, HP-UX 10.x/11.x/11iv2/11iv3, SCO OpenServer 5.0. 6/5.0.7/6.0, RedHat® Linux 6.x/7.

x/8.x/9.x/Enterprise, IBM® AIX v4.3/5L v5.1/v5.2/v5.3, Macintosh OS X v10.2 or later (OS X native), IBM® System i5TM HPT, SAP® R/3®, NDPS Gateway, AS/400® using OS/ 400 Host Print Transform, Citrix OTHER OPTIONS Platen cover, 100-sheet Auto Reverse Document Feeder, Scanner accessibility option, Low cabinet, 2 x 550-sheet paper trays, 1,200-sheet side large capacity tray, 2,000-sheet large capacity tray, Bridge unit, 1,000-sheet multi-tray finisher, 2,000-sheet booklet finisher, 3,000-sheet finisher, Several punch kits, 2nd G3 port, Fax memory unit, Internal shift tray, One-bin tray, Side tray, Envelope feeder, Browser unit, Card reader bracket, File Format Converter, Data Overwrite Security Unit, Counter interface unit, Key counter bracket, Remote Communication Gate, GlobalScan NX, Card authentication package, USB 2.0/SD Slot, Unicode Font Package for SAP, Camera direct print card, Professional software solutions Ricoh has designed these products to meet EC ENERGY STAR guidelines for energy efficiency. For availability of models, options and software, please consult your local Ricoh supplier. Network protocol: Supported environments: ISO9001 certified, ISO14001 certified All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. @@@Copyright © 2009 Ricoh Europe PLC. All rights reserved.



[You're reading an excerpt. Click here to read official RICOH AFICIO MP C4501 user guide](http://yourpdfguides.com/dref/3799378)  
<http://yourpdfguides.com/dref/3799378>