



Your PDF Guides

You can read the recommendations in the user guide, the technical guide or the installation guide for SENNHEISER SR 300 IEM G2. You'll find the answers to all your questions on the SENNHEISER SR 300 IEM G2 in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

User manual SENNHEISER SR 300 IEM G2
User guide SENNHEISER SR 300 IEM G2
Operating instructions SENNHEISER SR 300 IEM G2
Instructions for use SENNHEISER SR 300 IEM G2
Instruction manual SENNHEISER SR 300 IEM G2



General Description
The heart of the evolution wireless monitoring system is the SR 300 IEM rack-mount transmitter, which transmits the monitoring signals to the extremely compact ER 300 IEM bodypack receiver. Designed for rugged live work, the receiver is easy to use and protected against accidental operation. The artist or the sound engineer listens via stereo earphones, with pain-friendly ear-impacts. Transmitter and receiver have nine frequency banks with up to 12 directly accessible presets each - ready for immediate use.
The receiver is fitted with a special Focus mode, i.e. it can be switched from stereo reception to double mono, with one channel reserved for the mix and the other one for your own voice/instrument. The level of each channel is set by the balance control. The receiver also features a switchable audio limiter, which keeps the monitoring sound at a safe level.

Technical Data
System
Frequency ranges 518-554, 626-662, 740-776, 788-822, 830-866 MHz
Transmission/receiving frequencies 1,440
Compatible frequencies per frequency bank up to 12
Compressor HDX
AF frequency response 40-15,000 Hz
Signal-to-noise ratio 91 dB
Pilot tone-equival. 19 kHz, stereo-HFX (can be switched off)



Receiver
Scan function receiver scans one frequency bank
Adjacent channel rejection > 70 dB
Intermodulation distortion > 70 dB
Sensitivity (with HDX, at peak deviation) < 2.5 µV at 52 dB, S/N EQ preset HI Boost (+6 dB @ 10 kHz)
Dimensions 87 x 64 x 24 mm
Operating time 6-10 hrs, depending on volume
Weight approx. 170 g

- Optional Accessories**
- CCZ carrying case for a complete SR 300 IEM system Cat. No. 009826
 - BA 2015 accupack for ER 300 IEM receiver Cat. No. 009993
 - L 2015 charger for BA 2015 accupack Cat. No. 009828
 - GA 2 19" rack adaptor Cat. No. 009823
 - HA/2 antenna mount Cat. No. 009913
 - A 1031-U passive omni-directional antenna Cat. No. 004645
 - A 2003-UHF passive directional antenna Cat. No. 003858
 - AC 2 antenna combiner Cat. No. 009832
 - NT 3 plug-in mains unit for A 2 NT 3 Cat. No. 004863
 - NT 3-120 Cat. No. 004864
 - NT 3-UK Cat. No. 004865



You're reading an excerpt. [Click here to read official SENNHEISER SR 300 IEM G2 user guide](http://yourpdfguides.com/dref/3709959)
<http://yourpdfguides.com/dref/3709959>

Manual abstract:

The artist or the sound engineer listens via stereo earphones with skin-friendly ear-moulds. Transmitter and receiver have nine frequency banks with up to 12 directly accessible presets each ready for immediate use. The receiver is fitted with a special Focus mode, i. e. it can be switched from stereo reception to double mono, with one channel reserved for the mix and the other one for your own voice/instrument. The level of each channel is set by the balance control. The receiver also features a switchable audio limiter which keeps the monitoring sound at a safe level. Technical Data System Frequency ranges ...

.....
.....
@@1,440 Compatible frequencies per frequency bank @@91 dB Pilot tone squelch

.....
.....
.....
..... @@@@ @@@@ approx.

@@30 mW Max. input voltage (unbalanced, peak deviation)

.....
.....
.approx. 2.4 Vrms Dimensions

.....
.....
.....
.....
.....212 x 145 x 38 mm Weight ...

.....
.....
.....
.....
.....

..... approx. 1,100 g Optional Accessories CC2 carrying case for a complete ew 300 IEM g system BA 2015 accupack for EK 300 IEM g L 2015 charger for BA 2015 accupack GA 2 19" rack adaptor AM 2 antenna mount A 1031-U passive omni-directional antenna A 2003-UHF passive directional antenna AC 2 antenna combiner NT 3 plug-in mains unit for A 2 NT 3 NT 3-120 NT 3-UK Cat. No. 009826 Cat.

No. 009950 Cat. No. 009828 Cat. No.

009823 Cat. No. 009912 Cat. No. 004645 Cat.

No. 003658 Cat. No. 009822 Cat. No. 004863 Cat. No. 004864 Cat. No. 004865 j j j j j j j j evolution wireless g 300 IEM Series RF Wireless Systems | evolution wireless g System overview 300 IEM g Ready-to-use wireless monitoring system; additional bodypack receivers with earphones are available separately.



[You're reading an excerpt. Click here to read official SENNHEISER](#)

[SR 300 IEM G2 user guide](#)

<http://yourpdfguides.com/dref/3709959>