



Your PDF Guides

You can read the recommendations in the user guide, the technical guide or the installation guide for SMC 8926EM. You'll find the answers to all your questions on the SMC 8926EM in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

User manual SMC 8926EM
User guide SMC 8926EM
Operating instructions SMC 8926EM
Instructions for use SMC 8926EM
Instruction manual SMC 8926EM

POWER TO CONNECT
www.smc.com

SMC8926EM / SMC8950EM
TigerStack II 10/00 Stackable 24/48 10/100/1000
Managed Layer 3 Switch with 2 x 10G Uplink slots

OVERVIEW
SMC Networks' TigerStack™ II 10/100/1000 SMC8926EM/SMC8950EM switches are a new enhanced series of high performance stackable switches that deliver high scalability, wire-speed Gigabit performance, high availability, 10 Gigabit Ethernet uplinks, and redundant power options. These switches were the first to include both IPv4 and IPv6 Management options enabling future proofed flexibility and maintainability.

The TigerStack II 10/100/1000 SMC8926EM/SMC8950EM stacks up to 4 units in a stack, providing up to 192 Gigabit ports. A stack can be created with either 24 or 48 port switches, providing unprecedented flexibility. It provides 48 built-in copper Gigabit ports, including (4) Combo SFP ports supporting either copper links or SFP adapters for easy, flexible connection to fiber-based Gigabit media and a switching capacity of up to 186Gbps. The 2 10G module slots on the rear of the switch provide support for XFP 10G connections. These provide high bandwidth connections to the core of a network and are in addition to the 2 stacking connectors giving high capacity connections to the other units in the stack.

The SMC8926EM/SMC8950EM is the latest example of SMC's continued commitment to our channel partners and customers to be the industry leader in cost-effective, reliable, high performance, feature-rich switches.

KEY FEATURES

Layer 3 Routing Support

Advanced edge networks can have the requirement for layer 3 routing and this family of switches is able to offer that support in hardware without additional cost.

Flexible Security Features

Security is critical for advanced edge networks. This switch family includes a range of User and Device security functions which will help protect the network. Secure management interfaces for protecting device configuration and secure user access using 802.1x or Private Vlans to prevent unauthorized access.

Performance and Redundancy

Advanced edge networks are demanding higher performance and reduced down time. SMC is committed to both of these requirements. Stacking switches together in a single wiring closet increases the uplink flexibility in terms of 10G uplinks and redundancy in the event of a device problem. Similarly this switch includes a Redundant Power option to protect against primary power failure.

Quality of Service

Networks are supporting many different types of data including voice, video, email, file transfers. Each data type has different characteristics and requirements. The SMC TigerSwitch II switches provide 8 levels of priority in hardware and flexible software to configure the system to address your specific network requirements.

APPLICATION DIAGRAM

LEGEND

- 10G FIBER
- 1G FIBER
- 10G COPPER
- 1G COPPER
- 10GDC
- RJ45
- PHONE/CABLES
- WIRELESS

SWITCHES
VDL
WIRELESS
VOIP
STORAGE
BROADBAND
ADAPTERS



[You're reading an excerpt. Click here to read official SMC 8926EM user guide](http://yourpdfguides.com/dref/3457410)
<http://yourpdfguides.com/dref/3457410>

Manual abstract:

The TigerStack II 10/100/1000 SMC8926EM/SMC8950EM stacks up to 4 units in a stack, providing up to 192 Gigabit ports. A stack can be created with either 24 or 48 port switches, providing unprecedented flexibility. It provides 48 built-in copper Gigabit ports, including (4) Combo SFP ports supporting either copper links or SFP adapters for easy, flexible connection to fiber-based Gigabit media and a switching capacity of up to 186Gbps. The 2 10G module slots on the rear of the switch provide support for XFP 10G connections. These provide high bandwidth connections to the core of a network and are in addition to the 2 stacking connectors giving high capacity connections to the other units in the stack. @@@@help protect the network. @@@SMC is committed to both of these requirements. @@@@Each data type has different characteristics and requirements. The SMC TigerSwitch II switches provide 8 levels of priority in hardware and flexible software to configure the system to address your specific network requirements. VOIP APPLICATION dIAGRAM LEGEND 10G FIBER 1G FIBER 10G COPPER 1G COPPER 10/100 PoE WIRELESS STORAGE SERVER SERVER Finance bROAdbANd RD LEGEND 10G FIBER 1G FIBER 10G COPPER 1G COPPER 10/100 PoE PHONE CABLES WIRELESS 6EM/ SMC892 M 0E SMC895 RD Marketin g Network AdAPTERS www.

smc.com TECh SPECS - SMC8926EM/SMC8950EM PORTS · 24/48 10/100/1000bASE-T ports · 4 Combo SFP ports · 2 Stacking ports · 2 10G Module slots NETWORK INTERFACE · 10/100/1000 bASE-T ports · XFP Transceiver slots supporting SR, LR and ER XFP · Multimode fiber cable; 62.5/125 or 50/125 microns · Singlemode fiber cable: 9/125 micron SWITCHING FABRIC · SMC8926EM · 138Gbps · 103Mpps · SMC8950EM · 186Gbps · 138Mpps bUFFER ARChITECTURE · SMC8926EM · 2Mbytes · SMC8950EM · 4Mbytes SWITCHING dATABASE · 16k MAC address entries LEd · System: Stack Master, Stack Link, Module, Power, diag, RPS · Port: Link/Activity WEIGHt · SMC8926EM/SMC8950EM: 6.1kg / 13.4lbs DIMENSIONS · 44.

0 x 41.5 x 4.4 cm / 17.4 x 16.4 x 1.

8 in. TEMPERATURE · Operating: 0 to 50 °C (32 to 122 °F) · Storage: -40 to 70 °C (-40 to 158 °F) hUMIdITy · Operating: 5% to 95% (non-condensing) AC INPUT · 100 to 240 V, 50-60 hz, 2A POWER SUPPLY · Internal, auto-ranging transformer: 100 to 240 VAC, 50 to 60 hz · External, supports connection for redundant power supply POWER CONSUMPTION · SMC8926EM · 66 Watts · SMC8950EM · 105 Watts MAXIMUM CURRENT · 1.6 A @ 100 VAC · 0.6 A @ 230 VAC MTbF · 8 years SWITCH FEATURES · RiPvI/2 · Static routing · OSPF · VRRP · LACP 802.3ad (up to 32) · VLANs (up to 4k) · GVRP · 802.1v (Protocol based VLANs) · Private VLAN support · Spanning Tree (802.1d, 802.1w, 802.1s) · broadcast Storm Control · Flow Control · IGMP Snooping (v1,v2,v3) · IGMP Querying · IGMP Immediate Leave · Jumbo Frame (up to 9k) · ACL's · 802.1x · RADIUS · TACACS+ · Static Port Security · dNS · QinQ · LLdP QUALITy OF SERVICE · Supports 8 levels of priority with flexible classification and prioritization · Per port bandwidth management · diffServ dIAGNOSTIC FEATURES · Port Mirroring · Remote Ping · Event/Error Log · SMTP · SNMP MANAGEMENT FEATURES · In-band Features · IPv6 and IPv4 support · Telnet and SSh · hTTP and hTTPS · SNMP (v1,v2c,v3) · Out-of-band Management · RS-232 Console port · Software upgrade · TFTP or XModem · dual Firmware Images · Configuration download/Upload RMON SUPPORT · Groups 1,2,3, 9 (Statistics, history, Alarm, Event) STANdARdS · IEEE 802.

3-2002 Ethernet, Fast Ethernet, Gigabit Ethernet · IEEE 802.3ae 10 Gigabit Ethernet · IEEE 802.1d Spanning Tree Protocol · IEEE 802.1w Rapid Spanning Tree Protocol · IEEE 802.1s Multiple Spanning Tree Protocol · IEEE 802.1Q Virtual LAN · IEEE 802.1p Priority tags · IEEE 802.3ad Link aggregation control protocol · IEEE 802.1v Protocol based Vlans COMPLIANCE · ISO · IEC8802.3 POWER TO CONNECT CE MARK EMISSIONS · FCC Class A · Industry Canada Class A · EN55022 (CISPR 22) Class A · EN 61000-3-2/3 IMMUNITY · EN 61000-4-2/3/4/5/6/8/11 SAFETY · CSA/CUS (CSA 22. 2. NO 60950-1 & UL60950-1) · Cb (IEC60950-1) WARRANTy · Please check www.smc.com for the warranty terms in your country/region SUPPORTED MOdULES ANd CabLES STACKING CabLES SMC8700S-30 · 30cm stacking cable SMC8700S-130 · 130cm stacking cable SMC8700S-300 · 300cm stacking cable SMCXFPMod MOdULE · 1 Port XFP module SLIdE-IN TRANSCeIVERS FOR 10G MOdULE SMC10GXFP-SR · 10G SR XFP Transceiver, 300m, Multimode fiber SMC10GXFP-LR · 10G LR XFP Transceiver, 10km, Single mode fiber SLIdE-IN TRANSCeIVERS FOR COMbO PORTS SMC1GSFP-SX · 1G SX SFP Transceiver, 550M, Multimode fiber SMC1GSFP-LX · 1G LX SFP Transceiver, 10km, Singlemode fiber SMC1GSFP-ZX · 1G Lh SFP Transceiver, 70km Singlemode fiber SWITCHES VdSL WIRELESS VOIP STORAGE CONTACT North America 20 Mason Irvine, CA 92618 1-800-SMC-4yOU 24/7 Technical Support Europe/Africa Fructuos Gelabert 6-8 08970 Sant Joan despí barcelona, Spain Check www.smc.com for your local country contact information © 2009 SMC Networks. SMC and the SMC logo are registered trademarks of SMC Networks in the United States or other countries. @@Information is subject to change without notice. All rights reserved. 8/2010 bROAdbANd AdAPTERS .



[You're reading an excerpt. Click here to read official SMC 8926EM user guide](http://yourpdfguides.com/dref/3457410)

<http://yourpdfguides.com/dref/3457410>