



Your PDF Guides

You can read the recommendations in the user guide, the technical guide or the installation guide for TOSHIBA RAS-07PKVP-E. You'll find the answers to all your questions on the TOSHIBA RAS-07PKVP-E in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

User manual TOSHIBA RAS-07PKVP-E
User guide TOSHIBA RAS-07PKVP-E
Operating instructions TOSHIBA RAS-07PKVP-E
Instructions for use TOSHIBA RAS-07PKVP-E
Instruction manual TOSHIBA RAS-07PKVP-E

TOSHIBA
Leading Innovation >>>



E09-321



[You're reading an excerpt. Click here to read official TOSHIBA RAS-07PKVP-E user guide](http://yourpdfguides.com/dref/3703255)
<http://yourpdfguides.com/dref/3703255>

Manual abstract:

DIMENSION 3. WIRING DIAGRAM 4. SENSIBLE CAPACITY TABLE 5. PART LOAD PERFORMANCE 6. AIR SPEED DISTRIBUTION 7. @ - max.)

Rated current (220V / 230 V / 240V) Power input Power input (min. @ @ 0 7 - 0. @ @ @ @ Piping Length Min. Piping Length Chargeless Length Max.

@ @ 55 A Heating 4.0 0.3 - 6.1 4.01 / 3.

84 / 3.68 0.84 0.07 - 1.60 95 4.

76 A 9.5 RAS-13PKVP-E 295 x 790 x 242 12 696 / 318 193 / 88 696 / 348 193 / 97 30 45 / 27 45 / 27 60 / 42 60 / 42 RAS-13PAVP-E 550 x 780 x 290 40 43

750 Twin rotary 50 50 65 65 aiseikai PKVP/PAVP Technical specifications Heat Pump RAS-16PKVP-E RAS-16PAVP-E 220-240/1/50, 220-230/1/60 Cooling

4.5 0.3 - 5.0 5.81 / 5.56 / 5.33 1.22 0.07 - 1.

49 96 3.69 A Heating 5.5 0.3 - 6.5 6.24 / 5.97 / 5.72 1. 34 0.07 - 1.

70 98 4. @ @ 07 - 1. 75 97 3. 36 A Heating 6.0 0.

3 - 6.7 7.16 / 6.85 / 6.57 1.

54 0.07 - 1.75 98 3.90 A 9.5 RAS-18PKVP-E 295 x 790 x 242 12 804 / 408 223 / 113 804 / 420 223 / 117 30 49 / 31 49 / 31 64 / 46 64 / 46 RAS-18PAVP-E

550 x 780 x 290 40 43 750 Twin rotary 52 52 67 67 6.35 - 12.7 1/4" - 1/2" Flare 20 2 15 10 6.35 - 12.7 1/4" - 1/2" Flare 20 2 15 10 WH-H06JE Remote

control holder Drain nipple Water-proof rubber cap (2 pieces) WH-H06JE Remote control holder Drain nipple Water-proof rubber cap (2 pieces) 21 to 32

deg C / 0 to 28 deg C -10 to 46 deg C / -15 to 24 deg C 21 to 32 deg C / 0 to 28 deg C -10 to 46 deg C / -15 to 24 deg C uper aiseikai PKVP/PAVP Dimension

RAS-07PAVP-E, RAS-10PAVP-E uper Dimension RAS-13PAVP-E, RAS-16PAVP-E, RAS-18PAVP-E aiseikai PKVP/PAVP uper aiseikai PKVP/PAVP

Wirering diagram RAS-07PKVP-E/RAS-07PAVP-E, RAS-10PKVP-E/RAS-10PAVP-E, RAS-13PKVP-E/RAS-13PAVP-E, RAS-16PKVP-E/RAS-16PAVP-E,

RAS-18PKVP-E/RAS-18PAVP-E uper Sensible capacity table Indoor Unit : RAS-07PKVP-E Outdoor Unit : RAS-07PAVP-E Outdoor temperature (CDB)

10.0 12.

0 14.0 16.0 18.0 20.0 21.0 23.0 25.0 27.0 29.0 31.

0 33.0 35.0 37.0 39.0 14.

0 CWB 20.0 CDB TC SHC (kW) (kW) 2.4 2.1 2.3 2.

1 2.3 2.1 2.2 2.0 2.2 2.0 2.1 2.0 2.1 2.

0 2.1 2.0 2.0 1.9 2.0 1.9 1.9 1.9 1.9 1.

9 1.9 1.8 1.8 1.8 1.

8 1.8 1.7 1.7 16.0 CWB 23.

0 CDB TC SHC (kW) (kW) 2.5 2.2 2.4 2.2 2.4 2.2 2.3 2.2 2.3 2.

1 2.2 2.1 2.2 2.1 2.2 2.1 2.1 2.0 2.1 2.

0 2.0 2.0 2.0 2.0 1.

9 1.9 1.9 1.9 1.8 1.

8 1.8 1.8 Indoor temperature 18.0 CWB 20.0 CWB 26.0 CDB 28.0 CDB TC SHC TC SHC (kW) (kW) (kW) (kW) 2.6 2.3 2.7 2.

4 2.5 2.3 2.7 2.4 2.5 2.3 2.6 2.3 2.4 2.

3 2.6 2.3 2.4 2.3 2.

5 2.3 2.3 2.2 2.5 2.

3 2.3 2.2 2.4 2.3 2.3 2.2 2.4 2.2 2.2 2.

1 2.3 2.2 2.2 2.2 2.3 2.2 2.1 2.1 2.2 2.

2 2.1 2.1 2.2 2.1 2.

0 2.0 2.1 2.1 2.0 2.

0 2.1 2.0 1.9 1.9 2.0 2.0 1.9 1.9 2.0 1.

9 aiseikai PKVP/PAVP TC : Total cooling capacity SHC : Sensible heat capacity 22.0 CWB 30.0 CDB TC SHC (kW) (kW) 2.9 2.4 2.9 2.4 2.8 2.4 2.8 2.

3 2.7 2.3 2.6 2.3 2.

6 2.2 2.6 2.3 2.5 2.

2 2.4 2.2 2.4 2.2 2.3 2.1 2.3 2.1 2.2 2.

1 2.2 2.0 2.1 2.0 24.0 CWB 32.0 CDB TC SHC (kW) (kW) 3.1 2.4 3.1 2.

4 3.0 2.4 2.9 2.4 2.

9 2.3 2.8 2.3 2.7 2.

2 2.7 2.3 2.7 2.3 2.6 2.2 2.5 2.2 2.5 2.

2 2.4 2.1 2.4 2.1 2.3 2.1 2.2 2.1 Indoor Unit : RAS-10PKVP-E Outdoor Unit : RAS-10PAVP-E Outdoor temperature (CDB) 10.0 12.

0 14.0 16.0 18.0 20.0 21.

0 23.0 25.0 27.0 29.0 31.

0 33.0 35.0 37.0 39.0 14.0 CWB 20.0 CDB TC SHC (kW) (kW) 2.9 2.4 2.8 2.

4 2.8 2.3 2.7 2.3 2.7 2.3 2.6 2.3 2.6 2.

2 2.6 2.2 2.5 2.2 2.

5 2.2 2.4 2.1 2.4 2.

1 2.3 2.1 2.3 2.1 2.2 2.0 2.1 2.0 16.0 CWB 23.

0 CDB TC SHC (kW) (kW) 3.1 2.5 3.0 2.5 2.9 2.5 2.9 2.4 2.8 2.
4 2.8 2.4 2.7 2.4 2.
7 2.3 2.6 2.3 2.6 2.
3 2.5 2.3 2.5 2.2 2.4 2.2 2.4 2.2 2.3 2.

2 2.2 2.1 Indoor temperature 18.0 CWB 20.0 CWB 26.0 CDB 28.0 CDB TC SHC TC SHC (kW) (kW) (kW) (kW) 3.2 2.6 3.4 2.
7 3.1 2.6 3.3 2.7 3.
1 2.6 3.3 2.7 3.0 2.
6 3.2 2.6 3.0 2.5 3.1 2.6 2.9 2.5 3.1 2.

6 2.9 2.5 3.0 2.6 2.8 2.5 3.0 2.5 2.8 2.
4 2.9 2.5 2.7 2.4 2.
8 2.5 2.6 2.4 2.8 2.
4 2.6 2.4 2.7 2.4 2.5 2.3 2.7 2.4 2.5 2.

3 2.6 2.4 2.4 2.3 2.5 2.3 2.3 2.2 2.4 2.

3 TC : Total cooling capacity SHC : Sensible heat capacity 22.0 CWB 30.0 CDB TC SHC (kW) (kW) 3.6 2.8 3.
5 2.7 3.5 2.7 3.4 2.
7 3.3 2.6 3.3 2.6 3.2 2.6 3.2 2.6 3.1 2.

5 3.0 2.5 3.0 2.5 2.9 2.4 2.8 2.4 2.8 2.
4 2.7 2.4 2.6 2.3 2.4.

0 CWB 32.0 CDB TC SHC (kW) (kW) 3.9 2.8 3.8 2.
8 3.7 2.7 3.6 2.7 3.6 2.7 3.5 2.6 3.5 2.

6 3.4 2.6 3.3 2.6 3.3 2.5 3.2 2.5 3.1 2.
5 3.0 2.4 3.0 2.4 2.

9 2.4 2.7 2.3 Indoor Unit : RAS-13PKVP-E Outdoor Unit : RAS-13PAVP-E Outdoor temperature (CDB) 10.0 12.
0 14.0 16.0 18.0 20.0 21.0 23.0 25.0 27.0 29.0 31.

0 33.0 35.0 37.0 39.0 14.0 CWB 20.0 CDB TC SHC (kW) (kW) 4.1 3.1 4.0 3.
1 3.9 3.0 3.8 3.0 3.
8 3.0 3.7 2.9 3.7 2.
9 3.6 2.9 3.5 2.8 3.4 2.8 3.4 2.7 3.3 2.

7 3.2 2.7 3.1 2.6 3.1 2.6 3.0 2.5 16.0 CWB 23.
0 CDB TC SHC (kW) (kW) 4.3 3.3 4.2 3.2 4.
1 3.2 4.1 3.1 4.0 3.
1 3.9 3.1 3.9 3.0 3.8 3.0 3.7 3.0 3.6 2.

9 3.5 2.9 3.5 2.8 3.4 2.8 3.3 2.8 3.2 2.

7 3.1 2.7 Indoor temperature 18.0 CWB 20.0 CWB 26.
0 CDB 28.0 CDB TC SHC TC SHC (kW) (kW) (kW) (kW) 4.5 3.4 4.8 3.
5 4.4 3.4 4.7 3.5 4.4 3.3 4.6 3.4 4.3 3.

3 4.5 3.4 4.2 3.2 4.4 3.3 4.1 3.2 4.3 3.
3 4.1 3.2 4.3 3.3 4.
0 3.1 4.2 3.2 3.9 3.
1 4.1 3.2 3.8 3.1 4.0 3.1 3.7 3.0 3.9 3.

1 3.6 3.0 3.8 3.1 3.5 2.9 3.7 3.0 3.5 2.
9 3.6 3.0 3.4 2.9 3.
6 2.9 3.3 2.8 3.5 2.

9 TC : Total cooling capacity SHC : Sensible heat capacity 22.0 CWB 30.0 CDB TC SHC (kW) (kW) 5.1 3.6 5.0 3.5 4.9 3.5 4.8 3.

4 4.7 3.4 4.6 3.3 4.6 3.3 4.5 3.3 4.4 3.
2 4.3 3.2 4.2 3.1 4.
1 3.1 4.0 3.1 3.9 3.

0 3.8 3.0 3.7 2.9 24.0 CWB 32.0 CDB TC SHC (kW) (kW) 5.4 3.7 5.3 3.

6 5.2 3.6 5.1 3.5 5.0 3.5 4.9 3.4 4.9 3.
4 4.8 3.3 4.7 3.3 4.
6 3.3 4.5 3.2 4.4 3.

2 4.3 3.1 4.2 3.1 4.1 3.0 4.0 3.0 uper aiseikai PKVP/PAVP Sensible capacity table Indoor Unit : RAS-16PKVP-E Outdoor Unit : RAS-16PAVP-E Outdoor temperature (CDB) 10.0 12.

0 14.0 16.0 18.0 20.0 21.0 23.0 25.0 27.0 29.0 31.

0 33.0 35.0 37.0 39.0 14.
0 CWB 20.0 CDB TC SHC (kW) (kW) 5.2 3.8 5.1 3.
8 5.0 3.7 4.9 3.7 4.8 3.6 4.7 3.6 4.7 3.

6 4.6 3.5 4.5 3.4 4.4 3.4 4.3 3.3 4.2 3.
3 4.1 3.2 4.0 3.2 3.

9 3.1 3.8 3.0 16.0 CWB 23.
0 CDB TC SHC (kW) (kW) 5.5 4.0 5.4 3.9 5.3 3.9 5.2 3.8 5.1 3.

8 5.0 3.7 4.9 3.7 4.8 3.6 4.7 3.6 4.6 3.
5 4.5 3.5 4.4 3.4 4.
3 3.4 4.2 3.3 4.1 3.

2 4.0 3.2 Indoor temperature 18.0 CWB 20.0 CWB 26.0 CDB 28.0 CDB TC SHC TC SHC (kW) (kW) (kW) (kW) 5.8 4.1 6.1 4.

2 5.7 4.1 6.0 4.2 5.6 4.0 5.9 4.1 5.5 4.
0 5.8 4.1 5.4 3.9 5.
7 4.0 5.3 3.9 5.6 4.
0 5.2 3.8 5.5 3.9 5.1 3.8 5.4 3.9 5.0 3.

7 5.3 3.8 4.9 3.7 5.2 3.8 4.8 3.6 5.0 3.
7 4.7 3.6 4.9 3.7 4.
6 3.5 4.8 3.6 4.4 3.
5 4.7 3.5 4.3 3.4 4.6 3.5 4.2 3.3 4.4 3.

4 TC : Total cooling capacity SHC : Sensible heat capacity 22.0 CWB 30.0 CDB TC SHC (kW) (kW) 6.5 4.4 6.4 4.3 6.3 4.2 6.2 4.

2 6.1 4.1 5.9 4.1 5.
9 4.0 5.8 4.0 5.6 3.
9 5.5 3.9 5.4 3.8 5.3 3.7 5.1 3.7 5.0 3.

6 4.9 3.6 4.8 3.5 24.0 CWB 32.0 CDB TC SHC (kW) (kW) 7.0 4.5 6.8 4.
4 6.7 4.3 6.6 4.3 6.
5 4.2 6.3 4.2 6.3 4.
1 6.1 4.1 6.0 4.0 5.9 3.9 5.7 3.9 5.6 3.

8 5.5 3.8 5.3 3.7 5.2 3.6 5.1 3.6 Indoor Unit : RAS-18PKVP-E Outdoor Unit : RAS-18PAVP-E Outdoor temperature (CDB) 10.0 12.

0 14.0 16.0 18.0 20.0 21.
0 23.0 25.0 27.0 29.0 31.
0 33.0 35.0 37.0 39.0 14.0 CWB 20.0 CDB TC SHC (kW) (kW) 5.7 4.2 5.6 4.

1 5.5 4.1 5.4 4.0 5.3 4.0 5.2 3.9 5.2 3.
9 5.1 3.8 5.0 3.8 4.
9 3.7 4.7 3.6 4.6 3.
6 4.5 3.5 4.4 3.5 4.3 3.4 4.2 3.3 16.0 CWB 23.

0 CDB TC SHC (kW) (kW) 6.1 4.4 5.9 4.3 5.8 4.2 5.7 4.2 5.6 4.
1 5.5 4.1 5.5 4.0 5.
3 4.0 5.2 3.9 5.1 3.
9 5.0 3.8 4.9 3.7 4.8 3.7 4.7 3.6 4.6 3.

6 4.4 3.5 Indoor temperature 18.0 CWB 20.0 CWB 26.0 CDB 28.0 CDB TC SHC TC SHC (kW) (kW) (kW) (kW) 6.4 4.5 6.7 4.

6 6.3 4.4 6.6 4.6 6.
2 4.4 6.5 4.5 6.0 4.
4 6.4 4.5 5.9 4.3 6.2 4.4 5.8 4.2 6.1 4.

3 5.8 4.2 6.1 4.3 5.6 4.1 5.9 4.3 5.5 4.
1 5.8 4.2 5.4 4.0 5.
7 4.1 5.3 4.0 5.6 4.
1 5.2 3.9 5.4 4.0 5.0 3.8 5.3 3.9 4.9 3.

8 5.2 3.9 4.8 3.7 5.1 3.8 4.7 3.7 4.9 3.

8 TC : Total cooling capacity SHC : Sensible heat capacity 22.0 CWB 30.0 CDB TC SHC (kW) (kW) 7.2 4.8 7.

1 4.7 6.9 4.6 6.8 4.
6 6.7 4.5 6.6 4.5 6.5 4.4 6.4 4.4 6.2 4.

3 6.1 4.2 6.0 4.2 5.8 4.1 5.7 4.0 5.5 4.
0 5.4 3.9 5.3 3.8 24.

0 CWB 32.0 CDB TC SHC (kW) (kW) 7.7 4.9 7.5 4.

