



Your PDF Guides

You can read the recommendations in the user guide, the technical guide or the installation guide for TRAILERS TA510. You'll find the answers to all your questions on the TRAILERS TA510 in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

User manual TRAILERS TA510
User guide TRAILERS TA510
Operating instructions TRAILERS TA510
Instructions for use TRAILERS TA510
Instruction manual TRAILERS TA510



Livestock



[You're reading an excerpt. Click here to read official TRAILERS TA510 user guide](http://yourpdfguides.com/dref/2446009)
<http://yourpdfguides.com/dref/2446009>

Manual abstract:

As specialists in trailer design and engineering, we have continued to set the standard both in the UK and throughout much of Europe. We are an independent company with one focus: to build the best products on the market. More than 25,000 people choose our trailers each year - but we're not standing still. Our dedicated investment in new technologies and materials ensures that our products continue to exceed the expectations of our customers. We know that quality, strength, value and ease of maintenance are of vital importance to you. That's why we've made them the driving force behind everything we do. Ifor Williams Livestock Trailers Located in rural North Wales, we have grown up in the agricultural community, employing local people with farming links. Our unique understanding of the industry allows us to deliver the highest quality products and contribute to the protection of this precious way of life. Take a look at any of the features of our livestock trailers. You'll find that practicality, safety and reliability are paramount to us.

Flexibility From the smallest P6e to the largest 14' tri axle, Ifor Williams Trailers have something to meet the demands of most livestock farmers.

@@@@@@@@The flooring on these trailers comprises of thick pressure treated timber planking protected by 2mm thick slip resistant aluminium treadplate. Stability when towing DP120 10' (6' headroom) standard ramp All of our braked trailers feature the exclusive Ifor Williams beam axle and leaf spring suspension system which has been developed and refined for a safe and stable ride. Similar systems are widely used on commercial vehicles where performance under load is essential. Renowned for its durability and ease of maintenance the Ifor Williams beam axle system contributes significantly to the low depreciation of our trailers.

P6e Livestock version (750kg) P6e Unbraked Livestock Trailer The P6e is a small trailer with outstanding flexibility both on and off road. Light enough to be towed by a quad bike, it can be used for moving sheep or calves around the farm on short off-road journeys. With the canopy removed, the P6e becomes a general utility trailer for carrying feed, fertiliser and other goods. The optional welded mesh side panels are invaluable when carrying large bulky objects such as wool, branches and firewood. The smallest trailer in our livestock range, the P6e has a floor area of 1.

21m x 1.98m (4'x 6'6" approx.) and a maximum gross weight of either 500 or 750kg. With the axle, drawbar and body panels constructed from hot-dipped galvanized steel, this trailer provides the same built-in quality and durability as all other Ifor Williams trailers. This is also true of the 18mm thick high density plywood platform with a tough, water-proof resin coating on both sides. A factory fitted option of 2mm aluminium treadplate overlay is available. The loading ramp is panelled in 2mm thick slip resistant aluminium treadplate. A single axle (rubber torsion type) is fitted with a choice of either 145R10 (500kg gross weight) or 20.5 x 8-10 (750kg gross weight) flotation tyres. The P6e livestock version includes aluminium ramp gates, ventilation louvres in the front of the canopy and fixing points for the optional cross division.

Other standard features include: Spare wheel and carrier 50mm ball coupling Safety chain Front prop stand Rope hooks Impact resistant plastic mudguards Aluminium / steel loading ramps P6/P8 Livestock Trailers These two models, the lightest in our braked Livestock range, are designed for those who need a light yet robust means of transporting small types of livestock. @@@@@@@@@@Both models offer 4' of headroom with a width of 4'. @@@@@@@@@@The system is shown in more detail later in the brochure. @@@@@@@@@@All trailers have a maximum gross weight of 3500kg; payload varies between 2010kg and 2550kg depending on size and specification. All sizes are available with either the standard ramp, combination ramp doors or with the EasyLoad™ ramp and folding deck system (shown in more detail later in the brochure). TA510 trailers are fitted with a twin axle beam (triaxle option on 14' model), leaf sprung suspension, galvanized steel chassis, aluminium side panels, heat reflecting roof, and grip-faced aluminium planking covered rear ramp. These trailers also feature aluminium ramp gates, pressure treated timber planking with slip resistant aluminium treadplate flooring, receiver brackets for the optional cross divisions, side ventilation flaps and front access door. Other standard features include:

. Spare wheel and carrier 50mm locking ball coupling Aluminium ramp gates Side vents and flaps Split front access door Rear ramp assister Heavy duty Jockey wheel AVAILABLE IN 10', 12', 14' LENGTH & 6', 7' HEADROOM TA510 10' (7' headroom) *Subject always to The Welfare of Animals (Transport) Order 1997. DP120 Dual Purpose Trailers The DP120 range combines a substantial maximum volume and gross weight (3500kg) with the option of a removable container. When the container is removed, the DP120 can be used as a conventional flatbed trailer.

Body lengths of 10', 12' and 14' are available, all with standard headroom of 6'. A triaxle is an option on the 12' model and standard on the 14' version. All sizes are available with either the standard ramp or with the EasyLoad™ ramp and folding deck system (shown in more detail later in the brochure). The trailer also includes aluminium ramp gates, pressure treated timber planking and slipresistant aluminium treadplate flooring, receiver brackets for the optional cross division, side ventilation flaps and a split front access door. Other standard features include: Spare wheel and carrier 50mm ball coupling Aluminium ramp gates Side vents and flaps Split front access door Rear ramp assister Headboard sockets for use with optional headboard in flatbed configuration · Heavy duty Jockey wheel Other options include dropside fittings and kit.

DP120 12' (6' headroom) AVAILABLE IN 10', 12', 14' LENGTH DP120 12' (6' headroom) Livestock Trailer Range STD RAMP EASYLOAD 8' 10' 12' 12' TRI-AXLE 14' 14' TRI-AXLE TA5 4' H/R N/A N/A N/A N/A TA5 6' H/R N/A N/A N/A TA5 7' H/R N/A N/A N/A TA510 6' H/R N/A N/A TA510 7' H/R N/A N/A DP120 N/A N/A Livestock Trailer Features It's the attention to detail of Ifor Williams trailers that makes our products so popular with owners. Just take a look at these standard features. Chassis The underside of the trailer features a galvanized steel chassis and drawbar.



[You're reading an excerpt. Click here to read official TRAILERS](#)

[TA510 user guide](#)

<http://yourpdfguides.com/dref/2446009>

