



Your PDF Guides

You can read the recommendations in the user guide, the technical guide or the installation guide for ZYXEL IES-6000. You'll find the answers to all your questions on the ZYXEL IES-6000 in the user manual (information, specifications, safety advice, size, accessories, etc.). Detailed instructions for use are in the User's Guide.

- User manual ZYXEL IES-6000**
- User guide ZYXEL IES-6000**
- Operating instructions ZYXEL IES-6000**
- Instructions for use ZYXEL IES-6000**
- Instruction manual ZYXEL IES-6000**



Future Proof Next Generation Multi-Service IP Access Solution

Benefits

FutureProof Architecture

As the flagship of Zyxel's IP DSLAM product portfolio, the IES-6000 is equipped with non-blocking Gigabit backplane, Ethernet-based Management Switch Card (MSC), dual input power modules and various high-port density multi-purpose line cards. With comprehensive IP-centric firmware features, the IES-6000 is a high-capacity system that facilitates Telco/ISP to deliver high-quality residential or business user services experience at competitive CAPEX/OPEX as well as satisfying its current and future infrastructural requirements of reliability, flexibility and scalability.

Easy & Reused Logistics

The IES-6000 is a 12.5U-high, 17-slot chassis-based multi-service access node capable of adopting the same line cards as those for ES-500S/5000 systems. The MSC 1024G control card with eight 1G uplinks is designed to fit slot 8 and/or slot 9, while the remaining slots are available for equipping various line cards. The new MSC 1224G control card is with two 10G and six 1G Ethernet uplinks to support even larger bandwidth requirements. The variety of line cards are including 48-port or 72-port ADSL2+ line cards that provide subscribers with asymmetric transmission bandwidth up to 25Mbps/24 Mbps, 48-port SDSL2 line cards with symmetric transmission bandwidth of 5.69 Mbps per port, 24-port and 48-port VDSL2 line cards that offer up to 17.7 (100 Mbps/45 Mbps) high-speed connectivity per port over copper wires, 48-port VoIP line card that supports either 1.248 or SIP protocol and 20-port fiber-based Fast Ethernet line card that supports 100 Mbps transmission speed per port. The primary designed concept of IES-6000 is also taking account of the further technology evolution such as PON.

Advanced Triple Play and Mass Deployment Functionality

The IES-6000 inherits all the Layer 2 and Layer 3 QoS, security and multicast functionalities from the ES-500S/5000, while the following features are added to satisfy the requirements for mass field deployments: (1) IP bridge functionality that alleviates the Layer 2 access network deployment restrictions resulted from MAC address table limitation and security attack issues, (2) ARP Proxy which minimizes the ARP broadcast requests to all subscribers, (3) TACACS+ mechanism to support remote authentication with TACACS+ servers, (4) ISL-based DHCP snooping which binds VLAN information into DHCP snooping tables, (5) DHCP Protection sub-option 2 for providing remote client ID information to DHCP servers for flexible IP address assignment, (6) Cluster management feature that is able to reduce the OPEX of multiple DSLAM maintenance.

- 768/1152 ports, 17 Vertical Slots with a Maximum Configuration of 1 MSC Card and 16 Line Cards
- Multi-service interfaces including ADSL2+, G.SHDSL, SDSL, VDSL2 and VOIP (S/P & H.248)
- 10G Ethernet Uplinks to Provide Non-blocking Network Interfaces
- Comprehensive QoS to Enhance Triple Play Users' Experience (S/R, WRR)
- Field Proven IGMP v1, v2 Snooping and Proxy for IPTV Deployment (S/R Multicast Groups)
- Flexible ACL, VLAN-aware DHCP and Anti-IP/MAC Address Spoofing to Prevent Malicious Attack
- DHCP Option 82 and PPPoE EA Features Support Versatile IP Address Assignment



12.5U High Capacity Multi-Service Access Node
IES-6000



[You're reading an excerpt. Click here to read official ZYXEL IES-6000 user guide](http://yourpdfguides.com/dref/2433877)
<http://yourpdfguides.com/dref/2433877>

Manual abstract:

Easy & Reused Logistics The IES-6000 is a 12.5 U-height, 17-slot chassis-based multi-service access node capable of adopting the same line cards as those for IES-5005/5000 systems. The MSC1024G control card with eight 1G uplinks is designed to plug into slot 8 and/or slot 9, while the remaining slots are available for equipping various line cards. The new MSC1224G control card is with two 10G and six 1G Ethernet uplinks to support even larger bandwidth requirement. The variety of line cards are including 48-port or 72-port ADSL2+ line cards that provide subscribers with asymmetric transmission bandwidth up to 25 Mbps/2.4 Mbps; 48-port SHDSL.bis line cards with symmetric transmission bandwidth of 5.69 Mbps per port; 24-port and 48-port VDSL2 line cards that offer up profile 17a (100 Mbps/45 Mbps) high-speed connectivity per port over copper wires; 48port VoIP line card that supports either H.248 or SIP protocol and 20-port fiber-based Fast Ethernet line card that supports 100 Mbps transmission speed per port. @@@@Second-level accounts have similar access rights except creating new administrative accounts, while the third-level accounts are granted read-only access rights to the MIB objects.

NetAtlas Access EMS also provides view-based MIB management that partial MIB objects can be defined and accessed for customization and security reasons. In addition, Cluster Management enables multiple DSLAM administration with single/master IP address, XML-based northbound interface is equipped to interoperate with external OSS systems. Specifications System Specifications DSL Compliant · ADSL: - G.992.1 Annex A, G.992.3 Annex A, G.992.5 Annex A - G.992.

1 Annex B, G.992.3 Annex B, G.992.5 Annex B Support G.992.3 and G.992.5 Spectral Mask Support Annex M and Annex L in G.992.

3 and G.992.5 Support EOC and Overhead Channel Access Support the latency path function Support loop diagnostic function specified Support the power management capability Support the capability of the Seamless Rate Adaptation (SRA) on-line configuration Single and Dual end loop test G.998.1 port bonding · SHDSL: G.991.2, G.991.2.bis, G.998.1 · VDSL2: G.993.2, G.994.

I, G.997.1 ······ Rule-based packet filtering (L2 ~ L4 ACL) MAC count limiting ARP broadcast filtering DHCP broadcast filtering VLAN aware DHCP snooping NetBIOS filtering IGMP filtering Anti IP/MAC address spoofing Support TACACS+ remote authentication · RTCP (RFC 1890) · FAX/Modem pass through (T.38) via RTP · Tone detection and generation (bi-directional)RFC2833 RTP Payload for DTMF · Echo cancellation and auto gain control (G.165, G.

168) · VAD (voice activity detection) · CNG (comfort noise generation) · Caller ID generation and detection · Supplementary services · Local dial available · Emergency call local route* · Do not Disturb · Selective/Anonymous call rejection · Call waiting · Call transfer (blind and attended transfer) · Call return and call back on busy · Off hook warning tone VLAN · 4094 IEEE 802.1Q compliant VLAN tagging · VLAN stacking (Q-in-Q) · VLAN Bridge Function (multiple PVCs to one VLAN)(N:1) · PVC and VLAN one to one mapping (1:1) · VLAN Trunking (Single PVC join Multiple VLAN)(1:N) · Support GVRP function Network Management Traffic Management · Bandwidth control and Broadcast/Multicast/ Unknown Unicast control on Gigabit Ethernet ports · RSTP: IEEE 802.1d, IEEE 802.1w, IEEE 802.1s · IP Bridge · IEEE 802.3ad (Link Aggregation Control Protocol) · IP multicast forwarding · IGMP v1, v2 snooping/proxy · IGMP multicasting channel limiting · VLAN aware DHCP snooping · DHCP Relay Option 82 with Sub-option 1 & 2 · TR-101 compliant PPPoE intermediate Agent · Multicast bandwidth control · L2 ~ L4 ACL · IGMP group count/filtering profile Local management through a craft terminal Web-based Management Interface Cluster Management (Up to 8 cluster members) View-based Network Management Support XML-based North Bound Interface NetAtlas Access EMS · In-band and out-of-band IP interface for management (SSH, SFTP) · SNMP Management (through ZyXEL NetAtlas Access EMS) - SNMPv1/v2c/v3 agent/traps - Standard MIBs RFC 1213 MIB II ADSL Line MIB (RFC2662)/Extension Line MIB (RFC 3440) SHDSL Line MIB (RFC 3276) VDSL line MIB (RF3728) Bridge MIB/Extension MIB RMON MIB (RFC 1757) - Vendor specific MIBs, e.g., Chassis Management MIB (Fan Speed, Voltage, Temperature) · · · · ATM Traffic Management · Support 8 PVC per DSL port · Support UBR, CBR, rt-VBR, nrt-VBR, QoS Mechanisms · Support ATM Forum TM 4.0 peak cell rate traffic parameter · Support downstream traffic shaping function per ATM PVC · Support ATM F5 OAM cells for End-to-End Loop back test (ITU-T Rec. I.

610) Performance · Eight queues with packet priority scheduling (SPQ, WRR) · Support 512 IGMP multicast groups · The maximum channel zapping processing time is 250 ms · DSCP to 802.1p mapping VoIP Features · Codes: G.711, G.726, G.729a/b, G.723.1 · Network signaling protocols: ITU-T H.248 v2, SIP v2 (RFC3261) · RTP (RFC 1889) Security · Per Port and Per VLAN isolation · IEEE 802.1x (Authentication) Hardware Specifications IES-6000M · 17-slot rack mountable enclosure, 19" or 23" chassis · Maximum 16 slots for DSL line cards (slot 1 ~ 7, 8 or 9, 10 ~ 17) · 2 slots for management and switch cards (slot 8 & 9) · 2 DC power input module and filter · One FAN and dust filter module · One Alarm Module · Support UPBO and DPBO, Reed Solomon and Trellis coding · Support ADSL fall back with ADSL/ADSL2/ADSL2+ CPE in Annex A, M, L modes · Support IEEE 802.1ag Connectivity Fault Management (CFM) Physical Specifications IES-6000M · Dimensions: 439.

2 (W) x 280.5 (D) x 543.3 (H) mm · Weight: 15 Kg ALC1272G-51 · Dimensions: 390.6 (W) x 240 (D) x 13.8 (H) mm · Weight: 0.

7 Kg ELC1220G-55 · Support 20 open slots for Fast Ethernet SFP (100BASE-FX/BX/LX/EX) · One mini-RJ-11 console · Aggregates layer-2 traffic from Fast Ethernet subscribers to the chassis system · Support Multicast VLAN, IGMP Snooping, IGMP Filter and Static Multicast functions for MoD services · Support DHCP Relay, Option82 and Snooping functions · Support ACL, Anti-IP Address Spoofing and AntiMAC Address Spoofing security functions ALC1248G-51 · Dimensions: 390.6 (W) x 240 (D) x 13.8 (H) mm · Weight: 0.5 Kg ALC1248G-51/ALC1272G-51 · Hot swappable 48-port/72-port ADSL2/ADSL2+ Annex A line card · Maximum transmission rate up to 25 Mbps/ 2.



[You're reading an excerpt. Click here to read official ZYXEL](http://yourpdfguides.com/dref/2433877)

[IES-6000 user guide](http://yourpdfguides.com/dref/2433877)

<http://yourpdfguides.com/dref/2433877>

4 Mbps for ADSL2+ · One mini-RJ11 console port · One gigabit backplane · Support G.992.3 and G.992.5 Spectral Mask · Support EOC and Overhead Channel Access defined in G.992.3 and Rec.G.997.1 · Support the latency path function specified in G.992.

3 and G.992.5 · Support Annex L and Annex M specified in G.992.3 and G.992.5 · Support loop diagnostic function specified in G.992.3 and G.992.5 · Support the power management capability specified in G.992.3 and G.992.5 · Support the capability of the Seamless Rate Adaptation (SRA) on-line configuration specified in G.

992.3 and G.992.5 · Support ADSL2+ 2-port bonding (G.998).

1) ALC1248G-53 · Dimensions: 390.6 (W) x 240 (D) x 13.8 (H) mm · Weight: 0.5 Kg SLC1248G-22 · Dimensions: 390.6 (W) x 240 (D) x 13.8 (H) mm · Weight: 0.5 Kg VLC1324G-51/VLC1324G-53 · Dimensions: 390.6 (W) x 240 (D) x 13.8 (H) mm · Weight: 1 Kg MSC1024G/MSC1224G · Failover-enabled Network Termination Card · Embedded 48G, non-blocking full duplex switching fabric · MSC1024G supports eight 1G Ethernet uplink & subtending ports: - 4 optical fiber port (SFP modules) for uplink traffic aggregation - 2 100/1000Base-Tx interface module for subtending - 2 1000 Mbps interface modules (combo design, SFP + copper) for dynamic adjustment about subtending and uplink aggregation, depending on the practical deployment requirement · MSC1224G supports two 10G (XFP) and six 1G uplink/subtending interfaces: - 2 optical fiber port (SFP modules) for uplink traffic aggregation - 2 100/1000Base-Tx interface module for subtending - 2 1000 Mbps interface modules (combo design, SFP + copper) for dynamic adjustment about subtending and uplink aggregation, depending on the practical deployment requirement · One RS232 (DB-9) serial console port · One 10/100M out-of-band Mgmt interface · 16 Gigabit Ethernet (SerDes) backplane interface · 16K MAC addresses · 512 L2 multicast groups (1K scalability) · 4K VLANs VLC1348G-51 · Dimensions: 390.6 (W) x 240 (D) x 13.

8 (H) mm · Weight: 1.3 Kg ELC1220G-55 · Dimensions: 390.6 (W) x 240 (D) x 13.8 (H) mm · Weight: 0.5 kg MSC1024G · Dimensions: 390.6 (W) x 240 (D) x 13.8 (H) mm · Weight: 0.6 Kg MSC1224G · Dimensions: 390.6 (W) x 240 (D) x 13.8 (H) mm · Weight: 0.8 Kg ALC1248G-53 · Hot swappable 4All other brands, product names, or trademarks mentioned are the property of their respective owners. .



[You're reading an excerpt. Click here to read official ZYXEL](#)

[IES-6000 user guide](#)

<http://yourpdfguides.com/dref/2433877>